


Magnetic Resonance in Porous Media 2026



Goupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

PROCEEDINGS



RIBEIRÃO PRETO & CAMPINAS, BRAZIL

OCTOBER 26–30, 2026

Proceedings of the 17th
International Bologna
Conference on Magnetic
Resonance in Porous
Media

Ribeirão Preto & Campinas

Brazil

2026

Cataloging Record

17th International Bologna Conference on Magnetic Resonance in Porous Media

CATALOGING-IN-PUBLICATION DATA

Preliminary Version - Disclaimer

This version of the Conference Proceedings is preliminary and should not be regarded as the official publication. The final version will be prepared following the conclusion of the conference and will include only abstracts corresponding to contributions that have been formally presented during the event. Figures and graphical elements are also provisional and may be revised or further refined prior to the official release.

RESPONSIBILITY FOR CONTENT

The authors are solely responsible for the content of their respective contributions, including the information, statements, and conclusions presented.

Sponsors & Support

17th International Bologna Conference on Magnetic Resonance in Porous Media

SPONSORSHIP

PLATINUM



GOLD



Groupeement
AMPERE



SILVER



ISMAR

BRONZE



SUPPORT



USP



FDRP / USP



IFSC / USP



CNPq



AUREMN



CAPES



CNPEM
Brazilian Center for Research
in Energy and Materials

CNPEM



Brazil InterPore



FAFQ



FUSP



FAPESP

ACKNOWLEDGEMENTS



Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

ORAL PRESENTATIONS

60 ABSTRACTS / 6 THEMATIC AREAS

01 AREA 01

12 PAPERS

Digital Porous Media & NMR 1

- An Overview of SIRIUS, the Brazilian 4th Generation Synchrotron Light Source 2
- Bridging Digital Porous Media and NMR 3
- Dual high-field NMR approach to oil-water quantification in porous rocks 4
- Dual-Scale Simulation of NMR Responses in Chalk 5
- Estimating surface relaxivity as a function of pore size via conditional diffusion models 7
- Magnetic resonance imaging of acid-induced wormholes in carbonate rock: three-dimensional morphology and its control on flow capacity 8
- MOGNO Beamline and Applications in Porous Materials 10
- Origin and key figures behind Bologna MRPM conference 11
- Physics-Based Multiscale Modeling of Coal Swelling from NMR Cryoporometry to Reservoir Injectivity 12
- Study of the effect of porosity on transport properties in carbonate reservoirs using the Lattice Boltzmann Method 13
- Towards a connection between geometry, phase transition and relaxation in mesoporous materials 14
- Using Approximate Bayesian Computation (ABC) to analyze uncertainties in relaxometry experiments and their consequences in permeability estimation. 15

02 AREA 02

14 PAPERS

NMR Methods & Instrumentation 16

- CO₂-hydrate formation and dissociation study using an innovative NMR probe at low field. 17
- Development of a benchtop high-resolution Magic Angle Spinning NMR 18
- Development of NMR methodologies for the characterization of source rocks from unconventional oil and gas reservoirs. Applications in the Vaca Muerta formation. 19

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

ORAL PRESENTATIONS

60 ABSTRACTS / 6 THEMATIC AREAS

02

AREA 02 / CONTINUED

14 PAPERS

NMR Methods & Instrumentation

16

- Diffusion coefficient measurements for moving samples under strong magnetic field gradients 21
- Dipolar-Based Low-Field TD-NMR: From Soft Matter to Porous Media 23
- EPR and DNP-MRI of Sandstones 24
- Fluid transfers through versatile dynamic NMR relaxometry 25
- Frequency domain NMR Relaxometry: the relevance of time scale and noise in data fitting 26
- Localization-driven exchange contrast in diffusion exchange spectroscopy 27
- Low-Field NMR Relaxometry System Solutions: Rapid Quantification of Pore and Fluid Properties in Porous Media 29
- Magnetic Resonance Pore Imaging with Extended Echo Times and Cartesian q-Space Mapping 30
- Probing the interaction between a MOF and the CO₂ using ultra-high field NMR 32
- Robust Methods and Durable Devices for NMR in Harsh, Non-laboratory Conditions 33
- Understanding NMR Signal Behavior Under Sample Motion: Implications for Logging While Drilling Operations 34

03

AREA 03

11 PAPERS

Human Health, Environmental Science, Food, and Biomaterials

35

- A Low-Field MRI scanner for Multimodal Preclinical Imaging: Gamma detected-MRI 36
- Characterization of 3D-Printed Biomimetic Scaffolds by Low-Field NMR: Relaxation and Diffusion Studies in Soft Porous Media 37
- Climate change: the science, impacts, and mitigation strategies 39

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

ORAL PRESENTATIONS

60 ABSTRACTS / 6 THEMATIC AREAS

03

AREA 03 / CONTINUED

11 PAPERS

Human Health, Environmental Science, Food, and Biomaterials

35

- CNPEM, a Unique Laboratory in Latin America 40
- CO₂ Storage Strategies in the Oil Sector – Perspectives in Petrobras 41
- Determining the Crystallite Size of Organic Solids with ¹H NMR T₁ Relaxation 42
- Diffusion Dynamics in Axons and the understanding of diffusion MRI in Brain 43
- Diffusion MRI in cerebral small vessel disease: characterization of longitudinal microstructural decline with advanced markers 44
- Low-Field NMR Relaxometry for GAG Assessment: A Multimodal Investigation of Articular Cartilage 46
- Magnetic Resonance and Magnetic Resonance Imaging with a Variable Field Cryogen Free Superconducting Magnet 48
- The Pore Size of PLGA Bone Implants Determines the De Novo Formation of Bone Tissue in Tibial Head Defects in Rats 49

04

AREA 04

10 PAPERS

Natural and Artificial Porous Media & Cultural Heritage

50

- Application of Proton Time-Domain NMR to Investigate Water Distribution and Pore Structure Development in Low-Carbon Cements 51
- Capabilities of the Powder X-ray Diffraction Beamline (PAINEIRA) at SIRIUS for Structural Characterization of Porous Materials 53
- Characterization of magnetic rocks: a challenge for NMR 54
- Combined quantitative ¹H, ²³Na and ³⁵Cl NMR to study the salt crystallization of NaCl-NaNO₃ mixtures in sandstone during drying 55
- Development of Portland Cement Binders with Low CO₂ Footprint Utilizing Solid-State NMR spectroscopy 57

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

ORAL PRESENTATIONS

60 ABSTRACTS / 6 THEMATIC AREAS

04

AREA 04 / CONTINUED

10 PAPERS

Natural and Artificial Porous Media & Cultural Heritage

50

- Enhancing magnesium mineral carbonation in Western Australia for sustainable carbon storage **58**
- Monitoring the Hydration of Brazilian Commercial Cements Using Low-Field NMR **59**
- Reducing CO₂ Emissions in the Cement Industry **60**
- Soil Pore Size Distribution and Water Retention Curves by Low-Field NMR **62**
- Soil Strategic Role in Global Food Production and CO₂ emissions mitigation **64**

05

AREA 05

6 PAPERS

Mobile NMR

65

- 3D printed passive shims for permanent magnets: Application to iron-pole, Halbach arrays, and a unique tilted field magnet **66**
- Compact and Mobile NMR **67**
- Drug-Assisted Network Formation in Biopolymeric Wound Dressing Membranes Revealed by Single-Sided and Benchtop NMR **68**
- Facility-scale NMR studies of complex mining tailing materials **70**
- Probing Solid-Liquid Separation Dynamics in Anaerobic Digestate via 1D and 2D Low-Field NMR Relaxometry **72**
- Single-Sided NMR Relaxometry and Diffusometry Across Porous Media Applications **73**

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

ORAL PRESENTATIONS

60 ABSTRACTS / 6 THEMATIC AREAS

06

AREA 06

7 PAPERS

Advances in Mathematics, Engineering, AI, and Quantum Computing

75

• A compative study of effective surface relaxation estimation using two NMR relaxometry inverse modeling approaches	76
• A Two-Stage Galerkin Physics-Informed Neural Network Approach for Forward and Inverse Nuclear Magnetic Resonance Modeling at the Pore Scale	77
• Categorical Diversity Optimization: A framework for inversion and component analysis of NMR data	78
• Mapping local foam mobility in porous media from computed tomography data	80
• Microfluidics as a Tool to Study Pore-Scale Phenomena in Complex Multiphase Flow in Porous Media	81
• Quantum Computing and Porous Media: Applications in CO ₂ Capture & Storage	83
• Quantum Computing Applied to Oil & Gas Problems	84

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

POSTER PRESENTATIONS

41 ABSTRACTS / 6 THEMATIC AREAS

01 AREA 01

8 PAPERS

Digital Porous Media & NMR

85

- Bayesian framework for inverse modeling in estimating porous media properties from Nuclear Magnetic Resonance signals 86
- Computational toolkit for simulating the Nuclear Magnetic Resonance response of porous media 88
- Evaluating Magnetic Surface Relaxivity through NMR Simulations in Digital Porous Media 89
- Exploring the preasymptotic regime in synthetic rocks coated by goethite 90
- Permeability Estimation in Heterogeneous Pre-Salt Carbonates: A Multicomponent Model Based on NMR T_2 Distributions from Well Logs 91
- Spectral parameters of the T_2 distribution for heterogeneity characterization and permeability estimation in carbonates by NMR 92
- Study of NMR T_2 Relaxation Time and Electrical Resistivity Correlation by Numerical Simulations in Synthetic Porous Media Under Variable Saturation and Wettability Conditions 94
- Water mobility during gypsum hydration and drying: Relationships with hydration kinetics and mechanical strength assessed by low-field NMR 96

02 AREA 02

17 PAPERS

NMR Methods & Instrumentation

98

- Adsorption Kinetics and isotherms by TD-NMR 99
- Bicontinuous Microemulsions as Dynamic Nanostructured Media: Composition-Dependent Molecular Dynamics Probed by FFC-NMR Relaxometry 101
- Development of a Rheo-NMR instrument to study dynamical material properties 103
- Dipolar-Filtered Magic Sandwich Echo: A Self-Normalized Approach for NMR Cryoporometry of Mesoporous Materials 104

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

POSTER PRESENTATIONS

41 ABSTRACTS / 6 THEMATIC AREAS

02

AREA 02 / CONTINUED

17 PAPERS

NMR Methods & Instrumentation

98

- Direct Determination of Pore Size Distribution from Multi-Temperature MR Relaxation Measurements **106**
- Effects of Temperature-Dependent Surface Relaxivity on Variable-Temperature NMR Pore Size Measurements **107**
- Electromagnetic Design and Optimization of a Quadrature RF Probe for Single-Sided NMR at 13 MHz **109**
- FFC-NMR STUDY OF WATER-PROTEIN DYNAMICS IN DAIRY PRODUCTS WITH AN INVERSION-DEDICATED TOOL **110**
- Improving NMR Cryoporometry with Octamethylcyclotetrasiloxane **112**
- Kinetic study of rehydration of C-S-H dehydrated by means of water mobility and change in the microporos **113**
- Magnetic Resonance Pore Imaging using Simple Echo Pulse Sequences **115**
- Monitoring Water Populations During White Cement Hydration Using NMR Relaxometry and Dipolar NMR **116**
- NMR and High-Resolution imaging on the MOGNO Beamline for dynamic system analysis on Porous Media **118**
- Open-Access Web Application for Inverse Laplace Transform Processing of Time Domain NMR Signals **120**
- Quantifying Inter-pore Exchange in Complex Porous Media: A T₂-Filtered NMR Study from Reservoir Rocks to Bioactive Glasses **122**
- Study of Local Environments in Crystalline and Glassy Framework Materials by Solid-State NMR **124**
- Understanding the role of cellulose ether in water retention and hydration process of cementitious tile adhesive using NMR analysis **126**

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

POSTER PRESENTATIONS

41 ABSTRACTS / 6 THEMATIC AREAS

03

AREA 03

2 PAPERS

Human Health, Environmental Science, Food, and Biomaterials

128

- Solid-state NMR study of species confined into the nanopores of porous carbon materials **129**
- Study on Human Bone Samples Using Acoustography **131**

04

AREA 04

7 PAPERS

Natural and Artificial Porous Media & Cultural Heritage

133

- Darcian and non-Darcian gas permeametry as a transport-based probe of carbonation in cement-based porous media **134**
- Fabrication of Artificial Carbonate Porous Media: A Comparison between Powder Compaction and Additive Manufacturing **135**
- Factors Influencing Pore Structure Changes in Purple- clay (Zisha) Ceramics: A Comparative Study Using ^1H NMR Relaxometry and Mercury Intrusion Porosimetry **137**
- Oleogel assembly and application: from a porous-media characterization to a biofertilizer technology **139**
- Two-Photon Confocal Microscopy for Simultaneous Three-Dimensional Characterization of Pore Architecture and the Spatial Distribution of Aromatic Molecules in Sedimentary Porous Rocks **141**
- Water Absorption and Dynamics in 11th Century Wall Paintings: Assessing Surface Treatments via NMR Profiling **143**
- Water dynamics and structural evolution in silicate- based porous media: from solutions to colloidal gels probed by dynamic NMR relaxometry **145**

Summary

17th International Bologna Conference on Magnetic Resonance in Porous Media

POSTER PRESENTATIONS

41 ABSTRACTS / 6 THEMATIC AREAS

05 AREA 05

3 PAPERS

Mobile NMR

147

- Designing and Shimming Halbach Array Magnets: A Historical Perspective with Modern Implications 148
- Revisiting Shim-a-Ring Magnets for Improved B Homogeneity 149
- TD-NMR in Semicrystalline Polymers: Morphology and Dynamics 150

06 AREA 06

4 PAPERS

Advances in Mathematics, Engineering, AI, and Quantum Computing

152

- Acoustic Techniques for Porosity Analysis in Petroleum Reservoir Sandstones 153
- An NMR Platform for Quantum Computing 155
- Deep Learning Analysis of T₁-Weighted MRI for Characterizing Vertebral Fragility 157
- Ugly Cat, a computational system for Quantum Information processing based on NMR 159

AUTHOR INDEX

161

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE


17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

01

Digital Porous Media & NMR

ORAL PRESENTATIONS



RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26-30, 2026

An Overview of SIRIUS, the Brazilian 4th Generation Synchrotron Light Source

Helio Cesar Nogueira Tolentino¹

¹Brazilian Center for Research in Energy and Materials (LNLS)

e-mail: helio.tolentino@lnls.br

SIRIUS is the synchrotron light source of Centro Nacional de Pesquisa em Energia e Materiais (CNPEM), operated by the Brazilian Synchrotron Light Laboratory (LNLS). It is a 3 GeV diffraction-limited storage ring designed to deliver highly brilliant, stable, and coherent X-ray beams to a diverse suite of beamlines dedicated to imaging, scattering, spectroscopy, and time-resolved experiments. This contribution presents an overview of the facility, its design principles, and its experimental capabilities, highlighting opportunities enabled by multiscale and in situ/operando approaches. Particular attention is given to research on porous and heterogeneous materials, where synchrotron X-ray methods provide strong complementarity to Magnetic Resonance techniques by accessing pore architecture, structural and chemical heterogeneity, interfaces, and their evolution under realistic conditions. Together, these capabilities position SIRIUS as a platform for integrated, cross-scale studies of complex materials and transport processes.

Bridging Digital Porous Media and NMR

Christoph Arns¹, Igor Shikhov², Rupeng Li²

¹University of New South Wales (*Minerals and Energy Resources Engineering*) , ²University of New South Wales (*School of Minerals and Energy Resources Engineering*)

e-mail: c.arns@unsw.edu.au

NMR relaxation measurements provide powerful, non-invasive probes of porous media microstructure, yet their interpretation remains challenging due to the complex interplay of surface relaxation, diffusion coupling, internal magnetic field gradients, and heterogeneous relaxation regimes. Traditional interpretation frameworks rely on simplifying assumptions that often break down in realistic reservoir rocks. This presentation demonstrates how integrating high-resolution imaging with physics-based forward modeling enables robust extraction of intrinsic physical properties and advanced interpretation of NMR responses.

A workflow is presented combining micro-CT imaging, random walk simulations, and Bayesian optimization to bridge the gap between digital rock physics and NMR petrophysics. Random walk algorithms on high-resolution segmented images naturally incorporate structural heterogeneity and diffusive motion without limiting assumptions. This enables quantitative assessment of effects like diffusion coupling between different relaxation regimes and the influence of internal gradients at varying field strengths.

Applications are illustrated for Bentheimer sandstone using a Bayesian optimization framework. First, NMR T2 relaxation measurements are matched by simulation and surface relaxivity of quartz and effective relaxation and effective diffusion properties of clay regions are simultaneously extracted. Second, the framework is applied to dual T1 and T2 relaxation measurements extracting 5 parameters and extended to T2 measurements at two different temperatures, extracting surface relaxivities, effective clay relaxation times and effective diffusion coefficients significantly. Finally, I will discuss an analysis of internal gradient effects and microstructure distributions on an artificial “soil” sample at full and partial saturation.

Acknowledgements

Open Access funding enabled and organized by CAUL and its Member Institutions. This work was supported by the Australian Research Council through ARC discovery projects DP200103548 and DP240100378. Computational resources were provided by the Australian Government under the National Computation Merit Allocation Scheme (grant m65).

References

R. Li, I. Shikhov, C.H. Arns, *Phys. Rev. Appl.* 15 (5), 054003 (2021)

R. Li, I. Shikhov, C.H. Arns, *Water Resources Research* 58 (9), e2021WR031590 (2022)

C.H. Arns & I. Shikhov, *New Developments in NMR: NMR in Plants and Soils* 37, 58-84 in “New Developments in NMR: NMR in Plants and Soils”, Royal Society of Chemistry, 2025

Dual high-field NMR approach to oil-water quantification in porous rocks

Mariana Teixeira de Azevedo¹, Alexsandro dos Santos Evangelista da Cruz², Alexandre Martins Souza¹, Roberto Sarthour¹, Moacyr Nascimento³, Ivan S. Oliveira¹

¹Brazilian Center for Research in Physics, ²Brazilian Center for Research in Physics (COMAN), ³Centro de Pesquisa, Desenvolvimento e Inovação Leopoldo Américo Miguez de Mello

e-mail: marianateixeiraa99@gmail.com

The oil industry plays a pivotal role in identifying promising exploration areas to enhance hydrocarbon recovery and reduce drilling costs. Although much effort has been made to achieve these goals, the success rate still remains significantly below the desired one and, in some cases, a success of 20 % has been reported. In this context, high-field nuclear magnetic resonance imaging has attracted growing interest for being noninvasive, possessing a high signal-to-noise ratio, and enabling oil and water identification in porous rocks [1]. In this work, we produced microporous rocks with grain sizes in the range of 75-125 μm , 150-212 μm , 250-300 μm for oil and water saturation in different fractions. The spectra showed consistently two broad peaks for water (≈ 0.5 kHz) and oil (≈ 1.0 kHz), enabling chemical shift contrast. From this, we could spatially resolve water and oil, obtaining information on fluid conformation. Signal decay experiments were undertaken using the CPMG pulse sequence protocol. We observed that the water signal decays faster than the oil signal, allowing relaxation imaging-based contrast. T2-weighted imaging was employed using the RARE protocol. From the signal segmentation and pixel counting, we could quantify oil and water fractions across 100 rock samples for comparison with known fluid saturation volumes. Our protocol allowed an error of less than 12 % for all samples. These findings suggest that magnetic resonance imaging can serve as a complementary logging tool for well analysis.

Acknowledgements

This study was financed by Petrobras

References

Teixeira de Azevedo, M., S. E. Cruz, A., M. Souza, A. et al. Dual High-Field NMR Approach to Oil-Water Quantification in Porous Rocks. *Appl Magn Reson* 57, 29 (2026). <https://doi.org/10.1007/s00723-026-01845-9>

Dual-Scale Simulation of NMR Responses in Chalk

Christoph Arns¹, Igor Shikhov²

¹University of New South Wales (*Minerals and Energy Resources Engineering*) , ²University of New South Wales (*School of Minerals and Energy Resources Engineering*)

e-mail: c.arns@unsw.edu.au

Dual-Scale Simulation of NMR Responses in Chalk

Chalk formations constitute important targets for CO₂ geological storage in depleted oil fields, yet their complex pore networks spanning nanometer to micron scales pose significant challenges for NMR characterization. Understanding how internal magnetic field gradients and multi-scale porosity heterogeneity influence relaxation responses is essential for reliable interpretation of NMR measurements in these formations. This presentation details a sophisticated dual-scale numerical simulation approach designed to capture these effects in chalk microstructure.

The simulation methodology combines micro-CT imaging at 3.62 μm resolution with Gaussian Random Field (GRF) reconstruction of nano-CT data at 64 nm resolution. The micro-CT image is segmented into three phases: resolved macroporosity (vugs), intermediate unresolved porosity, and semi-solid inclusions. The GRF approach enables periodic generation of the fine-scale microporosity, matched to experimental nano-CT images through two-point correlation functions. This dual-scale representation is utilized by a random walk algorithm where the microstructure is generated on-the-fly rather than storing the complete high-resolution volume. The internal fields are computed using dual-scale FFT methods, capturing both fine-scale heterogeneity within microporosity and long-range gradients from larger-scale susceptibility variations.

Results demonstrate significant effects of paramagnetic inclusions on T_2 relaxation distributions. Even at low field strength (2 MHz), moderate inclusion fractions with susceptibility contrasts of up to 0.01 SI produce significant distribution shape changes. CPMG simulations at multiple echo spacings (0.1-1.0 ms) reveal the echo-spacing dependence of gradient refocusing, distinguishing fine-scale from large-scale internal field effects, and enabling quantitative assessment of their relative contributions to observed relaxation behaviour.

Acknowledgements

Open Access funding enabled and organized by CAUL and its Member Institutions. This work was supported by the Australian Research Council through ARC discovery projects DP200103548 and DP240100378. Computational resources were provided by the Australian Government under the National Computation Merit Allocation Scheme (grant m65).

References

Arns, C.H., AlGhamdi, T. and Arns, J.Y. (2011). Numerical analysis of nuclear magnetic resonance relaxation-diffusion responses of sedimentary rock. *New Journal of Physics* 13(1), 015004.

Cui, Y., Shikhov, I. and Arns, C.H (2022). NMR Relaxation Modelling in Porous Media with DualScaleResolved Internal Magnetic Fields. *Transport in Porous Media* 142(), 453-474.

Rybin, I., Shikhov, I. and Arns, C.H. (2022). Lattice Boltzmann framework for accurate NMR simulation in porous media. *Physical Review E* 105(5), 055304.

Estimating surface relaxivity as a function of pore size via conditional diffusion models

Alexsander Marciano da Cunha¹, Luiz Fernando Bez¹, Pedro Cortez Fetter Lopes², Ricardo Leiderman², Andre Maues Brabo Pereira²

¹Universidade Federal Fluminense (*Scientific Computing Lab - LCC*) , ²Universidade Federal Fluminense (*Departamento de Ciência da Computação*)

e-mail: amarciano@id.uff.br

Pore size distribution is a fundamental deliverable of Nuclear Magnetic Resonance (NMR) for reservoir rock characterization. Typically, it is determined in the fast diffusion regime via the surface-to-volume ratio and surface relaxivity (ρ). Although conventional methods rely on a uniform relaxivity assumption, it is highly unlikely that heterogeneous sedimentary rocks exhibit uniform mineralogy across all pore surfaces (Keating and Knight, 2012). To investigate how ρ varies as a function of pore size, we adopt an inverse problem framework (Benavides et al., 2017) to recover the relaxivity function whose corresponding simulated T2 distribution best matches the ground truth T2 distribution. Because standard iterative inversion frameworks require computing forward NMR simulations at each step, they may be computationally prohibitive. To overcome this limitation, we employ generative conditional diffusion models to solve the inverse problem using a data-driven approach. The model takes a rock sample's microstructure image and its experimental T2 distribution as inputs to predict the underlying relaxivity function. To build a robust training dataset, we adopted a sigmoid prior assumption for the relaxivity functions and utilized an in-house Random Walk (RW) simulator to generate the transversal NMR relaxation signals. Importantly, since the total number of wall collisions of a walker in an RW simulation correlates with the local pore size, we parameterize ρ as a function of the collision count rather than mapping it directly to complex pore coordinates. Tested on synthetic data, the proposed framework successfully reconstructed the non-uniform relaxivity functions, providing a significantly better match to the reference T2 distributions than the uniform relaxivity assumption and demonstrating high potential for accurate porous media characterization.

References

- Benavides, F., Leiderman, R., Souza, A., Carneiro, G., & Bagueira, R. (2017). Estimating the surface relaxivity as a function of pore size from NMR T2 distributions and microtomographic images. *Computers & Geosciences*, 106, 200-208. <https://doi.org/10.1016/j.cageo.2017.06.016>
- Keating, K., & Knight, R. (2012). The effect of spatial variation in surface relaxivity on nuclear magnetic resonance relaxation rates. *Geophysics*, 77(5), E365-E377. <https://doi.org/10.1190/geo2011-0462.1>

Magnetic resonance imaging of acid-induced wormholes in carbonate rock: three-dimensional morphology and its control on flow capacity

Pedro Tupã Pandava Aum¹, Lorena Cardoso Batista Aum¹, Cláudio Regis dos Santos Lucas¹, Bernd Uwe Foerster², Fernando Fernandes Paiva², Tito José Bonagamba²

¹Federal University of Pará (*Energy and Petroleum Science Laboratory - LCPETRO*) , ²São Carlos Institute of Physics - University of São Paulo

e-mail: pedroaum@ufpa.br

Matrix acidizing creates dissolution channels (wormholes) whose 3D morphology sets the conductivity a treatment delivers, yet it is usually inferred from breakthrough data rather than measured. We imaged six acidized Indiana limestone plugs by magnetic resonance and used the geometries directly as the computational domain for flow simulation. The plugs came from corefloods at 0.5-5 mL/min with nonionic acid nanoemulsions carrying 15 wt.% HCl. After saturation with deionized water, volumes were acquired at 2 T (Bruker Avance III) with a T2-weighted 3D gradient-echo sequence tuned to water in large voids: TE 15 ms, TR 30 ms, flip 60 deg, FOV 96x48x48 mm³, 200 μ m isotropic, 16 averages, 8 h per plug. Since the signal comes from the saturating fluid, the channel is recovered without contrast agents or a reference scan. A new processing step separates it from the free-water films coating the plug, which hold an order of magnitude more volume. Channels are labelled W1-W6 by decreasing median local thickness (2.38-0.74 mm; tortuosity 1.52-2.23). Three patterns emerge: a wide, sparsely branched dominant channel (W1, W3); a ramified dominant channel with bifurcations, loops and enlarged dissolution regions (W2, W4, W5); and a distributed network (W6) reaching the outlet through three mouths carrying 35/35/30% of the flow. The geometries were meshed and solved with the steady Navier-Stokes equations at ten rates, 0.1-200 mL/min, in both directions (120 simulations). Permeability scales as $d_{50}^{1.94}$, recovering the Poiseuille exponent from the images, and one tortuosity correction predicts it to 15%. Between 13 and 34% of the dissolved volume carries no flow, and the pressure drop is up to 67% higher against the direction of treatment. MRI therefore distinguishes wormhole morphologies while showing only the water-accessible network, and supplies a geometry from which treatment conductivity can be computed.

References

Krebs, M., Lungwitz, B., Souza, A., Pépin, A., Montoya, S., Schlicht, P., ... & Bonagamba, T. (2015). The first visualization of acid treatments on carbonates with 3D nuclear-magnetic-resonance imaging. *SPE Journal*, 20(04), 678-688.

Lucas, C. R. D. S., Aum, Y. K. P. G., Araújo, E. D. A., Castro Dantas, T. N. D., Araújo, E. A., Sousa, T. N., & Aum, P. T. P. (2020). Investigating the fluid-solid interaction of acid nonionic nanoemulsion with carbonate porous media. *Molecules*, 25(6), 1475.

Solcia, G., Foerster, B. U., Andreeta, M. B., Bonagamba, T. J., & Paiva, F. F. (2024). Computational fluid dynamics in carbonate rock wormholes using magnetic resonance images as structural information. *Applied Computing and Geosciences*, 23, 100172.

MOGNO Beamline and Applications in Porous Materials

Nathaly Lopes Archilha¹

¹Brazilian Center for Research in Energy and Materials

e-mail: nathaly.archilha@lnls.br

The MOGNO beamline at the SIRIUS synchrotron is designed to enable fast, high-resolution 3D and 4D imaging using multiscale X-ray micro- and nanotomography. Its optical layout and flexible operation modes allow users to probe materials across a wide range of length scales, combining submicrometric spatial resolution with large fields of view and enabling fast acquisition for time-resolved 4D imaging.

Porous materials benefit significantly from these capabilities, as their performance often depends on complex, multiscale pore networks. MOGNO enables detailed characterization of pore morphology, connectivity, and transport-relevant features across micro- and nanometric domains. Applications include studies in catalysis, energy materials, geology, construction materials, and filtration media. By integrating advanced imaging modalities with robust reconstruction and analysis tools, MOGNO provides a powerful platform for unveiling structure-property relationships in porous systems.

References

<https://iopscience.iop.org/article/10.1088/1742-6596/2380/1/012123>

Origin and key figures behind Bologna MRPM conference

Leonardo Brizi¹

¹Università di Bologna (*Physics and Astronomy*)

e-mail: leonardo.brizi2@unibo.it

The Bologna MRPM conferences grew out of the vision of G.C. Borgia and P. Fantazzini, who in the mid-1980s realized that both petroleum reservoirs and biological materials could be treated as porous media and studied using NMR¹. Building on the early foundational work in the field, they launched a research program in Magnetic Resonance in Porous Media and organized the first MRPM meeting at the University of Bologna in 1990, at a time when only a few groups worldwide were active in this area. The success of that meeting led to the establishment of a distinguished biennial international conference series, which expanded steadily over the years and eventually became part of Groupement Ampère. In recognition of Bologna's central role, the series was formally named the Bologna Conference, and the Giulio Cesare Borgia Award was created to honor his scientific legacy and encourage young researchers. The MRPM community has grown over the years thanks to the active participation of distinguished members from all over the world, who have demonstrated significant scientific activity. Their names can be found in the contributions to the MRPM Proceedings and as members of the organizing and scientific committees. From the long list, it is both a duty and a pleasure to recognize and honor the two great personalities that have passed away, R.J.S. Brown(1924-2019) and Sir P. T. Callaghan(1947-2012), who made great contributions to both the MRPM conferences and developments of MRPM science and applications. In Bologna, the seminal ideas of the founders have grown and continue to flourish in basic research². The most recent achievements regard the development of one- and two-dimensional inversion methods, FFC data analysis, and AI design for MR Fingerprinting, without neglecting applied research covering a wide range of natural and artificial porous materials (biological tissues, corals, rocks, ceramics, cements, etc.) inside homogeneous and inhomogeneous polarizing magnetic fields.

References

<https://www.mrpm2026.com/brief-history>

<https://www.mrpm2026.com/leonardo-brizi-1st>

Physics-Based Multiscale Modeling of Coal Swelling from NMR Cryoporometry to Reservoir Injectivity

Minchuan Jiang¹, Tien Dung Le², Didier. Stemmelen³, Christian Moyne³, Marcio Murad⁴

¹Laboratoire Énergies & Mécanique Théorique et Appliquée) (*Univ Lorraine*) , ²Laboratoire Énergies et Mécanique Théorique et Appliquée), ³Laboratoire Energies et Mecanique Theorique et Applique, ⁴Laboratório Nacional de Computação Científica (*Computational Modeling*)

e-mail: minchuan.jiang@univ-lorraine.fr

Unlike saline aquifers and depleted reservoirs, where CO₂ storage relies primarily on structural and residual trapping within a largely passive rock matrix, coal seams store CO₂ through direct adsorption onto the coal matrix itself, coupling storage capacity directly to the swelling-induced permeability decline. Such a role makes coal seams a mechanistically distinct and comparatively CCS target relative to conventional geological formations.

Accurate characterization of coal pore structure is essential for predicting CO₂ adsorption, transport, swelling, and injectivity loss during carbon capture and storage. NMR cryoporometry and (T₂) relaxometry are used to determine pore-size distributions and surface relaxivity across micro- and mesopore scales. These experimental data are combined with density functional theory calculations to quantify fluid-solid interactions, adsorption-induced stresses, and coal-matrix swelling. The resulting nanoscale constitutive relations are incorporated into a multiscale homogenization framework to derive effective poromechanical and transport properties at the reservoir scale. The integrated model links pore-scale adsorption and solvation forces to cleat closure, permeability reduction, and the progressive decline of CO₂ well injectivity.

References

Jiang, M., Le, T.D., Stemmelen, D. et al. Pore-Size Distribution of Coal Characterized by NMR Relaxometry and Cryoporometry. *Transp Porous Med* 153, 51 (2026).

Quoc D. Ha, Tien D. Le, Irina Panfilov, Christian Moyne, Marcio A. Murad, Upscaling poromechanical models of coalbed methane reservoir incorporating the interplay between non-linear cleat deformation and solvation forces, *International Journal of Solids and Structures*, Volumes 262–263, (2023)

Tien Dung Le, Christian Moyne, Marcio A. Murad, Irina Panfilova, A three-scale poromechanical model for swelling porous media incorporating solvation forces: Application to enhanced coalbed methane recovery, *Mechanics of Materials*, Volume 131, (2019)

Study of the effect of porosity on transport properties in carbonate reservoirs using the Lattice Boltzmann Method

Vladivostok F. S. Mamani¹, Wagner W. R. Araujo¹, Alexsandro Kirch¹, Alvaro Torrez¹,
Caetano Rodrigues Miranda¹

¹Universidade de São Paulo (IFUSP)

e-mail: znarf.vfsm@gmail.com

This work investigates porous media using Digital Rock Physics, a key approach for understanding pore-scale transport in carbonate reservoirs [1]. The objective is to characterize and simulate flow in a digital calcite sample (DRP-252) through a multiscale workflow combining image segmentation (Otsu's method) and Lattice Boltzmann Method (LBM) simulations. The pore geometry was reconstructed from the digital rock image, while the physical properties of the water-decane-butyric acid/calcite system (interfacial tension, density, and viscosity) were obtained from experimental and molecular dynamics data reported in the literature. These properties were mapped into consistent dimensionless LBM parameters and implemented with the explicit-force scheme in the TAXILA-LBM framework [2]. Simulations quantified the influence of pore morphology on flow behavior. An inverse relationship was observed between porosity and tortuosity, with increasing porosity promoting less restrictive flow paths. Absolute permeability showed a nonlinear dependence on porosity, increasing markedly as pore connectivity improved and wall effects decreased. Conversely, low-porosity structures exhibited a sharp permeability reduction due to the closure of critical pore throats, leading to higher tortuosity. Oil recovery efficiency also increased with porosity because more connected pore networks enabled a more uniform displacement process. The extraction rate proved highly sensitive to small porosity variations, demonstrating that subtle structural changes significantly affect recoverable oil volume. Overall, the proposed multiscale framework quantitatively links pore structure to transport properties, showing how porosity governs tortuosity, permeability, and hydrocarbon recovery efficiency in carbonate porous media.

Acknowledgements

This study was financed, in part, by the RCGI, CNPq, FAPESP, ANP and PETROBRAS

References

- [1] Digital Rocks Portal. DRP-252, 2024 <https://digitalrockportal.org/projects/252>.
- [2] Coon ET, Porter ML, Kang Q. Comp. Geosciences 18, 17,2014

Towards a connection between geometry, phase transition and relaxation in mesoporous materials

Georgiy Baroncha¹, Crina Rahause², Rustem Valiullin¹

¹Universität Leipzig (*Felix-Bloch Institute*) , ²Universität Leipzig

e-mail: georgiy.baroncha@uni-leipzig.de

Accurately capturing the full complexity of porous structures, including their topology and structural disorder, remains a central challenge in the study of mesoporous materials. Addressing this challenge requires the use of advanced theoretical approaches that explicitly account for pore-network effects and cooperative phenomena. In this work, we demonstrate how structural information can be extracted from phase transitions occurring within porous materials, including adsorption-desorption and melting-freezing transitions, and identify the key structural parameters governing the shape of the resulting hysteresis loops. We show how pore geometry and spatial correlations between pores affect adsorption and desorption behavior. Furthermore, by analyzing these phase transitions, we predict the transport properties of molecules confined within the material. Finally, we establish a link between melting-freezing behavior and relaxation dynamics in porous structures, demonstrating that relaxation phenomena provide additional opportunities for a more detailed and comprehensive characterization of the internal architecture of porous materials.

References

A. Alzaidi, E. S. Kikkinides, D. Schneider, P. A. Monson, and R. Valiullin, *The Journal of Chemical Physics* 157, 154701 (2022).

G. Baroncha, E. S. Kikkinides, and R. Valiullin, *The Journal of Physical Chemistry C* 129, 21197 (2025).

G. Baroncha, E. S. Kikkinides, T. Paul, D. Poppitz, D. Enke, and R. Valiullin, *ACS Materials* Au 6, 425 (2026).

Using Approximate Bayesian Computation (ABC) to analyze uncertainties in relaxometry experiments and their consequences in permeability estimation.

Arthur Costa Poyares Rocha¹, Luiz Fernando Bez², Daniel Castello³, Andre Alves de Souza⁴,
Andre Maues Brabo Pereira⁵, Ricardo Leiderman⁵

¹Universidade Federal Fluminense (*Ciência da Computação (TCC)*) , ²Universidade Federal Fluminense (*Computer Science*) , ³Universidade Federal do Rio de Janeiro (*Mechanical Engineering*) , ⁴Observatório Nacional (*Coordenação de Geofísica*) , ⁵Universidade Federal Fluminense (*Departamento de Ciência da Computação*)

e-mail: arcosta@id.uff.br

Nuclear Magnetic Resonance (NMR) techniques enable fast and non-destructive characterization of porous media, ideal for laboratory analysis and well logging in the field. Relaxometry is a technique that stands out among the various NMR tools, as it provides accurate measurements of the medium's porosity, as well as an estimation of pore size distributions within it. However, these observations are subject to noise levels and uncertainties inherent to the process. We propose a combination of Approximate Bayesian Computation (ABC) with reduced-order T2 distribution models as a framework for statistical analysis and uncertainty propagation. The T2 time distribution is decomposed as families of gaussian pore size distributions with uncertainty bounds associated with their medium pore size, standard deviation, and relative contribution for the relaxometry experiment. We show that these uncertainties can be propagated using traditional petrophysical correlations, such as the Kenyon model, thus providing upper and lower bounds to permeability estimations.

Acknowledgements

This study was financed, in part, by Coordenação de Aperfeiçoamento de Pessoal de Nível Superior – Brasil (CAPES), Brasil. Process Number 001

References

BEZ, L. et al. Large scale voxel-based fem formulation for NMR relaxation in porous media. *Transport in Porous Media*, v. 151, p. 2405-2430, 08 2024.

Toni, T., Welch, D., Strelkowa, N., Ipsen, A., Stumpf, M.: Toni t, welch d, strelkowa n, ipsen a, stumpf mp. Approximate bayesian computation scheme for parameter inference and model selection in dynamical systems. *Journal of the Royal Society, Interface / the Royal Society* 6, 187-202 (2008)

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

02

NMR Methods & Instrumentation

ORAL PRESENTATIONS



RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26-30, 2026

CO₂-hydrate formation and dissociation study using an innovative NMR probe at low field.

Marc Fleury¹

¹IFP Energies nouvelles (*Earth Sciences and Environmental Technologies*)

e-mail: marc.fleury@ifpen.fr

In the context of CO₂ storage, injectivity is a critical factor and CO₂ hydrate formation in the near-wellbore region can alter petrophysical properties and hinder gas flow. Understanding the mechanisms governing hydrate formation, whether associated with salt precipitation or not, is essential for predicting its impact and defining optimal conditions to prevent its occurrence. This study investigates hydrate formation and dissociation in porous media using Nuclear Magnetic Resonance (NMR) techniques.

Experiments were conducted using an in-house high-pressure Peltier NMR probe, which provides a pressure range of up to 70 bar. The temperature is controlled via a Peltier system, providing temperature control with a precision of about 0.05 °C. This system can achieve a temperature difference of about 30°C below the reference temperature of the cooling bath. Additionally, it allows for slow temperature ramps (as low as 0.1°C/h), which are essential for observing quasi-static hydrate dissociation at constant pressure and for determining thermodynamic equilibrium points (T_{eq} and P_{eq}). The experiments were conducted on small cylindrical samples (5 mm in diameter, up to 20 mm in length), using model porous media as well as various sandstones and carbonates. A typical output of the experiment is the liquid fraction as measured by NMR vs. temperature.

It is well known that hydrate formation can be detected easily in NMR experiments since the T₂ relaxation time becomes very short. Here we focus on the T₁ relaxation to try to distinguish ice from hydrates; with an appropriate NMR instrument, we show that this is possible since hydrate and ice structures have different T₁ relaxation times around 1s. We also studied the kinetics of hydrate formation and dissociation using step temperature variations. Contrary to expectations, the gas water surface area obtained at different water saturations does not influence the kinetics.

References

N. Gland, M. Mascle, T. Chevalier, P. Dehghani, S. Youssef, M. Fleury, A. Estublier, A. Siquin, L. Pauget, CO₂ storage in depleted reservoir: Hydrate risk in the near wellbore region an integrated experimental approach using thermodynamics, NMR and X-Ray measurements, *International Journal of Greenhouse Gas Control* 141 (2025) 104298. <https://doi.org/10.1016/j.ijggc.2024.104298>.

T. Chevalier, M. Fleury, L. Pauget, A. Siquin, 2024. CO₂ Hydrate in Porous Media: A Quantitative NMR Method to Detect Formation, Dissociation, and Localization. *Energy Fuels*, *acs.energyfuels.4c03902*. <https://doi.org/10.1021/acs.energyfuels.4c03902>.

Development of a benchtop high-resolution Magic Angle Spinning NMR

Rodrigo de Oliveira Silva¹, Isabella Maria Riley¹, Aristarchos Mavridis¹, Dimitrios Sakellariou¹

¹Katholieke Universiteit Leuven (M2S/cMACS)

e-mail: rodrigo.deoliveirasilva@kuleuven.be

Over the last fifteen years we have witnessed a dramatic increase in low-field benchtop NMR applications many of which benefited from high spectral resolution. Nowadays, commercial instruments exist offering linewidths better than 0.5Hz on 5mm tube isotropic liquid samples for a variety of Larmor frequencies up to 90 MHz. The compromise to achieve strong field from permanent magnets is reduced free bore diameter. Although recent work to implement magic angle sample spinning have been reported [1, 2], they focused on reducing the anisotropic broadening from dipolar couplings where modest resolution is sufficient.

Here, we present results obtained with a benchtop high-resolution NMR magnet (0.9T) originally built 2010, having a clear bore of 54 mm, which is integrated with standard shim coils and SB liquids and solid-state MAS probes from superconducting NMR magnets. We demonstrate sub ppm high-resolution operation under fast and slow MAS conditions and showcase the potential of this low-cost technology towards democratizing Magic Angle sample Spinning in applications with minimal sample preparation: metabolomics, materials and food science.

References

- [1] Sørensen et al, "Magic-angle spinning solid-state multinuclear NMR on low-field instrumentation", JMR 238, p20-25 (2014).
- [2] K. Xu et al. "High resolution solid-state NMR on the desktop", Sol. Stat. NMR 126, 101884 (2023).

Development of NMR methodologies for the characterization of source rocks from unconventional oil and gas reservoirs. Applications in the Vaca Muerta formation.

Rodolfo Acosta¹, Gerónimo Sequeiros², Manuel Isaac Velasco³, Yamila Garro Linck⁴, Gustavo A. Monti², Esteban A. Domené⁵, Diana M. Masiero⁵

¹Universidad Nacional de Córdoba (FAMAF), ²Universidad Nacional de Córdoba, ³Instituto de Física Enrique Gaviola, ⁴Universidad Nacional de Córdoba, ⁵YPF Tecnología

e-mail: r.acosta@unc.edu.ar

One of the most relevant energy vectors in Argentina's development and economy is the exploitation of hydrocarbons from unconventional reservoirs, such as those found in the Neuquén Basin, particularly Vaca Muerta. Conventional reservoirs are composed mainly of compacted sandstones with high porosity and permeability, whereas shale-type rocks exhibit very low connectivity, requiring hydraulic fracturing for their exploitation. A second major difference is the large amount of solid organic matter present in these reservoirs, known as kerogen, which is the source of hydrocarbon generation. Its characterization and quantification are of paramount importance for evaluating potential productivity and the type of recoverable hydrocarbon. In this talk, we discuss two main issues: the characterization of kerogen maturity, which is an indicator of the production window, which may correspond to oil, gas, or an intermediate phase known as condensate. Rapid methods based on ¹H detection are compared with traditional ¹³C CPMAS measurements. Another technique that is fundamental in the petroleum industry is the determination of fluids contained within the rock; for this purpose, the industry standard involves the use of equipment operating at magnetic fields of 0.05 - 0.5 T. We will present results to overcome limitations for probing both solid and liquid components in shale rocks.

Acknowledgements

This study was financed, in part, by the National University of Córdoba, Argentina. SECYT-UNC (33620180100154CB)

References

Total organic carbon determination by ¹³C CP/MAS solid-state NMR in unconventional oil/gas source rocks: a case study from the Neuquén and Cuyo basins in Argentina, Y. Garro Linck, G. Martinez Delfa, J.A. Donadelli, E.V. Silletta, M.I. Velasco, M.B. Franzoni, G.A. Monti, C. Smal, R.H. Acosta, Energy and Fuels, 38, 5098-5105 (2024)

E.V. Silletta, G. Martinez Delfa, M.I. Velasco, J.A. Donadelli, G.A. Monti, C. Smal, R.H. Acosta, Quantification of imbibed heptane in shale rocks determined by edited T1-T2 NMR

relaxation experiments at high magnetic field, *Energy and Fuels*, 36, 18, 10794-10802 (2022)

E.V. Silletta, G.S. Vila, E.A. Domene, M.I. Velasco, P.C. Bedini, Y. Garro-Linck, D. Masiero, G.A. Monti, R.H. Acosta, Organic matter detection in shale reservoirs using a novel pulse sequence for T1-T2 relaxation maps at 2 MHz, *Fuel*, 312, 122863 (2022)

Diffusion coefficient measurements for moving samples under strong magnetic field gradients

Agide Gimenez Marassi¹, Arthur Gustavo de Araujo Ferreira², Everton Lucas-Oliveira³,
Edson Vidoto², Willian Andrighetto Trevizan⁴, Tito José Bonagamba⁵

¹Universidade de São Paulo (*Instituto de Física de São Carlos*) , ²Universidade de São Paulo,
³Brazilian Center for Research in Energy and Materials (*Brazilian Synchrotron Light
Laboratory (LNLS)*) , ⁴Petroleo Brasileiro SA (*Cenpes*) , ⁵Universidade de São Paulo (*São
Carlos Institute of Physics*)

e-mail: agide@usp.br

Among the numerous measurements carried out during a well-logging procedure, the Nuclear Magnetic Resonance (NMR) assessment is a fundamental analysis for determining the economic viability of a well for the oil industry. [1] Nowadays, two reliable approaches, Wireline Logging (WL) and Logging While Drilling (LWD), stand out. WL comprises the acquisition of NMR data under static conditions. On the other hand, in LWD, NMR measurements occur simultaneously with drilling, while the NMR tool experiences translation, rotation, and vibration relative to the rock formation. To better understand the NMR response acquired under LWD conditions, a setup emulating an LWD tool was developed, consisting of a single-sided magnet, radiofrequency probes, and a mechanical device that simulates relative sinusoidal motion between the sample and the applied magnetic field. [2] A bulk sample and three representative rocks, Fontainebleau Sandstone, Berea Sandstone, and Indiana Limestone, were investigated. Even though diffusion coefficient measurements are often neglected due to their inherent data-acquisition characteristics, the findings demonstrate that the diffusion coefficient of a fluid in a bulk sample or confined in a porous rock can be precisely measured and accurately predicted. [3] In strong magnetic field gradients, the Hahn spin echo is predominantly weighted by diffusion, an effect used to measure diffusion coefficients. Under LWD conditions, the diffusion coefficient measurement is significantly affected by signal phase modulation caused by sample movement in the presence of strong magnetic field gradients, making this measurement difficult. These results present solutions for accurate diffusion coefficient measurements by synchronizing Hahn spin-echo experiments with sample movement.

Acknowledgements

This study was financed by Petrobras, Brazil. Process Number 2020/00010-0

References

A. Gimenez Marassi, A. Gustavo de Araújo-Ferreira, E. Lucas-Oliveira, E. Luiz Géa Vidoto, A. Donizeti Fernandes de Amorim, W. Andrighetto Trevizan, T. José Bonagamba, Transverse relaxation measurements for moving samples in the presence of strong magnetic field gradients, *Journal of Magnetic Resonance* (2023) 107522. <https://doi.org/10.1016/j.jmr.2023.107522>.

E. Lucas-Oliveira, A.G. Marassi, A.G. Araújo-Ferreira, E.L.G. Vidoto, A.D.F. de Amorim, W.A. Trevizan, T.J. Bonagamba, Mechanically oscillating sample under magnetic field gradients: MOS-NMR, *J. Magn. Reson. Open* 12-13 (2022) 100084. <https://doi.org/10.1016/j.jmro.2022.100084>.

A.G. Marassi, A.G. de Araújo-Ferreira, E. Lucas-Oliveira, A.D.F. de Amorim, E.L.G. Vidoto, W.A. Trevizan, T.J. Bonagamba, Diffusion coefficient measurements for moving samples under strong magnetic field gradients, *Journal of Magnetic Resonance* 371 (2025) 107830. <https://doi.org/10.1016/j.jmr.2025.107830>.

Dipolar-Based Low-Field TD-NMR: From Soft Matter to Porous Media

Eduardo Ribeiro de Azevedo¹

¹Universidade de São Paulo (*Instituto de Física de São Carlos*)

e-mail: azevedo@ifsc.usp.br

Low-field Time-Domain Nuclear Magnetic Resonance (TD-NMR) has become an important experimental approach for a wide variety of applications [1]. Continuous developments in instrumentation and methodology have substantially expanded its capabilities through the exploration of relaxation and diffusion phenomena, as well as changes in NMR interactions, such as dipolar couplings. As a result, TD-NMR is now widely employed for the characterization of material properties in a broad range of systems, including solids, soft materials, and porous media.

In ¹H TD-NMR studies of solid and soft materials, through-space magnetic dipolar couplings between ¹H nuclear spins play a crucial role, rendering the NMR signals highly sensitive to molecular packing and molecular mobility. This intrinsic sensitivity makes ¹H TD-NMR especially effective for identifying mobility transitions, including segmental motions in soft materials [2], freezing and melting phase transitions [3], and the dissolution of solids.

In this presentation, we explore the use of dipolar-based low-field TD-NMR methods across different classes of materials, ranging from soft matter to porous systems. Particular emphasis is placed on approaches based on dipolar filtering combined with the Magic Sandwich Echo (MSE) sequence and their applications to the characterization of molecular mobility in soft materials, water populations in cementitious materials, mesoporous structures by NMR cryoporometry, and solid dissolution processes in soils.

Acknowledgements

CNPq (Grant number 308760/2022-0)

References

- [1] B. Blümich, Low-field and benchtop NMR, *Journal of Magnetic Resonance* 306 (2019) 27-35.
- [2] B. Trebbi, M. Pierigé, R. H. dos Santos Garcia, F. Martini, M. Geppi, E. R. deAzevedo, Accessing molecular motion activation parameters with ¹H low-field time-domain NMR: Examples from glass transition in polymers, *Journal of Magnetic Resonance* 382 (2026) 108008.
- [3] B. Trebbi, J. G. Filgueiras, R. H. dos Santos Garcia, R. P. Murbach, M. de Oliveira, E. R. deAzevedo, Dipolar-Filtered Magic Sandwich Echo as an alternative method for NMR cryoporometry, *Journal of Magnetic Resonance* 388 (2026) 108075.

EPR and DNP-MRI of Sandstones

Adam Altenhof¹, Niktia Bondarenko¹, Devin Morin², Xiang-Zhao Kong¹, Bruce Balcom²,
Martin Saar¹

¹Swiss Federal Institute of Technology / Eidgenössische Technische Hochschule ETH Zürich,

²University of New Brunswick

e-mail: adam.altenhof@eaps.ethz.ch

Electron paramagnetic resonance (EPR) of natural rock samples has been proposed for geological dating based on radioactive dosage in the subsurface creating defects in quartz. Quartz is the predominant component of sandstone (> 90 %) and can occupy a large fraction in granites (*ca.* 30 - 50 %); the high quantity of quartz makes the sensitive EPR of silica-centered radicals (E') well-suited for measuring these effects. However, it is well known from recent chemical literature that mechanical impact on quartz powders also forms E' centers (*e.g.*, ball milling, tumbling, grinding, etc.). Therefore, stable E' centers may form in quartz-rich geologic formations by tectonic and tidal deformations, or induced by human activities like tunneling, mining, and geoenery applications. Herein, I will present results from laboratory-scale experiments of stress-induced microfracturing in Berea sandstones. Samples are subject to compressive and tensile loading or heating to induce microcracks, then analyzed by conventional CW X-band EPR and show the onset of additional E' signals.

Furthermore, we explore using Overhauser dynamic nuclear polarization (ODNP) for enhancing ¹H signals in H₂O-saturated Berea sandstones. A homebuilt magnet and DNP-NMR apparatus is used based on inexpensive ferrite permanent magnets and a simple birdcage-style DNP resonator, respectively. Experiments are performed at approximately 50 mT, 2.1 MHz, and 1.4 GHz corresponding to the B_0 field, NMR frequency, and EPR/DNP frequency, respectively. Preliminary results show that the spin polarization is modulated according to DNP irradiation times and relative pore sizes. Consideration is given to using E' in natural rock samples as an endogenous source of radicals for ODNP. Finally, a unique mechanism is revealed showing how hyperfine couplings can be spatially encoded into NMR spectra when ODNP is performed in a constant gradient field.

Acknowledgements

This study was financed by Werner Siemens-Stiftung and the Centre for Origin and Prevalence of Life.

Fluid transfers through versatile dynamic NMR relaxometry

Maillet¹, Sidi-Boulenouar², Coussot²

¹Laboratoire Navier (*Université Gustave Eiffel*) , ²Laboratoire Navier

e-mail: benjamin.maillet@univ-eiffel.fr

For years, our group has been developing innovative experimental methodologies [1] to monitor liquid transfer in porous media and complex fluids using dynamic NMR relaxometry. Combined with MRI, this non-invasive, multiscale, and time-resolved approach enables the individual tracking of all out-of-equilibrium protonic liquid phases during processes such as drying, imbibition, or internal water redistribution in model nanoporous media, for various applications involving geo-based (clay, granular systems) or bio-based materials (wood, paper, plant fibers [2]) and gels [3]. Here, we show how in this context, original quantitative information can be extracted from the detailed analysis of the evolution of the transverse NMR relaxation time distributions over time during such transfers based on fast exchange concept between bulk and surface water at the pore scale. Dynamic NMR relaxometry is able to reveal phenomena such as wetting and dewetting, chemical instabilities of the solid matrix, or the progressive loss of moisture homogeneity inside non-transparent materials — information that is highly valuable for improving predictive physical models of liquid transport for a large range of scale corresponding to all liquid states. Several examples of porous material and complex fluid will be presented to illustrate the versatility and robustness of this approach.

Acknowledgements

This study was financed, in part, by the European Research Council PHYSBIOMAT - 101095764

References

- [1] Maillet, B.; Sidi-Boulenouar, R.; Coussot, P. Dynamic NMR Relaxometry as a Simple Tool for Measuring Liquid Transfers and Characterizing Surface and Structure Evolution in Porous Media. *Langmuir* 2022, 38, 15009–15025.
- [2] L. Yan, Y. Zou, J. Gil-Roca, B. Maillet, B. St-Michel, P. Coussot, Fate of a water drop in a cellulosic material, *Phys. Rev. Appl.*, 23 (1) (2025), Article 014073, 10.1103/PhysRevApplied.23.014073
- [3] E. Julien, B. Maillet, L. Tocquer, S. Aime, P. Coussot, Dynamic NMR relaxometry as a straightforward measurement of concentration variations in colloidal gels, *Langmuir*, 40 (51) (2024), <https://pubs.acs.org/doi/10.1021/acs.langmuir.4c03404>

Frequency domain NMR Relaxometry: the relevance of time scale and noise in data fitting

Esteban Anoardo¹

¹Universidad Nacional de Cordoba (*Instituto de Física Enrique Gaviola*)

e-mail: eanoardo@gmail.com

The extraction of physical information from any experiment relies on two unavoidable and intimately connected essential aspects: the experiment itself and data processing [1]. The former pertains to both the hardware specifications and the experimental protocol that defines the measurement quality, whereas the latter is only meaningful when supported by a validated physical model or, alternatively, by carefully constrained model-free approaches.

In the context of frequency-domain NMR relaxometry, the fast field-cycling (FFC) technique [2,3] offers clear and well-established advantages over other methodologies, such as rotating-frame relaxometry. A key strength of FFC lies in the exceptionally broad range of Larmor frequencies that can be accessed through controlled cycling of the static magnetic field B_0 . Depending on the instrumental implementation, this approach enables the exploration of Larmor frequency windows spanning several orders of magnitude in the laboratory-frame. Moreover, both the fastest and slowest relaxation processes that can be probed also depend on the associated instrumentation.

In this contribution, we briefly discuss an illustrative example in which a single FFC NMR experiment enables the simultaneous estimation of the elastic bending modulus of liposome membranes and the diffusion dynamics of their constituent lipid molecules. This case study highlights the critical interplay between the experimental design, the model-based data analysis and the pertinence of the used fitting engine. We conclude by briefly commenting on the broader implications of these considerations for FFC NMR relaxometry studies in porous media.

References

M. B. Marzola Coronel, L. Montes, E. A. Pilotta and E. Anoardo, Dynamic range and noise considerations in pattern search optimal fitting of experimental data: a case study using field-cycling NMR relaxometry of liposomal formulations, *Journal of Physics D: Applied Physics*, 2025, 58, 355305.

R. Kimmich and E. Anoardo, Field-cycling NMR Relaxometry, *Progress in NMR Spectroscopy*, 2004, 44, 257-320.

New developments in NMR: Field-cycling NMR Relaxometry. Instrumentation, Model Theories and Applications, R. Kimmich Ed., RSC, Croydon, 2019.

Localization-driven exchange contrast in diffusion exchange spectroscopy

Teddy Cai¹, Peter Basser², Nathan Williamson²

¹National Institutes of Health (*Eunice Kennedy Shriver National Institutes of Child Health and Human Development*) , ²National Institutes of Health

e-mail: teddy.cai@nih.gov

Diffusion exchange spectroscopy (DEXSY) is commonly interpreted using models that assume Gaussian diffusion within compartments and first-order exchange between them. Here, we show that DEXSY signal contrast with mixing time can arise even in the absence of barrier permeation. Specifically, a one-dimensional restricted domain with reflecting boundaries produces apparent exchange under strong-gradient conditions associated with signal localization (also known as "edge enhancement").

We consider DEXSY with identical, extended-gradient encodings. Signals were generated via a numerical approach that solves the Bloch-Torrey equation in discrete space and time using matrix operators. In the localization regime, spatially localized magnetization near boundaries redistributes during the mixing time, producing signal contrast that resembles first-order exchange. Fitting these signals with conventional exchange models yields an apparent first-order rate constant, k , despite the absence of first-order exchange.

The measured rate constant scales approximately as D/L^2 , where D is the diffusivity and L is the domain size, with $k \approx \pi^2 D/L^2$ in many cases. We show that this behavior originates from the relaxation of *spatial* magnetization eigenmodes during the mixing time rather than transfer between distinct compartments; notably, $\pi^2 D/L^2$ is the first non-zero Laplacian eigenvalue for the restricted domain. We further identify the encoding and microstructural regimes in which this localization-driven exchange mechanism is expected.

These results demonstrate that DEXSY and related methods such as filter exchange spectroscopy (FEXSY) are not necessarily specific to genuine permeation across barriers. At the same time, the observed contrast provides sensitivity to the dominant spatial eigenmode(s) of restricted domains, suggesting a complementary source of microstructural information that may be obtained from such methods.

Acknowledgements

TXC, NHW, and PJB were supported by the intramural research program (IRP) of the *Eunice Kennedy Shriver* National Institute of Child Health and Human Development (NICHD). NHW was funded by the Military Traumatic Brain Injury Initiative (MTBI²) through the Uniformed Services University of the Health Sciences (USU), Bethesda, MD (award No. HU0001-24-2-0051).

References

- P. T. Callaghan, I. Furó, Diffusion-diffusion correlation and exchange as a signature for local order and dynamics, *The Journal of Chemical Physics* 120 (8) (2004) 4032–4038.
- I. Åslund, A. Nowacka, M. Nilsson, D. Topgaard, Filter- exchange PGSE NMR determination of cell membrane permeability, *Journal of Magnetic Resonance* 200 (2) (2009) 291–295.
- P. T. Callaghan, A. Coy, L. Forde, C. Roife, Diffusive relaxation and edge enhancement in nmr microscopy, *Journal of Magnetic Resonance, Series A* 101 (3) (1993) 347–350.

Low-Field NMR Relaxometry System Solutions: Rapid Quantification of Pore and Fluid Properties in Porous Media

Zhang Yingli¹

¹Suzhou Niumag Analytical Instrument Corporation (*R & D Department*)

e-mail: yl_zhang@niomag.com

Niumag has developed a fully integrated low-field NMR technology platform with independent intellectual property rights, covering single-board spectrometers, fast-discharge RF technology, in-house magnet manufacturing, and multidimensional relaxometry and imaging measurement technologies. This platform supports a systematic standard equipment portfolio for routine and advanced porous media analysis. The standard product portfolio includes benchtop analyzers for plug and cuttings samples, floor-standing analyzers for full-diameter cores, imaging analyzers for spatial fluid visualization, and modular relaxometers for T1/T2 and T1-T2 measurements. Standard configurations support multiple field strengths, open-bore and closed-bore magnets, and sample sizes from small plugs to full-diameter cores. All standard systems share a unified software platform for automated acquisition of FID/CPMG and other sequences, relaxation inversion, and petrophysical parameter calculation. Typical applications include porosity, permeability, bound and free fluids, movable fluids, and pore size distribution. Optional modules add temperature control, pressure capability, and fluid displacement, extending routine core analysis to reservoir-relevant conditions.

Beyond standard products, Niumag offers professional customization capabilities. Typical examples include: 1) multi-physics coupling NMR measurement systems for enhanced oil recovery (EOR) and flow-in-porous-media studies under complex stress, temperature, and pressure fields; and 2) field mobile NMR measurement systems for rapid on-site measurement and in-situ evaluation. These solutions bridge the gap between laboratory analysis and field applications, advancing low-field NMR as a mainstream quantitative method for porous media.

Magnetic Resonance Pore Imaging with Extended Echo Times and Cartesian q -Space Mapping

Humna Asad¹, Petrik Galvosas¹, Daniel Holand²

¹Victoria University of Wellington (*School of Chemical and Physical Sciences*) , ²University of Canterbury (*Chemical and Process Engineering*)

e-mail: humna.asad@vuw.ac.nz

Magnetic Resonance Pore Imaging (MRPI) also known as Diffusion Pore Imaging (DPI) [1] provides information on the structure of porous media by the acquisition of averaged pore shapes. The technique builds upon the pulsed-gradient spin-echo (PGSE) concept, but extends one diffusion-encoding gradient so that, in the long-time limit, the measured signal $E(q)$ approaches the pore form factor $S_0(q)$. This approach, inherently based on q -space, can also be combined with conventional k -space MRI, resulting in MRPI mapping [2].

A requirement for MRPI is the need for long echo times. This can be challenging experimentally because of relaxation decays, gradient imbalance, or gradient-induced dephasing [3]. Recently, we have shown that, under favourable conditions and in specific geometries, spin echo times (TE) can be pushed to approximately 2 s [EUROMAR 2025].

Here, we deploy these extended echo times to re-implement 1D and 2D PGSE/MRPI experiments in glass capillaries while retaining high signal-to-noise ratios using a simple spin-echo acquisition rather than a CPMG-backbone MRPI sequence as used previously [2]. In 1D PGSE, diffusive-diffraction minima remained visible with good SNR to echo times of up 500 ms while in 1D MRPI, echo times reached up to 800 ms, improving convergence of $E(q)$ towards $S_0(q)$

In 2D MRPI, a Cartesian q -space sampling scheme was used in conjunction with echo times of up to 400 ms. These yielded suitable cross-sectional pore-shape reconstructions from the capillary bundles. We are currently extending this 2D MRPI approach towards mapping, retaining the 2D Cartesian q -space scheme while combining it with a Cartesian k -space scheme. This will allow 2D pore images to be reconstructed by Fourier transformation only, providing a route towards spatially resolved 2D×2D MRPI, where different pore-size populations within the same sample can be separated while retaining the simplicity of a single spin-echo acquisition.

Acknowledgements

This work was supported by a Ministry of Business, Innovation and Employment, New Zealand Endeavour Programme Grant [UOCX1903].

References

- [1] Laun, F.B. et al., Phys. Rev. Lett. 107, 048102 (2011)
- [2] Hertel, S.A. et al., Phys. Rev. E 92, 012808 (2015)
- [3] Bertleff, M. et al., J. Magn. Reson. 278, 39–50 (2017)

Probing the interaction between a MOF and the CO₂ using ultra-high field NMR

Imane El Bakkali¹, Athulya Nadol¹, Yaye Niasse², Thomas-Xavier Métro², Danielle Laurencin², Christel Gervais³, Christophe Volkringer¹, Olivier Lafon⁴, Frederique Pourpoint⁵

¹Centrale Lille, ²Institut Charles Gerhardt Montpellier, ³Sorbonne Université, ⁴Université de Lille, ⁵Centrale Lille (UCCS)

e-mail: imane.el_bakkali@centralelille.fr

In response to the growing challenge of rising atmospheric CO₂ concentration, porous adsorbents have emerged as promising candidates for the separation and the capture of CO₂. Among these materials Metal-Organic Frameworks (MOFs) represent a pivotal approach due to their structural versatility. However, experimental techniques elucidating the nature of the host-guest interaction remain limited. Solid-state NMR as a local probe is a suitable spectroscopic method for the characterization of the adsorbed CO₂ in the MOF's pores. In particular, it can provide insight into the adsorption sites of the CO₂ in the MOF framework, the adsorption strength, and the dynamic behavior of guest molecules confined within the porous network. Such information is essential for establishing structure-property relationships and guiding the rational design of more efficient adsorbent materials.

We studied the insertion of 1 bar of CO₂ in two stable MOFs: the aluminum-based MIL-120, built from pyromellitate linkers and the zirconium-based UiO-66 constructed with terephthalate ligands. Owing to their narrow pores, both materials are particularly well suited for the adsorption of small molecules such as CO₂.

To obtain a comprehensive understanding of the adsorbed CO₂ we combined (i) advanced high-resolution solid-state NMR methods, (ii) selective ¹³C and ¹⁷O isotopic labelling and (iii) computational modeling. This enabled us to directly probe the local environment of CO₂ and reveal key structural features governing CO₂ confinement. Furthermore, our results highlight the critical importance of ultra-high magnetic fields (up to 28.2 T) especially for ¹⁷O nucleus to obtain valuable insight into the CO₂ adsorption in porous media.

Acknowledgements

THis study was financed by agence nationale de la recherche (ANR-24-CE29-5084-1), and the Institut Universitaire de France.

References

Nadol et al., Solid State Nucl. Magn. Reson., 2026, in press

Robust Methods and Durable Devices for NMR in Harsh, Non-laboratory Conditions

Matthew P Augustine¹

¹University of California, Davis (*Chemistry*)

e-mail: maugust@ucdavis.edu

Non-laboratory, at the point - of - care, field measurements require more than personnel and instruments. Most commercially available NMR instruments are not durable enough to survive deployment to real, harsh factory conditions involving severe electronic noise, mechanical vibration, and an uncontrolled environment. Also, these real non-laboratory conditions, unfamiliar to most spectroscopists, make most data acquisition and processing protocols unstable. Examples of stable data processing methods, portable lightweight, inexpensive instruments and their use in factories, the outdoors and hotel rooms will be provided and used to highlight the steps needed to convert real field measurements into meaningful information.

Understanding NMR Signal Behavior Under Sample Motion: Implications for Logging While Drilling Operations

Willian Andrighetto Trevizan¹, Bernardo Coutinho², Moacyr do Nascimento Neto², Agide Gimenez Marassi³, Arthur Gustavo de Araujo Ferreira⁴, Edson Vidoto⁴, Everton Lucas-Oliveira⁵, Aparecido Donizeti Fernandes de Amorim⁴, Tito José Bonagamba⁶

¹Petroleo Brasileiro SA (Cenpes) , ²Petroleo Brasileiro SA, ³Universidade de São Paulo (Instituto de Física de São Carlos) , ⁴Universidade de São Paulo, ⁵Brazilian Center for Research in Energy and Materials (Brazilian Synchrotron Light Laboratory (LNLS)) , ⁶Universidade de São Paulo (São Carlos Institute of Physics)

e-mail: williantrevizan@petrobras.com.br

Logging While Drilling (LWD) NMR measurements are critical for in-situ petrophysical characterization. Although mathematical correction approaches have been proposed to account for sample motion effects on transverse relaxation (T_2) measurements [1, 2], the comprehensive applicability of these corrections remains incompletely understood. This study investigates the effects of mechanical oscillations on NMR signals in representative rock samples using a laboratory-scale LWD emulator. Four different samples—three sandstones (Fontainebleau, Berea, Portland Red) and one carbonate (Indiana Limestone)—covering a broad range of relaxation times were analyzed under controlled sinusoidal motion at frequencies from 1–4 Hz and amplitudes up to 5 mm. Results demonstrate that sample motion significantly alters relaxation time distributions and pore size distribution interpretations, particularly when T_2 values are comparable to oscillation periods. However, crucially, total porosity estimates remain robust and independent of sample motion across all conditions, including high-amplitude oscillations. These findings reconcile contradictions in the literature regarding porosity loss during LWD operations and provide critical insights for improving petrophysical interpretation models in dynamic drilling environments. This work establishes practical guidelines for field data acquisition and processing under complex motion scenarios in the oil and gas industry.

Acknowledgements

This work was financed with the support of Agência Nacional do Petróleo (ANP).

References

Coman, Radu , Tietjen, Holger , Thern, Holger , Blanz, Martin , and Søren Amdi Christensen. "Improved NMR Logging Approach to Simultaneously Determine Porosity, T_2 and T_1 ." Paper presented at the SPE Annual Technical Conference and Exhibition, Houston, Texas, USA, September 2015. doi: <https://doi.org/10.2118/175050-MS>

Coman, Radu, Thern, Holger, and Tobias Kischkat. "Lateral-Motion Correction of NMR Logging-While-Drilling Data." Paper presented at the SPWLA 59th Annual Logging Symposium, London, UK, June 2018.

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

03

Human Health, Environmental Science, Food, and Biomaterials

ORAL PRESENTATIONS

**RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026**

A Low-Field MRI scanner for Multimodal Preclinical Imaging: Gamma detected-MRI

Dimitrios Sakellariou¹

¹Katholieke Universiteit Leuven (M2S/cMACS)

e-mail: dimitrios.sakellariou@kuleuven.be

The GAMMA-MRI project [1] explores magnetic-resonance spatial encoding of gamma photons emitted by hyperpolarized xenon isomers, detected by gamma sensors surrounding the subject [2]. This approach may achieve sensitivity to about 10^{13} spins while retaining the adaptability and spatial resolution of conventional MRI while working at low magnetic field.

Low-field MRI is gaining attention due to advances in permanent magnets and electronics, offering portability, lower acquisition and maintenance costs, improved sustainability, and flexibility for application-specific designs and multimodal integration.

We present principles and examples of custom MR instrumentation [3], focusing on a low-field preclinical scanner developed for small-animal imaging. To preserve access for GAMMA-MRI detection, the system uses a yokeless C-shaped permanent magnet with a central bore and 160 mm pole gap. The compact, portable assembly weighs about 40 kg and produces a 50 mT field; its homogeneity and temporal stability are characterized. Custom gradient coils and second-order shim elements were designed to maintain bore access. Initial proton images of phantoms were acquired using inductive Faraday detection and reconstructed with conventional PFG Fourier methods and alternative inverse Laplace/Radon techniques. Sensitivity and spatial resolution in standard operation are reported. Ongoing work targets full integration and in vivo imaging.

Acknowledgements

Funded by the European Union's Horizon 2020 programme under grant agreement No. 964644.

References

[1] gamma-mri.eu

[2] Zheng, Y., Miller, G. W., Tobias, W. A., Cates, G. D., Nature 537, 652 (2016)

[3] Oliveira-Silva, R., Bélime, A., Le Coeur, C., Chennevière, A., Helary, A., Cousin, F., Judeinstein, P., Sakellariou, D., Zanotti, J.-M., J. Neutron Res. 21, 155 (2019)

Characterization of 3D-Printed Biomimetic Scaffolds by Low-Field NMR: Relaxation and Diffusion Studies in Soft Porous Media

Manuel Isaac Velasco¹, Pablo Andrés Fernández², Mariana Paula Cid², Romina Comín²,
Rodolfo Acosta³

¹Instituto de Física Enrique Gaviola, ²Universidad Nacional de Córdoba (*Facultad de Ciencias Exactas, Físicas y Naturales*), ³Universidad Nacional de Córdoba (*FAMAF*)

e-mail: mvelasco@unc.edu.ar

The design of effective 3D-printed biomimetic scaffolds, such as collagen-hyaluronic acid hydrogels, requires rigorous characterization of their hierarchical pore networks and fluid-matrix interactions. Standard imaging techniques require drying and are destructive, failing to capture the physical reality of soft porous materials in their fully hydrated, functional state. This study presents a low-field Nuclear Magnetic Resonance (LF-NMR) methodology to characterize the hierarchical porosity, water dynamics, and structural anisotropy of these soft porous media subjected to different crosslinking treatments (physical or chemical). In particular, the focus is on the effect of crosslinking on water dynamics, pore network characterization, and microstructural anisotropy.

Transverse relaxation times showed distinct water populations representing different hierarchically confined pore environments. Porosity was also evaluated, linking crosslinking density to the swelling capacity of the network. Two-dimensional T_1 - T_2 correlation maps were used to evaluate exchange kinetics and confinement mechanisms at the biopolymer-solvent interface. The resulting deviations from the free-water diagonal directly revealed changes in the segment mobility of the polymer chains. Furthermore, the Magic Angle effect was exploited using the Magic Sandwich Echo (MSE-FID) sequence in the frequency domain to assess microstructural anisotropy of the material fibers induced by shear stresses during printing extrusion and its subsequent crosslinking. Additionally, components of the diffusion tensor were investigated using a unilateral NMR-MOUSE sensor to quantify directional mass transport within the scaffold matrices. The combination of these LF-NMR techniques provides a direct, non-destructive framework to quantify the physical properties and transport dynamics of soft porous biomaterials.

Acknowledgements

This study was financed, in part, by SECYT-UNC, ANPCYT, and CONICET

References

P.A. Fernández, M.P. Cid, R. Comín, M.I. Velasco, Structural Characterization and Hydration Dynamics of Cross-Linked Collagen and Hyaluronic Acid Scaffolds by Nuclear Magnetic Resonance, *Journal of Physical Chemistry B* 128 (2024) 12143-12153.

<https://doi.org/10.1021/acs.jpcb.4c06316>

Climate change: the science, impacts, and mitigation strategies

Paulo Artaxo¹

¹Institute of Physics - University of São Paulo

e-mail: artaxo@if.usp.br

Fossil fuel use largely drives climate change by increasing greenhouse gas emissions. Rising temperatures are changing weather patterns and intensifying extreme climate events. These shifts affect ecosystems, agriculture, water supplies, and human health. The impacts are uneven, placing greater burdens on vulnerable communities. Climate science helps explain these changes and project future risks. Reducing emissions is essential to limit further warming. Key strategies include clean energy, energy efficiency, and sustainable transport. Protecting forests and restoring ecosystems can also absorb carbon. Adaptation measures help communities prepare for unavoidable impacts. Combining mitigation with adaptation is crucial in building a new sustainable society

CNPEM, a Unique Laboratory in Latin America

Antonio José Roque da Silva¹

¹Brazilian Center for Research in Energy and Materials (*Diretoria-Geral*)

e-mail: nadia.dotta@cnpem.br

The Brazilian Center for Research in Energy and Materials (CNPEM) is a cutting-edge, multi-user, multidisciplinary scientific environment that supports the Brazilian National Science, Technology and Innovation System. It has globally competitive laboratory infrastructures open to the scientific community, such as Sirius, one of the world's most advanced synchrotron light source. The Center combines a range of skills, with an emphasis on nanotechnology, biosciences, biotechnology, biorenewables, cutting-edge engineering and scientific instrumentation, carrying out research and development in strategic areas such as health, energy, renewable materials, and sustainability, including innovative projects in partnership with the productive sector and contributing to the training of researchers and students. The Center is also responsible for the Ilum School of Science, a higher education course in Science, Technology and Innovation. CNPEM has recently began developing the Orion project, a laboratory complex for advanced research in pathogens, which will host facilities with advanced levels of biological containment (BSL-3 and BSL-4), planned to be the first in the world to be connected to a synchrotron light source. In this seminar an overview of the CNPEM's activities will be presented.

References

<https://cnpem.br/>

CO₂ Storage Strategies in the Oil Sector - Perspectives in Petrobras

Willian Andrighetto Trevizan¹

¹Petroleo Brasileiro SA (Cenpes)

e-mail: williantrevizan@petrobras.com.br

Evaluating porous media for Carbon Capture and Storage (CCS) requires a fundamental shift from traditional petroleum reservoir engineering frameworks. While oil and gas characterization primarily focuses on hydrocarbon recovery, CCS demands a comprehensive understanding of long-term containment, multi-phase fluid-rock interactions, and complex trapping mechanisms over geological timescales. This presentation addresses fundamental aspects of geological CO₂ storage, focusing on designing reliable Measurement, Monitoring, and Verification (MMV) programs. In this context, we give an overview of well monitoring technologies and strategies to be tested in Petrobras pilot-scale MMV of Barra do Furado, which will also include a sensitivity analysis of time-lapse NMR well logging.

Determining the Crystallite Size of Organic Solids with ^1H NMR T_1 Relaxation

Armin Afrough¹, Jari Pekka Pajander², Zacharias Brimnes Visby Damholt², Thomas Vosegaard¹

¹Aarhus University / Aarhus Universitet, ²Novo Nordisk

e-mail: armin@inano.au.dk

Polycrystalline organic solids are ubiquitous in food, pharmaceutical, and chemical industries. We demonstrate that the ^1H T_1 relaxation time of polycrystalline organic solids is strongly correlated with crystallite size over more than four orders of magnitude in size, from approximately 50 nm to 1 mm. We explain this behavior through a relaxation-diffusion model in which nuclear magnetization first migrates from the crystal interior to the surface by spin diffusion and subsequently relaxes at surface sinks. Therefore, larger crystals have a longer spin-diffusion length and hence longer T_1 relaxation time. This mechanism is analogous to the NMR relaxation of liquids in porous materials, where mass diffusion to relaxing surfaces produces relaxation times that are correlated to the pore size. We present evidence from literature data, model systems, commercial pharmaceutical lactose powders, and lactose tablets compressed at different tableting pressures. The model shows two distinct regimes corresponding to fast and slow spin diffusion and explains both linear and quadratic scaling relationships between ^1H T_1 and crystallite size. In low-temperature and dynamic nuclear polarization data, we observed nonground relaxation eigenmodes and used them to estimate the absolute crystallite size. Our findings establish ^1H T_1 relaxation as a non-invasive probe of crystallite size and suggest applications in the characterization and process monitoring of pharmaceutical, food, agricultural, and chemical materials.

References

Rabbani et al. Brazilian Journal of Physics 36 (1A):28-33, 2006

Lubach et al. Journal of Pharmaceutical Sciences 96: 777, 2007

Diffusion Dynamics in Axons and the understanding of diffusion MRI in Brain

Yi-Qiao Song^{1,2}

¹Harvard University, ²Massachusetts General Hospital

e-mail: yqsong@g.harvard.edu

Diffusion MRI is widely used for the clinical examination of a variety of diseases of the nervous system. However, clinical MRI scanners are mostly capable of low magnetic field gradients. The availability of the Connectome MRI scanners with ultra-high gradient strengths up to 300 mT/m enables the resolution of a wider range of diffusion coefficients and tissue structures. In addition, biological tissues are heterogeneous on many scales and the complexity of tissue microstructure may not be accurately captured by simplistic models based on pre-existing assumptions. For example, an axon may not be considered as a straight tube as in most of the diffusion literature. Here, we study the intrinsic diffusion physics in thousands of realistic axon models and show a diversity of diffusion behavior. We outline a framework for analyzing diffusion MRI to obtain a model-free Full Diffusion Tensor Distribution (FDTD). We then apply this method and use a machine learning method to identify features in FDTD to visualize and characterize tissue heterogeneity in diffuse gliomas.

Diffusion MRI in cerebral small vessel disease: characterization of longitudinal microstructural decline with advanced markers

Maddalena Cavallo¹, Alessandro Carozzi¹, Leonardo Brizi², Alessandro Chiarini³, Claudia Testa⁴

¹University of Bologna, ²Università di Bologna (*Physics and Astronomy*) , ³BI-REX Big Data Innovation & Research Excellence, ⁴University of Bologna (*Department of Physics and Astronomy*)

e-mail: maddalena.cavallo3@unibo.it

Cerebral small vessel disease (cSVD) is an umbrella term used to collectively describe different pathologies that affect small blood vessels in the brain. It's an emerging disease, contributing to 45% of dementia and 25% of stroke cases worldwide [1]. Diffusion MRI (dMRI) parameters have shown larger sensitivity to disease severity and progression compared to conventional markers based on structural MRI, such as white matter hyperintensities and microbleeds [2]. This work aimed to investigate whether these dMRI metrics can detect longitudinal decline in SVD patients. A cohort of 48 SVD patients was identified on the UK Biobank (application ID: 155020), with median age at baseline of 69 years (IQR: 66-74 years) and median follow-up time of 2.23 years (IQR: 2.07-2.28 years). DTI (Diffusion Tensor Imaging) and NODDI (Neurite Orientation and Density Imaging) model parameters were extracted in white matter (WM) and grey matter (GM) ROIs. Linear mixed-effects models were employed to study longitudinal change of the parameters in each ROI, adjusting for baseline age and sex and applying FDR correction. Significant differences ($p < 0.05$) were found across several WM ROIs, most notably in the corona radiata, internal and external capsules, corpus callosum, and superior longitudinal fasciculus (effect sizes 0.1-0.2 sd/year). These results highlight the sensitivity of advanced dMRI metrics to WM longitudinal deterioration in cSVD. Future work will explore the relationship between these metrics and cognitive performance, to further validate the clinical importance of these biomarkers.

Acknowledgements

Funded by the European Union - Next Generation EU, Mission 4, Component 2, Investment 3.3 (Ministerial Decree 630/2024) CUP J33C24001440009.

This research has been conducted using the UK Biobank Resource under Application Number: 155020.

References

R. J. Cannistraro, M. Badi, B. H. Eidelman, D. W. Dickson, E. H. Middlebrooks, and J. F.

Meschia, "CNS small vessel disease: A clinical review." *Neurology*, vol. 92, no. 24, pp. 1146-1156, Jun. 2019.

B. Patel and H. S. Markus, "Magnetic resonance imaging in cerebral small vessel disease and its use as a surrogate disease marker," *Int. J. Stroke*, vol. 6, no. 1, pp. 47-59, Feb. 2011.

Low-Field NMR Relaxometry for GAG Assessment: A Multimodal Investigation of Articular Cartilage

Leonardo Conti¹, Simone Fantoni², Matteo Berni², Carola Cavallo³, Roberta Fognani², Paolo Cardarelli⁴, Claudia Testa¹, Fabio Baruffaldi², Leonardo Brizi¹

¹Università di Bologna (*Department of Physics and Astronomy "Augusto Righi"*) , ²IRCCS Istituto Ortopedico Rizzoli (*Medical Technology Laboratory*) , ³IRCCS Istituto Ortopedico Rizzoli (*RAMSES Laboratory for regenerative and personalized medicine of musculoskeletal system*) , ⁴Istituto Nazionale di Fisica Nucleare (INFN) (*Division of Ferrara*)

e-mail: leonardo.conti8@unibo.it

Articular cartilage (AC) is a soft tissue covering the extremities of articulating bones within synovial joints. The collagen mesh, intertwined proteoglycans (PG) and their associated glycosaminoglycan (GAG) chains form a heterogeneous pore structure that constrains interstitial water. Single-sided Nuclear Magnetic Resonance (SS-NMR) relaxometry has been shown to discriminate tissue composition and structure among the three AC zones¹. This work investigated the sensitivity of SS-NMR to GAG concentration by comparing T_1 and T_2 distributions against results from contrast-enhanced μ CT, used as a reference technique. To further establish a multidisciplinary framework linking AC composition, structure, and mechanics, the relationship between NMR parameters and tissue mechanical properties was explored via indentation testing.

Thirty-two osteochondral samples were retrieved from the knee joints of healthy bovines. After indentation testing², CPMG and Saturation Recovery measurements were performed for each of the AC zones using an NMR-MOUSE ($B_0=0.327$ T) device. Finally, samples were exposed to CA4+, a cationic contrast agent affine to GAG chains³, and imaged with a tabletop μ CT system. The CT reference procedure was further validated via biochemical assay. Descriptive statistics of T_1 and T_2 distributions obtained using the UPEN algorithm were compared with the average CT attenuation coefficient for each zone and the samples' mechanical parameters.

Preliminary results showed a positive relationship between CT attenuation and the signal fraction of the short T_2 component (0.1–5 ms; Spearman $\rho=0.54$) as well as an inverse trend with its full width at half maximum (FWHM, $\rho=-0.54$). In addition, the FWHM of the T_1 distribution showed an inverse relationship with the timescale of the viscoelastic response ($\rho=-0.67$). These findings support the role of GAG chains in water confinement and suggest SS-NMR as a useful technique for probing AC composition and mechanical properties.

References

Golini, C., Barbieri, M., Nagmutdinova, A., Bortolotti, V., Testa, C., & Brizi, L. (2025). Depth-wise multiparametric assessment of articular cartilage layers with single-sided NMR. *NMR in Biomedicine*, 38(1), e5287

Berni, M., Erani, P., Lopomo, N. F., & Baleani, M. (2022). Optimization of In Situ Indentation Protocol to Map the Mechanical Properties of Articular Cartilage. *Materials*, 15(18), 6425

Fantoni, S., Gabucci, I., Cardarelli, P., Paternò, G., Taibi, A., Cristofori, V., ... & Baruffaldi, F. (2022). A cationic contrast agent in X-ray imaging of articular cartilage: pre-clinical evaluation of diffusion and attenuation properties. *Diagnostics*, 12(9), 2111

Magnetic Resonance and Magnetic Resonance Imaging with a Variable Field Cryogen Free Superconducting Magnet

Bruce Balcom¹

¹University of New Brunswick (*Physics*)

e-mail: bjb@unb.ca

Magnetic Resonance of realistic materials is often confounded by magnetic susceptibility mismatch effects which dramatically increase the MR linewidth. In an ideal world one would wish to choose the maximum field strength (for more signal) consistent with a tolerable magnetic susceptibility mismatch effect. For several years we have been employing a cryogen free magnet with an integrated magnet power supply which permits us to increase or decrease the static field as desired, controlling linewidth and susceptibility effects for relaxation and imaging studies.

There is however another advantage of the variable field magnet approach to materials MR/MRI. If we are studying a system with a complicated apparatus (for example a battery or a system at high temperature and pressure) the simplest possible RF probe is desirable. The variable field magnet makes it possible to bring different nuclei into resonance while maintain the original resonance frequency. The RF probe in this case maintains a constant frequency and constant sensitivity even as we change the nuclei being interrogated. For example, at 0.79 T the ^1H frequency is 33 MHz. If the field is increased to 2.99 T we measure ^{23}Na at 33 MHz and if we increase the field to 3.1 Tesla we measure ^{13}C at 33 MHz.

In this presentation we will outline measurements where we adjust the field to control susceptibility mismatch effects, and we will describe measurements in systems where we adopt the field changing approach to undertake ^{19}F , ^{13}C , ^{23}Na and ^7Li studies in conjunction with ^1H for battery studies and studies of fluids in porous media.

The Pore Size of PLGA Bone Implants Determines the De Novo Formation of Bone Tissue in Tibial Head Defects in Rats

Daniel Huster¹

¹University of Leipzig (*Medical Department*)

e-mail: daniel.huster@medizin.uni-leipzig.de

Purpose: The influence of the pore size of biodegradable poly(lactic-co-glycolic acid) scaffolds on bone regeneration was investigated.

Methods: Cylindrical poly(lactic-co-glycolic acid) scaffolds were implanted into a defect in the tibial head of rats. Pore sizes of 100–300, 300–500, and 500–710 µm were tested and compared to untreated defects as control. Two and four weeks after implantation, the specimens were explanted and defect regeneration and de novo extracellular matrix generation were investigated by MRI, quantitative solid-state NMR, and mass spectrometry.

Results: The pore size of the scaffolds had a pronounced influence on the quantity of the extracellular matrix synthesized in the graft; most collagen was synthesized within the first 2 weeks of implantation, while the amount of hydroxyapatite increased in the second 2 weeks. After 4 weeks, the scaffolds contained large quantities of newly formed lamellar bone while the control defects were filled by inhomogenous woven bone.

Best results were obtained for scaffolds of a pore size of 300–500 µm.

Conclusion: Our analysis showed that the structure and dynamics of the regenerated extracellular matrix was very similar to that of the native bone, suggesting that biomineralization was significantly enhanced by the choice of the most appropriate implant material.

Acknowledgements

DFG; Grant number: TRR 67, projects: A1, A2, A6, B5

References

Magn Reson Med 70:925–935, 2013

Magnetic Resonance in Porous Media 2026



Grouperment
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

04

Natural and Artificial Porous Media & Cultural Heritage

ORAL PRESENTATIONS

RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026

Application of Proton Time-Domain NMR to Investigate Water Distribution and Pore Structure Development in Low-Carbon Cements

Lucia Ferrari¹, Anastasiia Nagmutdinova¹, Leonardo Brizi², Claudia Testa², Villiam Bortolotti¹

¹Università di Bologna (Department of Civil, Chemical, Environmental, and Materials Engineering (DICAM)) , ²Università di Bologna (Department of Physics and Astronomy "Augusto Righi")

e-mail: lucia.ferrari9@unibo.it

Proton Time-Domain Nuclear Magnetic Resonance (¹H TD-NMR) was applied to investigate the role of water in low-carbon cements containing calcined clay, both in the fresh and hardened state. Water distribution in cement pastes was studied using transverse, T₂, relaxation times acquired with Carr-Purcell-Meiboom-Gill (CPMG) sequences. It is shown that the intraparticle pores of calcined clay particles absorb a significant fraction of the mixing water, reducing the amount of free water available in the system. This phenomenon affects the rheological behavior of fresh binders and may explain the loss of workability commonly observed in calcined clay-based cements.

Furthermore, Logarithmic Aperiodic Pulse Saturation Recovery (LAPSR) experiments and two-dimensional T₁-T₂ relaxation maps were used to follow the evolution of water environments during hydration. The NMR signals were processed through quasi-continuous linear 1D and 2D inversion using the software packages UPENWin and MUPEN2D, respectively, allowing the reconstruction of one- and two-dimensional relaxation time distributions. The analysis provided information on water mobility, pore structure refinement and the progressive development of hydration products.

In particular, white Portland cement, ordinary Portland cement and limestone calcined clay cement were investigated, and they showed distinct relaxation behavior, with T₁/T₂ ratios of approximately 2.5, 2.0 and 1.5, respectively. Relaxation behavior revealed differences in water-surface interactions and pore structure evolution during hydration, with iron-bearing phases affecting microstructural development but not significantly altering interlayer water relaxation.

The combined use of TD-NMR relaxation time distributions and T₁-T₂ correlation maps enabled the characterization of water dynamics and pore structure evolution during hydration of low-carbon cementitious systems.

References

A. Nagmutdinova, L. Brizi, C. Testa, V. Bortolotti, and L. Ferrari, "A comparative study of OPC, WPC, and LC3 cements by low-field 1H TD NMR," *Constr. Build. Mater.*, vol. 506, Jan. 2026, doi: 10.1016/j.conbuildmat.2025.144785.

Lucia Ferrari, Anastasiia Nagmutdinova, Arnaud Müller, Nikola Mikanovic, Mohsen Ben-Haha, Villiam Bortolotti, Elisa Franzoni. "Disclosing the mechanism behind rheological

challenges in calcined clay-based cements," *Constr. Build. Mater.*, vol. 492, p. 142837, Sep. 2025, doi: 10.1016/j.conbuildmat.2025.142837

1. V. Bortolotti, L. Brizi, A. Nagmutdinova, F. Zama, G. Landi. MUPen2DTool: A new Matlab Tool for 2D Nuclear Magnetic Resonance relaxation data inversion. *SoftwareX*, Vol. 20, 2022. <https://doi.org/10.1016/j.softx.2022.101240>

Capabilities of the Powder X-ray Diffraction Beamline (PAINEIRA) at SIRIUS for Structural Characterization of Porous Materials

Cristiane Barbieri Rodella¹, Flavia Regina Estrada², DANIELLE SANTOS GONCALVES²,
Amanda Iglessias Ferreira³, Júnior Cintra Maurício³

¹Brazilian Center for Research in Energy and Materials (LNLS) , ²Brazilian Synchrotron Light Laboratory (LNLS) , ³Brazilian Synchrotron Light Laboratory

e-mail: cristiane.rodella@lnls.br

X-ray diffraction analysis of polycrystals (PXRD) is crucial for examining the correlation between the crystalline structure and porosity and, consequently, its functionality. The organized packing of atoms and molecules dictates the size, shape, and connectivity of the void spaces that form, and this relationship is essential in material science and engineering. The Powder X-ray Diffraction technique using synchrotron radiation (SR-PXRD) offers advantages such as high photon flux, low-divergence X-ray beams, and adjustable energy levels, thereby minimizing instrumental effects on peak profiles and enabling high-resolution analyses. The PAINEIRA beamline is a facility dedicated to X-ray diffraction characterization of polycrystalline materials at the Brazilian synchrotron radiation (SR) facility, SIRIUS [1]. The benefits of using SR-XRD for characterizing polycrystalline materials at PAINEIRA extend beyond high resolution and signal-to-noise ratio. SR-XRD experiments can be combined with appropriate sample environments, fluid-handling systems, and large angular resolution and fast detectors to facilitate in situ and operando experiments that reveal transient crystalline phases or structures responsible for the performance of functional materials [2]. The beamline was designed to be efficient and flexible for data acquisition, providing high angular resolution with a multi-analyzer crystal detector and/or a fast-area detector. Automated experiments under variable temperature conditions will also be available [2]. In this presentation, I will provide an overview of the PAINEIRA beamline, primarily focusing on the mechanical, automated, and computational tools [3] that enhance efficiency and create a user-friendly environment for powder X-ray diffraction experiments. Ultimately, it will be demonstrated how this specialized synchrotron tool can investigate fundamental material properties at the atomic level and correlate them with their corresponding functions.

References

- Estrada, F. R., et al. (2022) J. Phys.: Conf. Series 2380, 012033.
- Ferreira, A. I., et al. (2025) J. Phys.: Conf. Series 3010, 012147.
- Biondo Neto, J. L., et al. (2025) J. Appl. Cryst. 58, 1061-1067.

Characterization of magnetic rocks: a challenge for NMR

Yi-Qiao Song¹

¹Harvard University (SEAS)

e-mail: yqsong@g.harvard.edu

Mapping mineral and pore distributions across scales is crucial for evaluating geochemical and reactive transport properties of subsurface rocks that underlie subsurface applications such as, oil and gas production, geological carbon storage/mineralization, geologic hydrogen generation, and mining exploration. Many of the relevant rocks contain a high percentage of iron and magnetic minerals so that the NMR relaxation is strongly affected by diffusion in the internal magnetic fields, even for very short echo times. Furthermore, the internal fields and their gradients are heterogeneous among the different pores, making it difficult to obtain the intrinsic T₂. We developed a new pulse sequence to separate the diffusion and intrinsic relaxation effects and recover the intrinsic T₂ for pore size determination. We have also developed a method for high-throughput super-resolution mineralogy mapping based on SEM imaging to identify the fine grain minerals for multiscale characterizations of rock mineralogy from submicron to centimeters. We will report our results on basalt, sandstone, carbonate and other mine rock samples. These new methods could be beneficial for a wide range of subsurface exploration.

Combined quantitative ^1H , ^{23}Na and ^{35}Cl NMR to study the salt crystallization of NaCl-NaNO₃ mixtures in sandstone during drying

Leo Pel¹, David Smeulders²

¹Eindhoven University of Technology / Technische Universiteit Eindhoven (*mechanical engineering*) , ²Eindhoven University of Technology / Technische Universiteit Eindhoven (*Mechanical Engineering*)

e-mail: l.pel@tue.nl

Salt crystallization is one of the major causes of deterioration of cultural heritage objects. While most studies focus on the crystallization behaviour of single salts real heritage materials are commonly exposed to complex salt mixtures. These mixtures are problematic due to their complex interactions and the crystallization is usually interpreted using equilibrium phase diagrams.

In this study, we investigate the crystallization behaviour of NaCl-NaNO₃ mixtures during drying in sandstone using a dedicated 4.7 T NMR setup. Quantitative measurements of ^1H , ^{23}Na and ^{35}Cl signals were performed quasi-simultaneously, allowing the determine the ratio of NaCl-NaNO₃ remaining in solution throughout the drying process. Hence the evolution of the salt mixture ratio can be monitored directly, providing direct insight into the crystallization pathway.

The sandstone samples were saturated with solutions containing different NaCl-NaNO₃ ratios and subsequently dried. Analysis of the drying curves yielded Peclet numbers between 5 and 10, indicating that ion transport is dominated by advection. The NMR measurements reveal that the ratio of NaCl-NaNO₃ in solution remains essentially constant throughout drying for all investigated mixtures. This behaviour is in sharp contrast to predictions based on equilibrium phase diagram, which anticipate substantial changes in solution composition.

The results indicate that under drying conditions crystallization is essentially transport-driven. The commonly used equilibrium approximation is therefore insufficient to describe salt-mixture crystallization. Indeed, this NMR study reveals that the equilibrium approximation does not hold under drying conditions and the measurements seem to indicate that either NaCl or NaNO₃ supersaturate, resulting the ratio keeping constant. These findings have important implications for understanding salt damage in cultural heritage and for interpreting salt analyses obtained from weathered porous materials.

Acknowledgements

MORISAL (Project No. 17636), which is (partly) financed by the Dutch Research Council

(NWO).

References

L. Pel, S. Godts, A. Stahlbuhk, N. Shahidzadeh, M. Steiger, M., Crystallization of NaCl-NaNO₃-H₂O in porous media during drying, *Crystal Growth & Design*, 25 2843-2848 (2025)

Development of Portland Cement Binders with Low CO₂ Footprint Utilizing Solid-State NMR spectroscopy

Jørgen Skibsted¹

¹Aarhus University / Aarhus Universitet (*Department of Chemistry*)

e-mail: jskib@chem.au.dk

Solid-state NMR, in particular ²⁷Al and ²⁹Si NMR, has been an invaluable tool for characterization of the structure, composition, and reactivity of Portland cement, supplementary cementitious materials (SCMs) such as calcined clays, and carbonation products [1]. This will be illustrated by three examples:

(i) For calcined clay - limestone Portland cements, ²⁷Al and ²⁹Si NMR has been provided information about the degree of reaction of the calcined clay (metakaolin) and the evolution of the Al-bearing phases during hydration. The principal binding phase is a less-ordered calcium-(alumino)-silicate-hydrate (C-(A)-S-H) phase, where the combination of ²⁷Al and ²⁹Si NMR has provided quantitative information on Al in this phase, giving a more detailed picture on the capacity of the C-(A)-S-H phase to incorporate Al under different compositional conditions and at different hydration stages.

(ii) ²⁷Al and ²⁹Si NMR investigations of aqueous carbonation of Portland cement pastes, incorporating different types of SCMs, reveal that nearly all calcium-bearing phases can be carbonated and thereby, that the initial calcium content governs the CO₂ uptake capacity. A model for deconvolution of the ²⁹Si NMR spectra of the carbonated cement pastes has been established, which has led to a structural model for the alumina-silica gel that accounts for the Al/Si ratio and the degree of polymerization of the gel [2].

(iii) ¹H, ¹³C, and ²⁷Al NMR experiments at very high magnetic field (22.3 T) has been utilized to characterize the structural environments for these elements in the cement hydrate phase, monocarbonate (Ca₄Al₂(OH)₁₂(CO₃)·5H₂O). Here, the combination of the very high magnetic field and ultra-fast MAS ($\nu_R = 100$ kHz) has allowed resolution of the 22 distinct ¹H resonances in a ¹H-¹H SQ-DQ (BABA) MAS experiment. The ¹H resonances are assigned to distinct sites in the hydrogen network from the correlations in the 2D spectrum combined structural relations for ¹H chemical shifts.

References

M. Zajac, I. Maruyama, A. Iizuka, J. Skibsted, *Cem. Concr. Res.* 174, 107285 (2023)

F. M. Neto, R. Snellings, J. Skibsted, *Cem. Concr. Res.* 177, 107428 (2024).

Enhancing magnesium mineral carbonation in Western Australia for sustainable carbon storage

Einar Fridjonsson¹

¹University of Western Australia (*Chemical Engineering*)

e-mail: einar.fridjonsson@uwa.edu.au

The natural global carbon cycle has been overwhelmed by anthropogenic carbon emissions, resulting in rapid increase in atmospheric CO₂. Secure long-term storage of this CO₂ by mineral carbonation (*i.e.* reaction of CO₂ with alkaline solids to form carbonates) is thermodynamically stable, and is the main source of long-term atmospheric cooling on the Earth via silicate weathering processes. It is possible to accelerate such mineral carbonation, but this is complicated by the economic costs, large volumes and long timeframes required for secure CO₂ storage. The process of direct mineral carbonation has in the last decade been demonstrated at industrial scales (e.g. the CarbFix project in Iceland), however these processes typically require specific local geographical advantages. Western Australia (WA) is rich in mafic and ultramafic formations containing minerals critical to future renewable energy technologies, mining these results in large quantities of mafic (magnesium and iron rich) mine tailings. WA is also rich in acidic brine lakes and acidic groundwater networks with low pH, these natural acidic brine lakes are rare globally. These components offer opportunities for developing novel, lower cost mineral carbonation processes in WA to off-set CO₂ production. The current project investigates the combination of acidic brine and mafic mine tailings to enhance the performance of magnesium-based mineral carbonation. An important component of this project is the non-invasive monitoring of the carbonation process using low field nuclear magnetic resonance (NMR), specifically the effect of exposed ferromagnetic surfaces on NMR signal relaxation, for the in-situ measurement of fractional surface coverage by the solid carbonate product. The critical balance between deposition rate and maximum access to, and use of, the tailings pore space can be dynamically probed and is important to assessing volumetric CO₂ storage capacity.

Acknowledgements

This research was funded by the Australian Government through the Australian Research Council DP260104384.

References

- Snæbjörnsdóttir et al. Nat. Rev. Earth Environ. 1.2 (2020): 90-102.
- Blichert-Toft et al. Geochem. Perspect. 12.2 (2023): 179-349.

Monitoring the Hydration of Brazilian Commercial Cements Using Low-Field NMR

PEDRO CESAR RODRIGUES ALVES ABRÃO¹, Arthur Gustavo de Araujo Ferreira², Vanderley M. John³, Tito José Bonagamba⁴

¹Universidade de São Paulo (IFSC), ²Universidade de São Paulo, ³Universidade de São Paulo (PCC Engenharia Civil), ⁴Universidade de São Paulo (São Carlos Institute of Physics)

e-mail: pedro.abrao@lme.pcc.usp.br

Low-field Nuclear Magnetic Resonance (LF-NMR) is a rapid and non-destructive technique with the potential to assess cement reactivity by monitoring water evolution during hydration. This study evaluates the applicability of LF-NMR for monitoring the hydration of Brazilian commercial cements with different chemical compositions.

Six cements were investigated, including one white cement with negligible iron content and five gray cements containing different levels of iron oxide. Hydration was monitored using a SPEC FIT DC low-field NMR system operating at 20 MHz. The NMR results were compared with conventional techniques used to assess cement reactivity, namely isothermal calorimetry and chemically bound water measurements.

The evolution of the NMR signal showed good agreement with both cumulative heat release and chemically bound water, confirming the ability of LF-NMR to track hydration progress. Strong correlations were observed between NMR measurements and the independent hydration indicators, demonstrating the potential of the technique for evaluating the hydration kinetics of commercial cements.

However, differences in NMR signal intensity were observed among cements exhibiting similar hydration behavior according to calorimetry and bound water measurements. In addition, no direct correlation was found between the total iron oxide content measured by X-ray fluorescence (XRF) and the NMR signal intensity. These results suggest that the NMR response is influenced not only by the hydration degree but also by magnetic characteristics of the cement, possibly associated with magnetically active iron-bearing phases.

Overall, the results demonstrate that LF-NMR is a valuable tool for monitoring the hydration of commercial cements and highlight the importance of considering compositional effects when comparing NMR measurements obtained from different cement types.

Acknowledgements

This study was financed, in part, by the São Paulo Research Foundation (FAPESP), Brasil. Process Number 2025/28232-0

Reducing CO₂ Emissions in the Cement Industry

Vanderley M. John¹

¹Sustainable Construction Research Centre, Polytechnic School, University of São Paulo (CICS USP) & hubIC - Hub of Innovation in Construction

e-mail: vmjohn@usp.br

Cement is the world's most produced artificial material, with annual demand of about 4.2 Gt (0.5 t per capita). Its production requires thermal decomposition of limestone, releasing chemically bound CO₂ and emissions from fuel combustion. Despite major efficiency improvements, cement manufacturing still accounts for roughly 6-8% of global anthropogenic CO₂ emissions.

Its environmental footprint extends beyond production. Cement is typically only 15% of the mass of concrete and mortar, making the resource footprint of cement-based materials about eight times larger than cement itself. These materials consume nearly 30% of all extracted natural resources and generate large volumes of long-lived construction waste.

Cement-based materials remain essential because raw materials are widely available, costs are low, and the technology is simple to use, even for untrained workers. These advantages are especially important in developing regions, where future demand will be concentrated.

With conventional mitigation options largely exhausted, the industry expects carbon capture and storage (CCS) to deliver about one-third of future emissions reductions. However, its high cost highlights the need for alternative, rapidly scalable solutions.

Cement consists mainly of CaO, SiO₂, Al₂O₃, and usually Fe₂O₃. It hardens through complex hydration reactions that form new mineral phases. Water is added primarily to achieve the required rheology and often exceeds stoichiometric needs. Excess water creates porosity, which strongly influences strength, stiffness, transport properties, and durability.

Nuclear Magnetic Resonance (NMR) is a valuable tool for monitoring hydration reactions and characterizing hydrated phases, pore volume, and pore-size distribution.

This presentation will discuss low-carbon, low-cost, easy-to-use cement technologies with potential for rapid large-scale deployment and highlight related research opportunities for the NMR community.

References

Scrivener, K., John, V.M., Gartner, E., 2017. Eco-efficient cements: Potential, economically viable, solutions for a low-CO₂, cement-based materials industry (UNEP SBCI). UN Environment, Paris. <http://hdl.handle.net/20.500.11822/25281>

John, V.M., Quattrone, M., Abrão, P.C.R.A., Cardoso, F.A., 2019. Rethinking cement standards: Opportunities for a better future. Cement and Concrete Research 124, 105832.

<https://doi.org/10.1016/j.cemconres.2019.105832>

Richardson, I.G., Taylor, H.F.W., 2025. Cement Chemistry, 3rd ed. ICE Publishing, London.

Soil Pore Size Distribution and Water Retention Curves by Low-Field NMR

Etelvino Henrique Novotny¹, Eduardo Ribeiro de Azevedo²

¹Empresa Brasileira de Pesquisa Agropecuária, ²Universidade de São Paulo (IFSC)

e-mail: Etelvino.novotny@embrapa.br

Freshwater scarcity is a preeminent global challenge, with agriculture alone accounting for 70% of total consumption. Soil's capacity to retain water, filter solutes, and recharge aquifers is dictated by its **Soil Water Retention Curve (SWRC)**. As a fundamental property in soil physics, the SWRC—alongside pore size distribution—is essential for modeling fluid and solute transport within the vadose zone. These properties have critical implications across agriculture, forestry, ecology, and civil engineering.

The Current Bottleneck Despite their importance, quantifying soil hydraulic properties remains a significant challenge. Conventional empirical methods, such as porous plates and pressure cells, are: **Laborious and time-consuming:** *Often taking weeks or months;* **Expensive:** *Requiring specialised, high-maintenance equipment;* **Prone to error:** *Susceptible to operator bias and experimental inaccuracies.*

These limitations make hydraulic characterisation the primary bottleneck in soil physics laboratories worldwide.

A New Analytical Frontier: NMR Relaxometry While ¹H NMR relaxometry has been used to characterise soil porosity, it often presents an "ill-posed problem." Traditional T_1 and T_2 results are confounded by two correlated unknowns: **pore length scales** and **surface relaxivity**.

To overcome this issue, we propose (Novotny et al., 2023) using a method that directly accesses **NMR diffusion modes**. This approach is governed solely by pore size, making it independent of unknown surface relaxivity. Our refined low-field NMR method is: **Fast:** *Delivers results in under 90 minutes;* **Precise:** *Provides unprecedented resolution and accuracy;* **Comprehensive:** *Simultaneously determines pore size distribution, the SWRC, and hydraulic conductivity.*

Validation and Results The results confirm that the proposed approach accurately determines pore size distribution and estimates SWRC in a fraction of the time required by conventional techniques.

Acknowledgements

This study was financed by Finep/CT-Agro/FNDCT (01.22.0081.00, Ref. 1218/21); CNPq (442377/2023-1 and 307694/2023-2) and Faperj (E-26/200.470/2023).

Text improved by Gemini (AI).

References

NOVOTNY, E. H.; AZEVEDO, E.R.; GODOY, G.; CONSALTER, D.M.; COOPER, M. Determination of soil pore size distribution and water retention curve by internal magnetic field modulation at low field ^1H NMR. *Geoderma*, v. 431, 116363. 2023. <https://doi.org/10.1016/j.geoderma.2023.116363>

Soil Strategic Role in Global Food Production and CO2 emissions mitigation

Ladislau Martin-Neto¹

¹Embrapa Instrumentação (R & D)

e-mail: ladislau.martin@embrapa.br

The soil, a very complex porous media, is the third bigger carbon reservoir of Planet, above of the atmosphere and biota pools sizes together, and with around less than half of Geologic pool, which is largely associated with increased greenhouse gas emissions (GHG) and climate change impacts. Besides to be an important carbon reservoir soil is pivotal to global agricultural sector that is one of few economic sectors that can work to reduce their own GHG emissions, using more sustainable practices, and simultaneously contribute to carbon sequestration, incorporated as a natural increase of soil organic matter content. So, in recent years soil has received a massive scientific effort to face adaptation and mitigation to global climate change challenges. In this presentation will be described a short overview of recent soil carbon scientific findings and combined with our research data of soil carbon sequestration from long term field experiments and large farms operations, and that includes innovative high and low field nuclear magnetic resonance results, demonstrating interesting achievements to conciliate agriculture and GHG emissions mitigation.

Magnetic Resonance in Porous Media 2026



Grouperment
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

05

Mobile NMR

ORAL PRESENTATIONS



RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026

3D printed passive shims for permanent magnets: Application to iron-pole, Halbach arrays, and a unique tilted field magnet

Andrew McDowell¹

¹NuevoMR, LLC

e-mail: mcdowell@nuevomr.com

Magnetically soft materials offer significant advantages over hard materials for implementing passive shims. In previous work, we have leveraged the ease of handling, the high precision and accuracy, and the low cost of magnetic ink to shim high-performance iron-pole magnets to sub ppm homogeneity.

For lower homogeneity magnets, for example those designed for time-domain measurements, the ink is not magnetically strong enough. For these magnets, we have been using 3D printed magnetic filament to achieve field improvements. We have found that readily available filament and a mid-level 3D printer are more than adequate for producing passive shims that substantially improve homogeneity. The precision is high enough that it is worthwhile to develop custom slicing software to drive the printer, thereby enabling improved accuracy in producing the calculated shim design.

We have applied 3D printed passive shims in a 0.3 T, 60 mm gap iron-pole magnet from Fine Instrument Technology (Brazil), reducing the peak-to-peak field variation over a 40 mm diameter sphere from 570 to 220 ppm. The final field error is almost entirely due to a Z^6 field, which is of high enough mathematical order that it has minimal impact on the NMR signal.

Halbach array/ring magnets can also be shimmed this way. For two magnets with 40 mm bores, we have achieved improvement over a 40 mm diameter sphere from 5625 to 221 ppm at 0.5 T and 400 to 14 ppm at 1.4T.

Presently, we are applying our methods to a 0.08 T cylindrical magnet from RE Magnet Studio, Ltd. that has a field pointing at 54.7 degrees with respect to the cylinder axis. We discuss the challenges of designing shims for such a magnet and (time permitting) the resulting homogeneity improvement.

References

A.F. McDowell and R.R. Lown, "Designing and shimming Halbach Array magnets," JMR Open, submitted.

Compact and Mobile NMR

Bernhard Bluemich^{1,2}

¹RWTH Aachen University, ²Institut für Technische und Makromolekulare Chemie (*Chemistry*)

e-mail: bluemich@itmc.rwth-aachen.de

The beginnings of compact NMR can be traced to the introduction of tabletop relaxometers for food quality control and materials testing in the early 1970ies. Mobile NMR started even earlier in the 1950ies with the exploration of earth-field NMR for well logging. It received a decisive boost with the introduction of permanent magnets in 1980, which enabled the sensitive volume to be localized in the stray field of the magnet. A derivative of this development are small stray-field devices for materials testing, one of which is the NMR-MOUSE. Efforts to shape the stray magnetic field benefitted the development of compact centerfield magnets for benchtop NMR spectroscopy with fields sufficiently homogeneous to resolve the chemical shift of protons in liquids. Miniaturizing the electronics and the magnet even further pushes the application of handheld centerfield relaxometers and miniature magnetic resonance sensors. Such sensors are particularly useful for rapid testing of short-lived and degradable products. The development of compact and mobile NMR is reviewed with attention to current developments and concluded with a recent study of an antique, late-Roman burial chamber in Trier, where moisture flux towards the surface of a naturally wet wall has been estimated based on NMR depth profiles and Fick's first law.

Acknowledgements

This parts of this work were funded by Deutsche Forschungsgemeinschaft (DFG), project number 450272390.

References

- B. Blümich, Low-field and benchtop NMR, *J. Magn. Reson.* 306 (2019) 27.
- J.A. Jackson, L.J. Burnett, J.F. Harmon, Remote (inside-out) NMR. III. Detection of nuclear magnetic resonance in a remotely produced region of homogeneous magnetic field, *J. Magn. Reson.* 41 (1980) 411.
- C. Golini, Q. Yang, M. Waldecker, et al., Investigation of the late-Roman burial chamber at Reichertsberg in Trier by NMR depth profiling, *Solid-State Nucl. Magn. Reson.* 143 (2026) 102074.

Drug-Assisted Network Formation in Biopolymeric Wound Dressing Membranes Revealed by Single-Sided and Benchtop NMR

Yamila Garro Linck^{1,2}, Patricio Díaz Marull^{1,2}, Fiamma Barbieri^{1,2}, María Eugenia Olivera^{1,2},
Gustavo A. Monti^{1,2}, Rodolfo Acosta^{3,2}

¹Universidad Nacional de Córdoba, ²CONICET, ³Universidad Nacional de Córdoba (FAMAF)

e-mail: y.garrolinck@unc.edu.ar

Burn wound dressings based on hydrophilic biopolymers require controlled network formation for adequate structural properties and drug retention. Although ionic crosslinkers are commonly used, the role of active pharmaceutical ingredients (APIs) in membrane structuring remains unclear. This study investigated whether an antibiotic and an anesthetic contribute to network formation during membrane fabrication. Membranes were prepared by solvent casting from molded bicomponent hydrophilic biopolymer hydrogels, using calcium gluconate as a reference ionic crosslinker. The hydrogel-to-membrane transition was monitored by single-sided ¹H NMR at 34 and 40 °C through drying profiles and T₁/T₂ relaxation measurements. Complementary ²³Na benchtop NMR experiments were performed to investigate formulation-dependent changes in the ionic environment. Drying profiles showed matrix contraction followed by dimensional stabilization despite continued evaporation. Crosslinked formulations exhibited two drying regimes independent of temperature, whereas non-structured systems showed one. The transition to the slower regime occurred at a membrane thickness of ~1.1 mm regardless of temperature, suggesting that membrane formation and surface barrier development are driven by structural rather than thermal effects. All formulations reached a similar final thickness, independent of crosslinker and temperature, although faster at 40 °C than at 34 °C. Membranes containing APIs showed restricted molecular mobility comparable to calcium-gluconate-crosslinked systems. Preliminary ²³Na NMR results indicated formulation-dependent ionic interactions during network formation. These findings indicate that APIs actively contribute to network development during membrane formation. The resulting structural constraints are comparable to those achieved with a conventional ionic crosslinker, supporting the design of self-structuring drug-loaded biopolymeric membranes without additional crosslinking agents.

Acknowledgements

This study was financed by CONICET and SECyT-UNC.

References

- S. Karki, H. Kim, S.-J.J. Na, D. Shin, K. Jo, J. Lee, Thin films as an emerging platform for drug delivery, *Asian J. Pharm. Sci.* 11 (2016) 559–574.
- S. Ghoshal, P. Denner, S. Stapf, and C. Mattea, Study of the Formation of Poly(vinyl alcohol)

Films. *Macromolecules* 2012, 45, 1913–1923.

C. Zhao, C. Zhang, H. Kang, Y. Xia, K. Suia, Ruigang Liu, Gelation of Na-alginate aqueous solution: A study of sodium ion dynamics via NMR relaxometry. *Carbohydrate Polymers* 169 (2017) 206–212

Facility-scale NMR studies of complex mining tailing materials

Hamed Derakhshandeh¹, Elena Kozlovskaya², Ville-Veikko Telkki¹, Vladimir V. Zhivonitko¹

¹University of Oulu / Oulun yliopisto (NMR research unit) , ²University of Oulu / Oulun yliopisto (Oulu mining school)

e-mail: Hamed.derakhshandeh@oulu.fi

Mining tailings storage facilities (TSFs) require reliable methods for assessing sedimentation, compaction, and drying, since these processes directly affect water recovery, geotechnical stability, and long-term environmental performance. In our recent work, we established a portable single-sided NMR methodology based on the NMR-MOUSE for monitoring water-content and water-mobility changes in complex gold-mine tailings through ¹H signal amplitudes and transverse relaxation times (T_2). The method was validated against tailings samples from a TSF in Lapland, Finland, and revealed clear relationships between NMR response, particle-size distribution, mineral composition, solids content, and the kinetics of sedimentation and dewatering.

In this contribution, we extend that methodology from controlled laboratory studies toward facility-scale assessment of beach-deposited tailings in Lapland. Measurements collected from different locations and depths are used to evaluate spatial variability in tailings behavior across the deposit and to test how well the NMR observables reflect local differences in consolidation state and moisture distribution under field-relevant conditions. Emphasis is placed on the capability of the method to distinguish rapid short-term settling from slower structural reorganization and drying, and to identify zones where mineralogical and granulometric heterogeneity control the NMR response. The approach follows the framework established in our recent publication, where faster-settling samples were associated with coarser particles and higher final T_2 values, whereas finer and more heterogeneous materials showed delayed settling and more restricted water mobility.

The results demonstrate that portable single-sided NMR has strong potential for near-real-time characterization of tailings at the facility scale. By linking NMR measurements with physical and mineralogical properties, the method support sustainable tailings management.

Acknowledgements

This work was supported by the funding from the European Union's Horizon Europe research and innovation program under the Marie Skłodowska-Curie grant agreement no. 101081280.

References

Derakhshandeh, S., Nousiainen, J., Piekkari, M., Karvo, J., Auer, A., Luukkanen, S., ... & Zhivonitko, V. V. (2026). Characterization of the sedimentation and drying processes of complex mining tailings materials using NMR. *Physical Chemistry Chemical Physics*, 28(1),

52-66.

B. Blümich , S. Anferova , R. Pechnig , H. Pape , J. Arnold and C. Clauser , J. Geophys. Eng.,
2004, 1 , 177 —180

Probing Solid-Liquid Separation Dynamics in Anaerobic Digestate via 1D and 2D Low-Field NMR Relaxometry

Einar Fridjonsson¹, Emanuel Gpmes Bertizzolo²

¹University of Western Australia (*Chemical Engineering*) , ²The University of Western Australia (*Chemical Engineering*)

e-mail: einar.fridjonsson@uwa.edu.au

Anaerobic digestate (AD) is a nutrient-rich residue of anaerobic digestion with potential as a biobased fertiliser, yet conventional metrics like turbidity and total solids are time-intensive and lack structural sensitivity. LF-NMR relaxometry offers a non-invasive route to characterise water distribution independently of sample opacity. Treating flocculated digestate as a porous medium with free (P1), interstitial (P2), and vicinal (P3) populations, this work applies 1D and 2D LF-NMR to two AD feedstocks. Red meat (RM) AD and food water (FW) AD were conditioned with flocculant (EM640CT (0.41% active)) across 0 to 4.5 and 0 to 25.5 wt%, and monitored using a 12.7 MHz Oxford GeoSpec and 14 MHz ilumr. T_2 CPMG (25,000 echoes, $t_e = 300 \mu\text{s}$), T_1 - T_2 IR-CPMG⁴ (32 steps, 10,000 echoes), and T_2 - T_2 CPMG-CPMG ($t_e = 300 \mu\text{s}$, $t_{\text{mix}} = 5$ to 300 ms) were applied; T_2 resolved by regularised inversion into four populations (P1 to P4). For RM-AD, polymer conditioning produced a T_2 shift from 0.19 to 1.77 s, transitioning the dominant population from interstitial (P2) to free water (P1) beyond a critical threshold, a nearly fivefold increase in recovered solids. For FW-AD, the same flocculant at doses up to fivefold higher produced negligible T_2 redistribution, consistent with EPS, DOM, and FOG-driven inhibition. T_1 - T_2 maps confirmed T_1/T_2 proportionality with surface-to-volume ratio. T_2 - T_2 exchange spectroscopy revealed off-diagonal cross-peaks (P2-P3) at $t_{\text{mix}} = 100 \text{ ms}$ in RM-AD, a coherence length $\sim 35 \mu\text{m}$; no exchange peaks detected in FW-AD. 1D and 2D LF-NMR resolve microstructural changes inaccessible to conventional process metrics. T_2 - T_2 exchange reveals the same polymer produces a coherent $\sim 35 \mu\text{m}$ network in RM-AD but fails in FW-AD, undetectable by turbidity or total solids metrics. Future work will integrate mobile LF-NMR into a pilot-plant AD facility for continuous flocculation monitoring.

References

Bertizzolo, E. G. et al. Monitoring settling of anaerobic digestates using low-field MRI profiling and NMR relaxometry measurements. *Water Research* 245, 9 (2023).

Maillet, B., Sidi-Boulenouar, R. & Coussot, P. Dynamic NMR Relaxometry as a Simple Tool for Measuring Liquid Transfers and Characterizing Surface and Structure Evolution in Porous Media. *Langmuir* 38 (2022).

Callaghan, P. T. Principles of nuclear magnetic resonance microscopy. (Oxford: Clarendon Press, 1993).

Single-Sided NMR Relaxometry and Diffusometry Across Porous Media Applications

Leonardo Brizi¹

¹Università di Bologna (*Physics and Astronomy*)

e-mail: leonardo.brizi2@unibo.it

Single sided NMR provides a framework for performing portable, non-invasive investigations of porous media through depth-selective relaxometry and diffusometry. The NMR-MOUSE device was exploited with 1D profiling and multidimensional correlation experiments to extract quantitative markers of layer structure, pore connectivity, and fluid transport in heterogeneous porous systems spanning cultural heritage^{1,2}, cementitious materials, and biological tissues³. In the case of paintings on canvas¹, T_2 distributions and signal-intensity depth profiles are correlated with stratigraphic cross-sections. This approach enhances the identification of textile support, preparatory grounds, and paint layers. Furthermore, it highlights the challenges intrinsic to inhomogeneous, partially overlapping strata that contribute jointly to the sensitive volume. About stone conservation², single-sided profiles are used to evaluate penetration depth and homogeneity of consolidation treatments. In cement pastes, low-field measurements have been shown to monitor hydration-driven decreases in T_1 and T_2 . Furthermore, via T_1 - T_2 correlation maps, these measurements have been demonstrated to resolve interlayer and gel-pore water populations, characterised by distinct T_1/T_2 ratios and sensitivity to binder composition and paramagnetic iron content. In the field of biomedical studies, the exploitation of strong static gradients for diffusion-weighted contrast is a key approach. Diffusion-weighted T_1 - T_2 encoding has been shown to suppress muscle/cartilage signal, thereby enabling trabecular-bone BV/TV estimation. Furthermore, depth-wise multiparametric mapping of articular cartilage³, supported by multivariate data analysis, provides a method of differentiating layered structures. Collectively, these studies demonstrate the effectiveness of single-sided NMR as a powerful and versatile tool for in situ diagnostics, monitoring of treatments and microstructural evolution in a wide range of porous media.

References

L Brizi, V Bortolotti, G Marmotti, M Camaiti. Identification of complex structures of paintings on canvas by NMR: Correlation between NMR profile and stratigraphy. *Magnetic Resonance in Chemistry* 58 (9), 889-901 (2020).

L Brizi, M Camaiti, V Bortolotti, P Fantazzini, B Blümich, S Haber-Pohlmeier. One and two-dimensional NMR to evaluate the performance of consolidants in porous media with a wide range of pore sizes: Applications to cultural heritage. *Microporous and Mesoporous Materials* 269, 186-190 (2018).

C Golini, M Barbieri, A Nagmutdinova, V Bortolotti, C Testa, L Brizi. Depth-wise

multiparametric assessment of articular cartilage layers with single-sided NMR. *NMR in Biomedicine* 38 (1), e5287 (2025).

Magnetic Resonance in Porous Media 2026



Groupe ment
AMPERE


17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

06

Advances in Mathematics, Engineering, AI, and Quantum Computing

ORAL PRESENTATIONS



RIBEIRÃO PRETO & CAMPINAS, BRAZIL

OCTOBER 26–30, 2026

A compative study of effective surface relaxation estimation using two NMR relaxometry inverse modeling approaches

MARTIN ALBERTO DIAZ VIERA¹, Sinai Morales Chávez², Luis Constante³, Adolfo Puime Pires³, Tito José Bonagamba^{4,5}

¹MEXICAN PETROLEUM INSTITUTE (*Research in Exploitation*) , ²MEXICAN PETROLEUM INSTITUTE, ³Universidade Estadual do Norte Fluminense Darcy Ribeiro (*Laboratório de Engenharia e Exploração de Petróleo*) , ⁴Universidade de São Paulo (*São Carlos Institute of Physics*) , ⁵Universidade de São Paulo

e-mail: mdiazv@imp.mx

This talk presents a comparative analysis of two advanced inverse modeling approaches for estimating the properties of porous media from NMR relaxometry signals. While inverse NMR relaxometry (T_1/T_2 distribution recovery) is a fundamental technique for characterizing pore-scale structures based on surface-influenced molecular relaxation, the choice of inversion methodology has a critical impact on the reliability and efficiency of the results. We specifically evaluate a rigorous **Bayesian framework with Markov Chain Monte Carlo sampling (MCMC)** [1] against a modern **Physics-Informed Neural Network (G-PINN) based on a Galerkin formulation** [2]. The comparison is made in terms of numerical accuracy, uncertainty quantification, and computational performance. Using synthetic NMR relaxometry signals—generated from both analytical and direct numerical models—the two approaches for estimating the **effective surface relaxation** are compared. The details of the complete methodological process are presented, encompassing mathematical formulations, numerical discretizations, and computational implementations, providing a guide for selecting an inversion approach tailored to the quality of the data and the specific requirements of the application.

References

- Morales-Chavez, S., Valdez-Grijalva, Diaz-Viera, M.A., Lucas-Oliveira, E., & Bonagamba, T.J. (2025). A mathematical model of NMR transverse relaxation for pore size distribution estimation in porous media. *Journal of Magnetic Resonance*, 379, 107922.
- Constante, L., Pires, A., Díaz-Viera, M.A. (2026). Galerkin Physics-Informed Neural Network Approach for Inverse Problems. Application to Estimation of Tracer Dispersion in Porous Media, *Computational Geosciences* 30(24).

A Two-Stage Galerkin Physics-Informed Neural Network Approach for Forward and Inverse Nuclear Magnetic Resonance Modeling at the Pore Scale

Luis Constante¹, Adolfo Puime Pires², MARTIN ALBERTO DIAZ VIERA³, Sinai Morales Chávez⁴

¹Universidade Estadual do Norte Fluminense Darcy Ribeiro, ²Universidade Estadual do Norte Fluminense Darcy Ribeiro (*Laboratório de Engenharia e Exploração de Petróleo*) , ³MEXICAN PETROLEUM INSTITUTE (*Research in Exploitation*) , ⁴Instituto Mexicano del Petróleo

e-mail: luispatricio1987@hotmail.com

Nuclear Magnetic Resonance (NMR) is widely used in reservoir characterization to evaluate pore-scale properties and fluid behavior in porous media. However, solving forward and inverse pore-scale NMR problems remains computationally challenging due to the coupled diffusion-relaxation mechanisms governing magnetization dynamics. Conventional numerical methods often require fine spatial discretization and high computational cost, particularly in inverse workflows. This work proposes a Pre-Trained Galerkin Physics-Informed Neural Network (pG-PINN) (Constante *et al.*, 2026) approach for solving direct and inverse pore-scale NMR problems in spherical pores. The methodology combines Galerkin-based domain decomposition with physics-informed learning to approximate the Bloch-Torrey diffusion-relaxation equation under diffusion-controlled relaxation conditions. Multiple compact neural subnetworks act as adaptive basis functions, improving training stability and solution accuracy near pore boundaries, where relaxation effects dominate. For the forward problem, the model predicts the spatiotemporal evolution of magnetization and reconstructs NMR relaxation responses for different pore radius, diffusion coefficients, and surface relaxivities. For the inverse problem, the pG-PINN estimates surface relaxivity directly from synthetic NMR relaxation responses. A two-stage pre-training strategy is introduced to accelerate convergence and improve parameter identification. The proposed approach was validated against analytical solutions for spherical pore geometries. Results demonstrate that the pG-PINN achieves high accuracy with reduced computational cost compared with conventional numerical approaches while maintaining robust inverse estimation capability under noisy conditions. The methodology provides an efficient and flexible alternative for AI-driven pore-scale NMR modeling and digital rock physics applications.

References

Luis Constante, Adolfo Pires, Martín A. Díaz-Viera. Galerkin physics-informed neural network approach for inverse problems. Application to estimation of tracer dispersion in porous media. Computational Geosciences. Springer. 2026.

Categorical Diversity Optimization: A framework for inversion and component analysis of NMR data

Moacyr Nascimento¹

¹Petróleo Brasileiro S.A (CENPES)

e-mail: moacyrnascimento@gmail.com

Classification of probed nuclei in NMR relaxometry via relaxation rate spectra is presented as a paradigmatic Categorical Inverse Problem (CIP)—a mixture model problem aiming to find a distribution of known types proportionally linked to a dataset. Here, the categorical set is a partitioned interval, mapping relaxation rate bands onto signal amplitudes via a discretized continuous response model related to the Laplace transform.

I define CIP generally to emphasize its normalization condition and present proper data preconditioning and denoising strategies for applying the principle of Categorical Diversity Optimization: Selection of either the most or least diverse distributions representing a solution set.

By varying diversity measures, the framework establishes a continuum of well-posed inverse problems for any dataset, proving a continuum of uniquely characterized distributions exists as special CIP solutions. This quality unifies traditional inversion methods like Entropy Maximization, Non-negative Least Squares, and the Minimax Principle under a single banner.

Effective 1D and 2D computational algorithms to compute these solutions are advanced, alongside theoretical results on their categorical support and the influence of noise.

As diversity measures differ mainly on how they weigh the contribution of rarer categories, their choice yields distinct qualitative and quantitative descriptions, yet numerical maximal diversity solutions display a remarkable consistency of signatures. Comparisons of minimal and maximal diversity solutions for polyexponential signal decay exemplify the impact of optimization principle.

Finally, the framework's versatility is demonstrated by unmixing problems based on NMR relaxometric data, where mixed signals of unknown proportions are decomposed using a few referential component decays. Potential applications in Quality Control and Petrophysical Evaluation are considered together with current methodological limitations.

References

Hansen, Per Christian. Discrete inverse problems: insight and algorithms. Society for Industrial and Applied Mathematics, 2010.

Polyanskiy, Yury, and Yihong Wu. Information theory: From coding to learning. Cambridge

university press, 2025.

Jost, Lou. "Entropy and diversity." *Oikos* 113.2 (2006): 363-375.

Mapping local foam mobility in porous media from computed tomography data

Grigori Chapiro¹

¹Universidade Federal de Juiz de Fora (*Mathematics*)

e-mail: grigorichapiro@gmail.com

Recovering apparent viscosity and foam texture fields from coreflooding experiments is challenging, even with modern computed tomography (CT) scan equipment. In this work, we present an explicit expression for efficiently calculating the effective foam viscosity and propose an improved procedure for processing CT scan images to obtain accurate water-saturation profiles. Using these techniques, we processed CT scan data from a coreflooding experiment, showing that the increase in effective foam viscosity due to foam generation occurs early during injection, before breakthrough. The rapid increase in apparent viscosity is due to foam formation before breakthrough. After the breakthrough, the foam texture reaches its maximum, and the effective foam viscosity increases logarithmically over time as the foamed gas sweeps out the water phase. The pressure drop obtained using the effective foam viscosity showed good agreement with the experimental values before breakthrough. The workflow proposed here could be readily adapted to other foam models, provided reasonable estimates for these new quantities can be determined from experiments.

Acknowledgements

The authors gratefully acknowledge support from Shell Brasil through the "Avançando na modelagem matemática e computacional para apoiar a implementação da tecnologia 'Foam-assisted WAG' em reservatórios do Pré-sal" ANP 23518-4 project at UFJF and the strategic importance of the support given by ANP through the R&D levy regulation. G.C. was supported in part by CNPq grants 306970/2022-8, 405366/2021-3, and FAPEMIG grant APQ-00405-21.

References

Chapiro, G., Quinelato, T. O., Pereira, W., dos Santos, R. W., and P. L. J. Zitha. "On Mapping Local Foam Mobility in Porous Media from Computed Tomography Data." SPE J. 29 (2024): 6096-6107. doi: <https://doi.org/10.2118/223115-PA>

Microfluidics as a Tool to Study Pore-Scale Phenomena in Complex Multiphase Flow in Porous Media

Marcio Carvalho¹

¹Pontifícia Universidade Católica do Rio de Janeiro (*Department of Mechanical Engineering*)

e-mail: msc@puc-rio.br

Multiphase flow in subsurface formations is ubiquitous in both oil production and CO₂ storage. The non-linear nature of the flow leads to complex fluid displacement mechanisms that operate across various scales, from pore-level to Darcy scale. Accurate flow models, necessary in the design and optimization of injection processes, require detailed description of pore scale multiphase flow. Traditionally, flow behavior at different temperature and pressure conditions is evaluated on laboratory-scale experiments using core-flooding systems, PVT cells and other equipment. The experiments are expensive, require long measurement times and large volumes of fluids. In this context, microfluidics emerges as a valuable technique. Improvement on the fabrication of microfluidic devices and flow control have led to growth in the use of microfluidics to gain fundamental understanding of pore-scale multiphase flow, enabling the correlation between pore scale events and macroscopic flow characteristics, and phase behavior. Recent developments allow microfluidic experiments to be run at high pressure and high temperature conditions, allowing the determination of minimum miscibility pressure between CO₂ and crude oil in approximately 30 minutes and using only 0.1 mL of oil sample for each data point.

Here, we report various multiphase flow analyses using porous media microfluidic devices to examine oil displacement by water, emulsions, and foam, as well as CO₂ storage in saline aquifers. By visualizing pore-scale phenomena, we can correlate these events with macroscopic flow characteristics, which may be leveraged to optimize subsurface processes.

Acknowledgements

This study was financed by CAPES, CNPq, Petrobras and CNODC Brasil.

References

- J. Fernandez, A. C. S. N. Pessoa, C. de Amorim, J. Avendano, M. S. Carvalho, "From pore-scale physics to relative permeability curves in porous media micromodels with different wettability", *Advances in Water Resources*, 203, 105038, 2025.
- N. Lima, S. Parsa, S. Paciornik, M. S. Carvalho, "Foam formation during drainage of a surfactant solution in a microfluidic porous medium model", *Scientific Reports*, 13:21802, 2023.
- C. de Amorim, R. V. de Almeida, R. V. Ponce, M. S. Carvalho, "Visualization and

Quantification of Mobility Reduction in Porous Media Flow Associated with Pore Blocking by Emulsion Drops”, Industrial & Engineering Chemistry Research, 62 (51), 22093-22102, 2023.

Quantum Computing and Porous Media: Applications in CO₂ Capture & Storage

Mathias B Steiner¹

¹Kunumi (*Quantum Computing*)

e-mail: mathiasbsteiner@gmail.com

Mitigating climate change requires efficient computational frameworks for simulating CO₂ capture and storage. In this presentation, I introduce an open simulation environment for pore-scale assessment in digital rock [1] that creates accurate capillary network representations [2] based on microscopic tomography data taken from sandstone and carbonate rock plugs [3]. Single-phase and two-phase flow simulations within a digital rock's capillary network can be performed assuming realistic reservoir conditions. One research use case of the simulator is the injection of super-critical carbon dioxide into sandstone, for optimizing carbon dioxide saturation as function of temperature and pressure, respectively [4]. For predicting the long-term geologic storage of carbon dioxide, the simulator tracks computationally the modifications caused by carbon mineralization within each capillary of the connected pore space [1]. The process gradually reduces the diameter of capillaries over time and causes the porosity and permeability of the rock to degrade. If flow conditions are not optimized, a rock might not achieve its full geologic storage potential.

While having the potential for improving the simulation of flow in digital rock, current applications of quantum computing are mainly in the prediction of materials properties at molecular scale [5]. One example is the binding of carbon dioxide in nano-pores designed for application in direct air capture [6]. Hybrid, quantum-classical algorithms on pre-fault tolerant quantum processing units deliver useful predictions and are a promising approach for advancing the discovery of novel materials for carbon dioxide capture.

References

D. A., Lazo Vasquez, et al. "Simulating Carbon Mineralization at Pore Scale in Capillary Networks of Digital Rock". *Transp Porous Med* 152, 64 (2025). <https://doi.org/10.1007/s11242-025-02193-1>

R. F. Neumann, et al. "High accuracy capillary network representation in digital rock reveals permeability scaling functions". *Sci Rep* 11, 11370 (2021). <https://www.nature.com/articles/s41598-021-90090-0>

M. Esteves Ferreira, et al., "Full scale, microscopically resolved tomographies of sandstone and carbonate rocks augmented by experimental porosity and permeability values". *Sci Data* 10, 368 (2023). <https://doi.org/10.1038/s41597-023-02259-z>

Quantum Computing Applied to Oil & Gas Problems

Ivan S. Oliveira¹

¹Brazilian Center for Research in Physics

e-mail: ivans0565@gmail.com

The oil and gas exploration industry demands the use of high-performance computing for subsurface modeling from seismic data. Such modeling supports decision-making regarding the drilling of new wells, a decision that involves investments on the order of hundreds of millions of dollars. Quantum computing emerges in this context as a promising tool, proposing algorithms capable of accelerating the solution of numerical problems, notably the so-called inversion problem. Other relevant applications that have been explored by quantum computing include, significantly, simulations of wave propagation in heterogeneous media and the search for new materials with potential for carbon capture. On this talk, these applications will be discussed, as well as the main bottlenecks of quantum computing regarding industrial applications.

Acknowledgements

This study is financed by Exxon Mobil of Brazil.

References

Potential impacts of quantum computing of full-wave inversion and reservoir simulation, in preparation.

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE


17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

01

Digital Porous Media & NMR

POSTER PRESENTATIONS



RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026

Bayesian framework for inverse modeling in estimating porous media properties from Nuclear Magnetic Resonance signals

Sinai Morales Chávez¹, MARTIN ALBERTO DIAZ VIERA², Adolfo Puime Pires³, Luis G. Constante⁴, Tito José Bonagamba⁵

¹MEXICAN PETROLEUM INSTITUTE, ²MEXICAN PETROLEUM INSTITUTE (*Research in Exploitation*), ³Universidade Estadual do Norte Fluminense Darcy Ribeiro (*Laboratório de Engenharia e Exploração de Petróleo*), ⁴Universidade Estadual do Norte Fluminense Darcy Ribeiro, ⁵Universidade de São Paulo (*São Carlos Institute of Physics*)

e-mail: geomorales91@gmail.com

Quantitative analysis of Nuclear Magnetic Resonance (NMR) relaxation data is essential for characterizing heterogeneous porous media. Outside the fast-diffusion regime, traditional inversion methods that assume a mono-exponential decay per pore oversimplify the problem, leading to a severely ill-posed inverse problem where surface relaxivity and pore size cannot be independently resolved without multi-modal or regularized approaches (Morales-Chávez et al., 2025).

To overcome this challenge, this work proposes a robust probabilistic inverse modeling framework based on a non-dimensional formulation of the Bloch-Torrey equation. Building upon recent advancements in probabilistic modeling for NMR parameter extraction (Li et al., 2021), the forward problem is solved with the Finite Element Method (FEM) and rigorously validated against the semi-analytical Brownstein-Tarr solution. Bayesian inference is performed via the t-walk Markov Chain Monte Carlo algorithm (Christen et al., 2010) to estimate the dimensionless surface relaxivity (α) and pore radius (φ_R) and then verified through twin experiments using synthetic data with additive Gaussian noise.

A comprehensive set of eight test cases were evaluated, systematically varying physical parameters across the fast, intermediate, and slow diffusion regimes, with pore radii ranging from 1 μm to 1000 μm and surface relaxivities from 3 $\mu\text{m/s}$ to 40 $\mu\text{m/s}$. Results demonstrate that the non-dimensional formulation effectively decorrelates the parameters, thereby resolving the degeneracy. Maximum A Posteriori (MAP) estimates recover the true petrophysical properties with high accuracy and robustness, accompanied by rigorous uncertainty quantification.

References

Morales-Chávez, S., Valdez-Grijalva, M. A., Diaz-Viera, M. A., Lucas-Oliveira, E., & Bonagamba, T. J. (2025). A mathematical model of NMR transverse relaxation for pore size distribution estimation in porous media. *Journal of Magnetic Resonance*, 379, 107922.

Li, R., Shikhov, I., & Arns, C. H. (2021). Solving multiphysics, multiparameter, multimodal

inverse problems: an application to nmr relaxation in porous media. *Physical Review Applied*, 15(5), 054003.

Christen, J.A. and Fox, C. (2010), "A General Purpose Sampling Algorithm for Continuous Distributions (the t-walk)", *Bayesian Analysis*, 5(2), 263-282.

Computational toolkit for simulating the Nuclear Magnetic Resonance response of porous media

Henrique Yan de Seta Coutinho¹, Ricardo Leiderman¹, Luiz Fernando Bez¹, Alexsander Marciano da Cunha¹, Andre Maues Brabo Pereira¹, Andreas Muzzi¹, Fellipe Carvalho Pombo Lima¹, ARTHUR COSTA POYARES ROCHA²

¹Universidade Federal Fluminense (*Scientific Computing Lab - LCC*) , ²Universidade Federal Fluminense (*Ciência da Computação (TCC)*)

e-mail: henriqueyan@id.uff.br

Here we introduce an in-house developed computational toolkit for simulating the Nuclear Magnetic Resonance response of porous media. The collection of Python implementations uses high-performance parallelism strategies to simulate Nuclear Magnetic Resonance experiments from 3D microtomographic digital images. Our toolkit has been employed to investigate direct and inverse problems considering different applications, including relaxometry, diffusometry, multi-tau, and DDIF. Among the investigations, we may emphasize advanced strategies to estimate the surface relaxivity, statistical analysis and uncertainty propagation in relaxometry, and the feasibility of using machine learning for permeability estimations. Further, our implementations served as basis for the development of a virtual Nuclear Magnetic Resonance profiling tool.

References

RIBEIRO, M. C.; FILGUEIRAS, J. G.; SOUZA, A.; VIANNA, P. M.; DE AZEREDO, R. B. V.; LEIDERMAN, R. Image-based simulation of molecular diffusion on NMR Pulsed-Field Gradient experiments: Feasibility to estimate tortuosity and permeability of porous media. *Journal of Petroleum Science and Engineering*, v. 219, art. 111064, 2022. DOI: 10.1016/j.petrol.2022.111064.

BEZ, Luiz F.; LEIDERMAN, Ricardo; SOUZA, André; AZEREDO, Rodrigo B. de V.; PEREIRA, André M. B. Large Scale Voxel-Based FEM Formulation for NMR Relaxation in Porous Media. *Transport in Porous Media*, v. 151, p. 2405-2430, 2024. DOI: 10.1007/s11242-024-02118-4.

Pore size distribution from NMR and image based methods: A comparative studyBENAVIDES, F.; et al. Pore size distribution from NMR and image based methods: A comparative study. *Journal of Petroleum Science and Engineering*, v. 179, p. 829-839, 2019. DOI: 10.1016/j.petrol.2019.04.083.

Evaluating Magnetic Surface Relaxivity through NMR Simulations in Digital Porous Media

Everton Lucas-Oliveira¹, Nathaly Lopes Archilha², Rodrigo Surmas³, Arthur Gustavo de Araujo Ferreira⁴, Willian Andrighetto Trevizan⁵, Tito José Bonagamba⁶

¹Brazilian Center for Research in Energy and Materials (*Brazilian Synchrotron Light Laboratory (LNLS)*) , ²Brazilian Center for Research in Energy and Materials, ³Centro de Pesquisa, Desenvolvimento e Inovação Leopoldo Américo Miguez de Mello, ⁴Universidade de São Paulo, ⁵Petroleo Brasileiro SA (*Cenpes*) , ⁶Universidade de São Paulo (*São Carlos Institute of Physics*)

e-mail: everton.oliveira@lnls.br

The fourth-generation synchrotrons deliver low- to high-energy X-rays with high photon flux, enabling high-resolution 3D tomography within seconds when combined with advanced detectors. The MOGNO beamline [1] at the Brazilian Synchrotron Light Laboratory (LNLS), located at Brazilian Center for Research in Energy and Materials (CNPEM), provides nano- to micrometer-scale computed tomography for multiscale analysis, including zoom tomography with a spatial resolution of approximately 200 nm and 4D imaging through *in situ* experiments with time resolutions on the order of a few seconds. Within this context, current efforts focus on integrating microtomography with complementary techniques to elucidate the physicochemical behavior of porous materials, particularly fluid-solid interactions and transport processes at the pore scale. Nuclear Magnetic Resonance (NMR) plays a central role in porous media characterization, both in laboratory studies and *in situ* applications. NMR enables fluid characterization while also providing morphological information, such as pore-size distribution and pore connectivity. Furthermore, wettability and magnetic surface relaxivity, parameters governed by the rock mineralogy, influence relaxation times and provide additional insight into the properties of porous media [2].

The integration of zoom tomography with NMR therefore offers a promising framework for investigating porous media under both static and dynamic conditions. In this work, we present NMR simulations in digital porous media and compare the magnetic surface relaxivity estimated directly from NMR measurements with that obtained from computational simulations.

References

Archilha, N. L et al. (2022, December). MOGNO, the nano and microtomography beamline at Sirius, the Brazilian synchrotron light source. In *Journal of Physics: Conference Series* (Vol. 2380, No. 1, p. 012123). IOP Publishing.

Lucas-Oliveira, E., Araujo-Ferreira, A. G., & Bonagamba, T. J. (2021). Surface relaxivity probed by short-diffusion time NMR and digital rock NMR simulation. *Journal of Petroleum Science and Engineering*, 207, 109078.

Exploring the preasymptotic regime in synthetic rocks coated by goethite

Alexsandro dos Santos Evangelista da Cruz¹, JORGE LUIZ Gonzalez Alfonso², Moacyr Nascimento³, Ivan S. Oliveira⁴

¹Brazilian Center for Research in Physics (COMAN) , ²Universidade Federal do Espírito Santo, ³Centro de Pesquisa, Desenvolvimento e Inovação Leopoldo Américo Miguez de Mello, ⁴Brazilian Center for Research in Physics

e-mail: alex.asec@gmail.com

Nuclear magnetic resonance has been an essential tool for non-invasive investigations of complex porous media and the extraction of relevant petrophysical parameters from relaxation rates obtained in signal decay experiments such as CPMG. In the free regime, the relaxation rates contain geometric (Brownstein-Tarr)[1] and diffusion (Torrey)[2] contributions, leading to a linear dependence with squared echo time (t_E). However, for long t_E values and/or high magnetic mineral content, the diffusion contribution is no longer described by the Torrey term and the experimental data become nonlinear. In this case, the spin ensemble gradually evolves to asymptotic regimes known as motional averaging or localization. Before reaching the asymptotic regime, a preasymptotic behavior emerges, producing a nonlinear monotonic increase of the relaxation rates that remains poorly explored. In this work, the preasymptotic regime was investigated in sintered porous rocks by varying t_E (100–600 μ s) and increasing the goethite content (0–128 ppm). For short t_E , the relaxation rates exhibited a linear dependence with squared echo times at low concentrations. Increasing the goethite content progressively reduced the linear range, indicating suppression of the free regime. The nonlinear data were fitted using a recent model that replaces the Torrey diffusion term with a logarithmic dependence on echo time[3]. From this model, the critical time associated with the transition to the asymptotic regime was extracted, showing a reduction of about 67 % at the highest goethite concentration. The characteristic lengths of the asymptotic regimes were also evaluated. The results indicate that localization dominates the asymptotic regime, suggesting that spins mainly lose phase coherence due to the enhanced internal gradient field generated by the magnetic minerals, estimated as ≈ 4.0 T/m. These findings provide insights into the nonlinear behavior of relaxation rates.

Acknowledgements

This study was financed by Petrobras

References

K. R. Brownstein and C E Tarr, Physical review A , 1-2446, 1979.

H. C. Torrey. Physical review, 104,563, 1956.

J. L. Gonzalez et .al., 51,581–595, 2020.

Permeability Estimation in Heterogeneous Pre-Salt Carbonates: A Multicomponent Model Based on NMR T2 Distributions from Well Logs

Anderson Augusto da Silva Costa¹, Silvia Lorena Bejarano Bermudez², Andre Alves de Souza², Giovanni Chaves Stael²

¹Observatório Nacional (COGEO), ²Observatório Nacional (Coordenação de Geofísica)

e-mail: andersoncosta@on.br

Permeability estimation in carbonate reservoirs represents a significant challenge due to their high heterogeneity. In these systems, the complexity of the pore structure, characterized by different pore-size distributions, varying degrees of connectivity, and a strong influence of depositional and diagenetic processes, often results in a non-linear porosity-permeability relationship. In this context, this study evaluates the application of a multicomponent permeability model based on transverse relaxation time (T2) distributions obtained from nuclear magnetic resonance (NMR) well logs. The proposed approach aims to classify the pore system into distinct groups, considering the contribution of different pore populations in order to improve permeability prediction. The study area corresponds to the Atapu Field, located in the Santos Basin, Brazil, within the geological context of the Pre-Salt. Its carbonate reservoirs exhibit pronounced heterogeneity, with the occurrence of interparticle, vuggy, and moldic porosity, associated with dissolution and fracturing processes, which directly affect fluid flow. The permeability estimates obtained from the multicomponent model were compared with those derived from conventional SDR and Timur-Coates (TC) models. The results showed that the multicomponent approach provided more accurate and reliable permeability estimates, thereby improving the ability of the parameter to reflect pore connectivity and pore-size distribution with greater precision. Therefore, the proposed methodology contributes to a more detailed and accurate petrophysical characterization of Brazilian Pre-Salt carbonate reservoirs.

References

- Bermudez, S. L. B., Ribeiro, G. S. S., Lima, M. C. O., and Couto, P., 2025. Permeability estimation in carbonate rocks using multicomponent models applied to nuclear magnetic resonance data. 19th International Congress of the Brazilian Geophysical Society, Rio de Janeiro, Brazil, 1-4.
- Han, Y., Zhou, C., Fan, Y., Li, C., Yuan, C., and Cong, Y., 2018. A new permeability calculation method using nuclear magnetic resonance logging based on pore sizes: A case study of bioclastic limestone reservoirs in the A oilfield of the Mid-East. *Petroleum Exploration and Development*, 45(1), 183-192.

Spectral parameters of the T_2 distribution for heterogeneity characterization and permeability estimation in carbonates by NMR

Silvia Lorena Bejarano Bermudez¹, Anderson Augusto da Silva Costa¹, Andre Alves de Souza¹, Giovanni Chaves Stael¹

¹Observatório Nacional (*Coordenação de Geofísica*)

e-mail: silviabermudez@on.br

Estimating permeability in heterogeneous carbonates from NMR data remains challenging because the classical SDR and Timur-Coates models rely solely on T_{2LM} and FFI/BVI as proxies for pore structure, overlooking the full pore-size distribution. This work proposes the sorting of the T_2 distribution, defined as the amplitude-weighted standard deviation in $\log_{10}(T_2)$, as an auxiliary permeability predictor, combined with NMR porosity (Φ_{NMR}), in a set of 10 carbonate samples from Morro do Chaves Formation, Sergipe-Alagoas Basin. Gaussian decomposition of the T_2 curves showed that 8 samples are trimodal and 2 are bimodal, with pore populations spanning micropores ($T_2 < 30$ ms), meso/macropores, and supramacropores ($T_2 > 200$ ms). Among the heterogeneity indices computed (skewness, kurtosis, Shannon entropy, sorting, and coefficient of variation (CV)), sorting ($r = -0.74$, $p < 0.05$) and CV ($r = -0.76$, $p < 0.05$) showed the strongest correlation with $\log(k)$ and distinguished the more permeable samples more effectively than the scalar parameters T_{2LM} and FFI/BVI. The partial correlation of sorting controlling for Φ_{NMR} reached $r = -0.85$ ($p = 0.002$), confirming that the spread of the T_2 distribution carries permeability-relevant information independently of pore volume. The parsimonious model ($k = 11.08 \cdot \Phi^{2.42} \cdot 10^{-1.26\log(T_2)}$), calibrated by log-log regression and validated by leave-one-out cross-validation (LOO-CV) with 2000-resample bootstrap, achieved R^2 LOO = 0.595 and RMSE LOO = 0.223, outperforming SDR (R^2 LOO = 0.550), Han's model (0.376), and Timur-Coates (0.327). Four-parameter models (Φ + sorting + T_{2LM} or CV) degraded LOO performance, confirming that sorting complements porosity without requiring additional predictors for this dataset. Taken together, these results suggest that the shape of the T_2 distribution carries structural petrophysical information that remains underexplored in conventional NMR permeability models for carbonates.

References

Wang, W.; Cui, Y.; Algheryafi, H. 2025. Parameterization of nuclear magnetic resonance transverse relaxation time distribution. US 12,196,910 B2. Depositante: Saudi Arabian Oil Company. Depósito: 30 mar. 2022. Concessão: 14 jan. 2025.

Lu, Y., et al. 2021. Applying NMR T_2 Spectral Parameters in Pore Structure Evaluation—An Example from an Eocene Low-Permeability Sandstone Reservoir. *Applied Sciences*, 11, 8027

Han, Y., et al. 2018. A new permeability calculation method using nuclear magnetic

resonance logging based on pore sizes: A case study of bioclastic limestone reservoirs in the
A oilfield of the Mid-East. *Petro. Explor. Develop.* 45(1), 183-192

Study of NMR T2 Relaxation Time and Electrical Resistivity Correlation by Numerical Simulations in Synthetic Porous Media Under Variable Saturation and Wettability Conditions

Manoel Vicente de Souza Filho¹, Ricardo Leiderman², André Maués Brabo Pereira², Rodrigo Bagueira de V. de Azeredo³, Giovanni Chaves Stael¹, José Alejandro Moreno Alfonzo¹, Andre Alves de Souza¹

¹Observatório Nacional (*Geophysics Department*) , ²Universidade Federal Fluminense (*Institute of Computing*) , ³Universidade Federal Fluminense (*Institute of Chemistry*)

e-mail: manoelfilho@on.br

Understanding fluid type, content, and spatial distribution within porous media is essential for developing reliable wettability index indicators. A key challenge lies in linking macroscopic observations to pore-scale fluid arrangements across multiple resolution scales — a problem for which no industry-accepted methodology currently exists.

To address this, we propose a framework based on synthetic porous media models designed to represent distinct fluid configurations associated with different wettability scenarios. These configurations capture variations in fluid phases and connectivity as saturation changes. Numerical simulations are employed to investigate the associated transport phenomena: Random Walk techniques model molecular diffusion and NMR relaxation within the pore space, while Finite Element Method (FEM) simulations compute electrical conductivity and track the evolution of conductive pathways during desaturation.

Particular attention is given to the role of fluid connectivity in electrical transport behavior. As saturation decreases, changes in fluid distribution and phase connectivity directly affect conduction, revealing wettability-controlled mechanisms. By systematically varying fluid arrangements, simulations illuminate the relationship between pore-scale structure and macroscopic measurements.

Simulated responses are compared with experimental data to identify which fluid configuration best matches laboratory observations, using quantitative metrics for objective model evaluation.

The integration of digital rock physics, NMR modeling, and electrical conductivity simulations provides a comprehensive framework for analyzing multiphase saturated porous systems. Expected outcomes include improved understanding of wettability effects, enhanced interpretation of NMR and electrical measurements, and new quantitative tools for characterizing pore-scale fluid distribution.

References

Hsu, W.-F., Li, X., & Flumerfelt, R. W. (1992). Wettability of porous media by NMR relaxation methods. SPE Annual Technical Conference and Exhibition, SPE-24761-MS. <https://doi.org/10.2118/24761-MS>

Arns, C. H. et al. (2009). Pore-scale simulation of NMR response. *Journal of Petroleum Science and Engineering*, 65(3-4). <https://doi.org/10.1016/j.petrol.2009.05.008>

Bergman, D. J. et al. (2007). Random-walk technique for simulating NMR measurements and 2D NMR maps of porous media with relaxing and permeable boundaries. *Journal of Magnetic Resonance*, 187(2), 347-363. <https://doi.org/10.1016/j.jmr.2007.05.011>

Water mobility during gypsum hydration and drying: Relationships with hydration kinetics and mechanical strength assessed by low-field NMR

Monique Palavro Lunardi¹, Anilet Cabrer Pérez², PEDRO CESAR RODRIGUES ALVES ABRÃO³, Vanderley M. John⁴

¹Universidade de São Paulo (*Engenharia Civil*) , ²Universidade de São Paulo (*LME*) ,
³Universidade de São Paulo (*IFSC*) , ⁴Universidade de São Paulo (*PCC Engenharia Civil*)

e-mail: monique.lunardi@lme.pcc.usp.br

Gypsum plaster strength is strongly affected by water retained after hydration, making it important to distinguish chemical reactions from subsequent drying. This study investigated water mobility during calcium sulfate hemihydrate hydration and assessed the relationship between NMR indicators and compressive strength. Plasters with water-to-gypsum ratios of 0.50, 0.55, and 0.60 were characterized by low-field ¹H-NMR using CPMG. Transverse relaxation (T₂) distributions were monitored during the first hour, and signal intensities were evaluated up to 7 days under sealed and oven-dried conditions. Isothermal calorimetry, thermogravimetry, and compression tests complemented the analysis. During early hydration, the dominant, longer-T₂ peak decreased in intensity, while a secondary, shorter-T₂ population shifted toward longer relaxation times, suggesting changes in water mobility and the developing crystalline microstructure. The evolution of the CPMG signal was associated with cumulative heat release, linking changes in detectable water to hydration kinetics. Under sealed conditions, NMR intensity decreased initially and remained nearly stable from 1 to 7 days. In oven-dried specimens, the signal declined further, consistent with moisture removal. The NMR-derived indicator for dried specimens correlated more strongly with compressive strength ($R^2 = 0.938$) than the indicator for sealed specimens ($R^2 = 0.467$), and showed a correlation comparable to thermogravimetry ($R^2 = 0.958$). These findings indicate that low-field NMR can distinguish hydration-related water redistribution from drying effects relevant to gypsum mechanical performance.

Acknowledgements

This study was financed, in part, by the National Council for Scientific and Technological Development (CNPq), Brasil, Process Number 141075/2022-8

References

WANG, D.; SUN, Z.; LU, Z.; ZHANG, T.; YANG, J.; JI, Y. Hydration characteristics and mechanism analysis of β -calcium sulfate hemihydrate based on low-field NMR. *Journal of Building Engineering*, v. 80, artigo 108077, 2023.

MCDONALD, P. J.; KORB, J.-P.; MITCHELL, J.; MONTEILHET, L. Surface relaxation and

chemical exchange in hydrating cement pastes: A two-dimensional NMR relaxation study. *Physical Review E*, v. 72, artigo 011409, 2005.

P.J. McDonald, O. Istok, M. Janota, A.M. Gajewicz-Jaromin, D.A. Faux, Sorption, anomalous water transport and dynamic porosity in cement paste: a spatially localised ^1H NMR relaxation study and a proposed mechanism, *Cement Concr. Res.* 133 (2020), 106045

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

02

NMR Methods & Instrumentation

POSTER PRESENTATION



RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26-30, 2026

Adsorption Kinetics and isotherms by TD-NMR

Diane Damaris Dorst¹, Bruno Trebbi², Caio M. Paranhos¹, Leandro Vinícius Alves Gurgel³, Luiz Alberto Colnago⁴, Eduardo Ribeiro de Azevedo⁵, Rodrigo Henrique dos Santos Garcia²

¹Univerdade Federal de São Carlos, ²Universidade de São Paulo (IFSC), ³Universidade Federal de Ouro Preto, ⁴Embrapa (*instrumentation*), ⁵Universidade de São Paulo (*Instituto de Física de São Carlos*)

e-mail: dianedorst@gmail.com

Time-domain nuclear magnetic resonance (TD-NMR) has become an important analytical technique for the characterization of organic and inorganic materials and several industrial applications due to its rapid, non-destructive, and bench-top operation. In addition to conventional measurements of proton relaxation, TD-NMR is highly sensitive to the presence of paramagnetic ions, such as Fe³⁺, Cr³⁺, Cu²⁺, Ni²⁺, and Co²⁺, which significantly accelerate nuclear relaxation through magnetic field fluctuations generated by unpaired electrons. This behavior enables the qualitative and quantitative determination of paramagnetic ions in aqueous media, providing a fast and in situ alternative for monitoring adsorption processes. In this work, TD-NMR was employed to evaluate the removal of Cr (III) ions from aqueous solutions using amino-functionalized mesoporous silica (MCM-41-NH₂) and chemically modified sugarcane bagasse as adsorbent materials. The mesoporous silica was synthesized by the sol-gel method and functionalized through a post-grafting procedure, with successful amino group incorporation confirmed by FTIR and solid-state CP-MAS ²⁹Si NMR. Adsorption isotherms were well described by the Langmuir and Freundlich models, yielding a maximum adsorption capacity of 51 ± 3 mg.g⁻¹ for MCM-41-NH₂, while the modified sugarcane bagasse exhibited a maximum adsorption capacity of 22 ± 2 mg.g⁻¹. TD-NMR relaxation measurements showed excellent correlation between proton relaxation times and Cr (III) concentration, enabling rapid, non-destructive monitoring of adsorption with minimal sample preparation. The method requires about two minutes per analysis and demonstrates that TD-NMR is a reliable and efficient tool for evaluating adsorbents and monitoring paramagnetic contaminant removal from aqueous solutions, with potential for water treatment and environmental remediation.

Acknowledgements

This study was financed, in part, by the Brazilian agencies CAPES, process number: 88887.839183/2023-00.

References

- ABRAGAM, Anatole. The principles of nuclear magnetism. Oxford university press, 1961.
- DORST, Diane Damaris. Estudo de membranas porosas de PEI e MCM-41-NH₂ na remoção de Cr (III). 2024.
- CONGER, Robert L.; SELWOOD, P. W. Proton relaxation in paramagnetic solutions. The

Journal of Chemical Physics, v. 20, n. 3, p. 383-387, 1952.

Bicontinuous Microemulsions as Dynamic Nanostructured Media: Composition-Dependent Molecular Dynamics Probed by FFC-NMR Relaxometry

Giselle de Araujo Lima e Souza¹, Muhammad Zulqarnain Arif², Adam Imel^{3,4}, Thomas Zawodzinski², Pedro José Sebastião⁵, Steven Greenbaum⁶

¹Universidade de São Paulo (*Centro de Energia Nuclear na Agricultura*), ²University of Tennessee Knoxville (*Department of Chemical and Biomolecular Engineering*), ³University of Tennessee Knoxville, ⁴University of Tennessee-Oak Ridge Innovation Institute, ⁵Universidade de Lisboa (*CeFEMA and Department of Physics, Instituto Superior Técnico*), ⁶CUNY Hunter College (*Department of Physics and Astronomy*)

e-mail: giselle.araujolina@gmail.com

Bicontinuous microemulsions are macroscopically homogeneous and isotropic systems, yet their nanoscale organization can give rise to complex molecular dynamics [1]. In these systems, oil-rich and water-rich domains form interconnected pathways organized around a surfactant-rich interfacial region, creating a dynamic nanostructured medium in which molecular motions occurring over different length and time scales may coexist. Understanding how composition modulates these motions is essential for linking internal organization to transport and relaxation behavior in complex soft media. Here, fast field-cycling nuclear magnetic resonance (FFC-NMR) relaxometry was used to selectively probe the composition-dependent dynamics of the surfactant Tergitol 15-S-9 in bicontinuous microemulsions. Because the oil and water phases were deuterated, the measured proton relaxation dispersion predominantly reflects the motion of the surfactant within the interfacial environment. Three formulations were compared to represent distinct compositional regimes: ME1, a water-rich system; ME2, an oil-rich system; and ME3, a surfactant-rich system. The resulting proton relaxation dispersion profiles revealed marked differences among the samples, indicating that variations in oil, water, and surfactant content strongly influence surfactant mobility within the bicontinuous microstructure. Differences among the ME1, ME2, and ME3 relaxation dispersion profiles are consistent with changes in hydration, oil swelling, surfactant packing, and interfacial organization, showing that samples classified within the same broad bicontinuous region exhibit distinct dynamic signatures. These results highlight FFC-NMR relaxometry as a sensitive approach for probing surfactant dynamics in soft nanostructured media, providing insight into the coupling between internal organization and molecular motion in bicontinuous microemulsions.

Acknowledgements

This study was financed, in part, by the São Paulo Research Foundation (FAPESP), Brasil. Process Number #2025/10789-8

This study was financed, in part, by Breakthrough Electrolytes for Energy Storage (BEES), an Energy Frontier Research Center funded by the U.S. Department of Energy, Office of

Science, Basic Energy Sciences under Award #DE-SC0019409.

References

J. Phys. Chem. B 2009, 113, 31, 10669-10678

Development of a Rheo-NMR instrument to study dynamical material properties

Aristarchos Mavridis¹, Antonela Ananiadou², Rodrigo de Oliveira Silva², Christian Clasen²,
Dimitrios Sakellariou³

¹Catholic University of Leuven (*Molecular and Microbial systems*) , ²Catholic University of Leuven, ³Katholieke Universiteit Leuven (*M2S/cMACS*)

e-mail: aris.mavridis@kuleuven.be

Instrumentation combining rheological and NMR measurements was first introduced in the literature three decades ago¹. Nevertheless, adoption to this day is limited, and no commercial options exist in the market. With such techniques, the molecular properties probed by conventional NMR methods can be studied under precisely controlled deformation, while simultaneously measuring macroscopic rheological properties of materials (shear/extensional).

Materials incorporating weak bonds (either covalent or supramolecular) in their molecular structure have attracted attention due to their useful mechanical properties². Under deformations, these weak bonds would break before the stronger chemical bonds of the molecule and subsequently re-attach, returning to their equilibrium positions once the deformation ceases. Such behaviour can introduce useful features into materials, such as self-healing and improved toughness. However, these properties have so far been difficult to quantitatively assess at the molecular level in-situ during deformation.

Our project aims to develop experimental methods combining rheology and time-domain NMR to investigate polymer samples involving weak bond structures. We develop an in-house Rheo-NMR setup based on a commercial rheometer, a low-field (0.3T) pseudo-Halbach magnet³ and a radio-frequency probe, enabling such measurements on the bench top. We will present the operational principles of this device, preliminary measurements, and challenges.

Acknowledgements

This study is funded by the Excellence of Science (EOS) project, Belgium.

References

- Creton, C. 50th Anniversary Perspective: Networks and Gels: Soft but Dynamic and Tough. *Macromolecules* 2017, 50 (21), 8297–8316. <https://doi.org/10.1021/acs.macromol.7b01698>
- Callaghan, P. T. Rheo-NMR: Nuclear Magnetic Resonance and the Rheology of Complex Fluids. *Rep. Prog. Phys.* 1999, 62 (4), 599–670. <https://doi.org/10.1088/0034-4885/62/4/003>
- Tayler, M. C. D.; Sakellariou, D. Low-Cost, Pseudo-Halbach Dipole Magnets for NMR. *J. Magn. Reson.* 2017, 277, 143–148. <https://doi.org/10.1016/j.jmr.2017.03.001>

Dipolar-Filtered Magic Sandwich Echo: A Self-Normalized Approach for NMR Cryoporometry of Mesoporous Materials

Bruno Trebbi¹, Rodrigo Henrique dos Santos Garcia¹, Renato Pereira Murback Filho¹,
Marcos de Oliveira Junior¹, Eduardo Ribeiro de Azevedo¹

¹São Carlos Institute of Physics - University of São Paulo

e-mail: brunotrebbi@usp.br

NMR cryoporometry is a well-established technique for determining pore size distributions by monitoring the melting behavior of confined fluids in porous materials. Conventional methods rely on spin-echo experiments and external reference measurements to compensate for temperature-dependent signal variations. An alternative approach based on the Dipolar-Filtered Magic Sandwich Echo (DFMSE) pulse sequence is presented.

The proposed method combines acquisitions performed with short and long dipolar filter times, providing an internally normalized signal that eliminates the need for external references while compensating for Curie-law effects and instrumental variations. Furthermore, the filter-time dependence offers a simple criterion for suppressing non-cryoporometric contributions, improving the accuracy of pore size determination.

The methodology was validated using porous silica and controlled-pore glass samples saturated with water and cyclohexane. The resulting pore sizes and pore size distributions showed excellent agreement with conventional NMR cryoporometry and nitrogen adsorption measurements. The approach was also successfully applied to a cadmium imidazolate metal-organic framework, demonstrating its applicability to structurally complex porous systems.

Acknowledgements

ERdA, BT, and RHSG acknowledge financial support from the Brazilian funding agencies CAPES, Brazil (grant no. 88887.839183/2023-00) and CNPq, Brazil (grant nos. 308760/2022-0 and 130118/2023-0).

References

Trebbi, B.; Filgueiras, J. G.; Garcia, R. H. S.; Murback, R. P.; de Oliveira, M.; Ribeiro de Azevedo, E. Dipolar-Filtered Magic Sandwich Echo as an alternative method for NMR cryoporometry. *J. Magn. Reson.* 388 (2026) 108075. <https://doi.org/10.1016/j.jmr.2026.108075>

Petrov, O. V.; Furó, I. NMR cryoporometry: Principles, applications and potential. *Prog. Nucl. Magn. Reson. Spectrosc.* 2009, 54(2), 97-122. <https://doi.org/10.1016/j.pnmrs.2008.06.001>

Mitchell, J.; Webber, J. B. W.; Strange, J. H. Nuclear magnetic resonance cryoporometry. *Phys. Rep.* 2008, 461(1), 1–36. <https://doi.org/10.1016/j.physrep.2008.02.001>

Direct Determination of Pore Size Distribution from Multi-Temperature MR Relaxation Measurements

Peiyuan Yan¹, Bruce Balcom²

¹University of New Brunswick (*UNB MRI Centre*) , ²University of New Brunswick

e-mail: pyan1@unb.ca

Brownstein-Tarr (BT) theory provides a comprehensive framework for understanding magnetic resonance (MR) relaxation in porous media. In our previous work, BT theory was validated experimentally and shown to explain the temperature-dependent MR relaxation behaviors observed in a wide range of porous materials [1-3]. In this presentation, we further extend the theory by introducing direct methods for determining pore size distribution and surface relaxivity from MR relaxation measurements.

The MR T_2 distribution is widely used as a proxy for the pore size distribution. However, this relationship is generally valid only in the fast-exchange BT regime and requires independent calibration of the surface relaxivity. These requirements limit the practical application of MR pore size characterization. Our recent work overcomes these limitations by exploiting the temperature dependence of T_2 relaxation in paramagnetic sandstones, when relaxation occurs in the intermediate BT regime. The determined surface relaxivity enables quantitative conversion of T_2 distributions into pore size distributions. The BT number of 0.1, marking the boundary between the fast-exchange and intermediate BT regimes, is found to lie close to the conventional T_2 cut-off value, providing a physical explanation for this empirical criterion.

We will also present a direct inversion method for determining pore size distributions directly from multi-temperature CPMG decays. Multi-temperature measurements generate temperature-dependent relaxation kernels through the fluid diffusivity. The pore size distribution and surface relaxivity are determined simultaneously by inversion of the multi-temperature CPMG decays. The method is validated using both simulation and experimental data from glass bead packs and porous rocks. The recovered pore size distributions show excellent agreement with imaging methods, demonstrating the robustness and broad applicability of the proposed method.

References

Yan, P., Zamiri, M.S., Marica, F., Nicot, B., Green, D., and Balcom, B.J. *Physical Review Letters* (2024) 133, 266202.

Yan, P. and Balcom, B.J. *Progress in Nuclear Magnetic Resonance Spectroscopy* (2026), Under revision.

Yan, P., Zamiri, M.S., Marica, F., Nicot, B., Green, D., and Balcom, B.J. *Physical Review Applied* (2025) 20, 014011.

Effects of Temperature-Dependent Surface Relaxivity on Variable-Temperature NMR Pore Size Measurements

Emanuele Amorim Oliveira¹, Bruno Trebbi², Rodrigo Henrique dos Santos Garcia², Eduardo Ribeiro de Azevedo³

¹Instituto de Física de São Carlos - USP (IFSC) , ²Universidade de São Paulo (IFSC) ,

³Universidade de São Paulo (Instituto de Física de São Carlos)

e-mail: emanueleamorim@usp.br

In this work, we build upon the method developed by Balcom and co-workers, who proposed a direct approach for measuring pore size and surface relaxivity using variable-temperature magnetic resonance experiments [1]. Their method estimates pore size and surface relaxivity by exploiting the relationship between the transverse relaxation time (T_2) and the temperature dependence of the self-diffusion coefficient of the saturating fluid. It combines variable-temperature Carr-Purcell-Meiboom-Gill (CPMG) measurements with nonlinear fitting based on three idealized pore geometries: planar, cylindrical, and spherical. In the original approach, the temperature dependence of the water self-diffusion coefficient was taken from literature data [2], while the surface relaxivity was assumed to remain constant over the investigated temperature range. In the present work, we investigate the limits of validity of the constant surface-relaxivity assumption by comparing the original model with an alternative approach in which the surface relaxivity is allowed to vary with temperature according to functions reported in the literature [3]. Numerical calculations were performed to determine the range over which the constant-relaxivity approximation remains valid and to identify signatures that can be used to establish its limits of applicability. The proposed criteria were then used to analyze experimental data obtained from glass-bead samples with nominal pore sizes of 36 and 112 μm and from a silica gel sample with pore sizes ranging from 30 to 70 μm . In all cases, the estimated pore sizes were in good agreement with the expected values. Applications to rock core samples and porous biomasses are currently under investigation.

Acknowledgements

This study was financed by the "Conselho Nacional de Desenvolvimento Científico e Tecnológico" (CNPq). Process Number 144397/2025-0

References

[1] YAN, Peiyuan; MARICA, Florea; GUO, Jiangfeng; BALCOM, Bruce J. Direct Measurement of Pore Size and Surface Relaxivity with Magnetic Resonance at Variable Temperature. *Physical Review Applied*, v. 20, n. 1, p. 014009, 2023. DOI: 10.1103/PhysRevApplied.20.014009

[2] HOLZ, Manfred; HEIL, Stefan R.; SACCO, Antonio. Temperature-dependent self-diffusion

coefficients of water and six selected molecular liquids for calibration in accurate ^1H NMR PFG measurements. *Physical Chemistry Chemical Physics*, v. 2, p. 4740–4742, 2000. DOI: 10.1039/B005319H.

[3] GODEFROY, S.; FLEURY, M.; DEFLANDRE, F.; KORB, J.-P. Temperature effect on NMR surface relaxation. Paper presented at the SPE Annual Technical Conference and Exhibition, New Orleans, Louisiana, September 2001. DOI: 10.2118/1700-MS

Electromagnetic Design and Optimization of a Quadrature RF Probe for Single-Sided NMR at 13 MHz

Márcio Kenji Uehara¹, Agide Gimenez Marassi², Leonardo Conti³, Edson Vidoto², Leonardo Brizi⁴, Tito José Bonagamba², Daniel Papoti¹

¹Univerdade Federal de São Carlos (*Departamento de Física*) , ²São Carlos Institute of Physics - University of São Paulo, ³Università di Bologna (*Department Of Physics And Astronomy*) , ⁴Università di Bologna (*Physics and Astronomy*)

e-mail: marciouehara@estudante.ufscar.br

Single-sided nuclear magnetic resonance (NMR) enables non-invasive characterization of materials and porous media without the geometrical restrictions of conventional closed-bore magnets. Systems such as the NMR-MOUSE allow relaxation and diffusion measurements in highly inhomogeneous magnetic fields and have been applied to moisture and porous-material characterization [1]. Quadrature RF probes can further improve NMR performance by reducing the RF power required to generate a given transmit field by a factor of two and increasing receive signal-to-noise ratio (SNR) by a factor of $\sqrt{2}$ compared with linear polarization [2]. This work investigates, through electromagnetic simulations, a quadrature RF probe operating at 13 MHz for a PM10 NMR-MOUSE system. The proposed configuration combines a D-shaped coil and a planar spiral coil to generate approximately orthogonal RF magnetic-field components. Simulations were performed in COMSOL Multiphysics at 13 MHz, with the spiral coil positioned 5 mm above the D-shaped coil and both ports excited with equal amplitudes and a 90° phase difference. Matching and tuning networks were optimized for 50 Ω . The selected D-shaped coil had a 40-mm radius, two loops, and a simulated inductance of 1064.27 nH, with optimized matching and tuning capacitances of 10.7 pF and 132.0 pF, respectively. Spiral coils with radii from 15 to 36.8 mm and five or seven turns were evaluated. Quadrature performance was assessed from the circularly polarized RF field components [2], identifying six configurations with satisfactory behavior. These preliminary results demonstrate the feasibility of quadrature RF excitation in a single-sided NMR sensor and provide a promising approach to improve RF efficiency and sensitivity while reducing transmit power requirements for NMR studies of porous and heterogeneous materials.

References

- B. Blümich, J. Perlo, F. Casanova, "Mobile single-sided NMR," *Prog. Nucl. Magn. Reson. Spectrosc.*, 52, 197-269 (2008).
- J. Wang et al., "Polarization of the RF field in a human head at high field: A study with a quadrature surface coil at 7.0 T," *Magn. Reson. Med.*, 48, 362-369 (2002).

FFC-NMR STUDY OF WATER-PROTEIN DYNAMICS IN DAIRY PRODUCTS WITH AN INVERSION-DEDICATED TOOL

Anastasiia Nagmutdinova¹, Leonardo Brizi², Lucia Ferrari³, Germana Landi⁴, Fabiana Zama⁴, Roberto Anedda⁵, Villiam Bortolotti³

¹Università di Bologna (*Department of Civil, Chemical, Environmental, and Materials Engineering*) , ²Università di Bologna (*Physics and Astronomy*) , ³Università di Bologna (*Department of Civil, Chemical, Environmental, and Materials Engineering (DICAM)*) , ⁴Università di Bologna, ⁵Porto Conte Ricerche S.r.l.

e-mail: anastas.nagmutdinov2@unibo.it

Nowadays, Fast Field Cycling (FFC) NMR is gaining recognition as a powerful technique to probe the molecular dynamics (MD) of various materials, including applications in material science, biomedical, environmental sectors, and food¹.

By varying the magnetic field strength and thus the Larmor frequency, it is possible to probe MD over a wide range of timescales from fractions of nano- to micro-seconds. The acquired data are usually displayed in the form of a nuclear magnetic resonance dispersion (NMRD) profile, $R_1 = 1/T_1$ versus the Larmor frequency.

Despite FFC-NMR being a powerful technique, interpreting NMRD profiles to understand the MD that characterize them is not straightforward; complex models (conceptual models) are required to describe the various processes (interactions) that can occur in the sample. In principle, the expression for R_1 is related to the Fourier transform of the appropriate correlation function, which takes into account all the phenomena and processes that occur through characteristic parameters (correlation times).

Here we present a MATLAB-based inversion tool expressly designed for the Bryant and Korb (BK) model for hydrated proteins, which is used here specifically to study cheese². BK assumes cross-relaxation between protein and water and a power-law spectral density due to the protein fractal dynamics³. The model was fitted to the NMRD profiles through a three-stage hybrid strategy addressing the practical non-identifiability of the parameters: a coarse grid search, a zoom refinement, and a final simultaneous weighted, regularized nonlinear least-squares fit. Physically motivated bounds and frequency-dependent weighting of the more informative mid- and low-frequency points improved robustness and stability.

The proposed fitting strategy provides a robust framework for extracting physically meaningful MD parameters from FFC-NMRD profiles of a hydrated protein.

Acknowledgements

This work was supported by the NMR-IMPROV project, financed by the European Union's

References

Bortolotti, V., Brizi, L., Landi, G., Testa, C., Zama, F. (2024). Introduction to FFC NMR Theory and Models for Complex and Confined Fluids. Burlington House, Piccadilly, London, W1J 0BA.: The Royal Society of Chemistry

Nagmutdinova, A., Brizi, L., Bortolotti, V., Ferrante, G., Zama, F., Landi, G., & Anedda, R. (2025). Studying the influence of milk processing on two relaxation components of aged cheeses through benchtop FFC-NMR analysis. Food Research International, 214, 116679.

Korb, J., & Bryant, R. G. (2002). Magnetic field dependence of proton spin-lattice relaxation times. Magnetic Resonance in Medicine, 48(1), 21-26.

Improving NMR Cryoporometry with Octamethylcyclotetrasiloxane

Crina Rahause¹, Georgiy Baroncha¹, Rustem Valiullin¹

¹Universität Leipzig (*Felix-Bloch Institute*)

e-mail: crina.rahause@uni-leipzig.de

NMR cryoporometry is a powerful technique for the structural characterization of multi-scale nanoporous materials, which relies on the pore-size-dependent shift of the solid-liquid phase transition in confinement¹. Extending this technique to materials with larger pore sizes would significantly broaden its applicability. However, this requires probe liquids with suitable thermodynamic properties and an accurate interpretation of cryoporometry data that accounts for the influence of pore-network topology and relaxation effects on phase transitions.

In this work, we study octamethylcyclotetrasiloxane (OMCTS), a probe liquid which is of particular interest for probing larger pore materials², but its thermodynamic parameters reported in literature exhibit significant differences. Exploiting recent advances in the description of solid-liquid equilibria in confined systems, we develop and apply two independent approaches for determining the thermodynamic parameters of OMCTS. The first approach combines measurements of water and OMCTS in a European reference Controlled Porous Glass material. The second approach relies on OMCTS measurements performed in highly ordered nanoporous alumina membranes with two distinct pore sizes. The two methods yield highly consistent results and the proposed framework establishes a basis for advanced NMR cryoporometry that can be readily extended to other probe liquids, enabling accurate characterization of a broad range of porous materials.

Acknowledgements

The German Science Foundation (DFG) is gratefully acknowledged for the financial support (Projects No. 545661271 and No. 522797772)

References

- [1] J. H. Strange, M. Rahman, and E. G. Smith, Phys. Rev. Lett. 71, 3589 (1993)
- [2] D. Vargas-Florencia, O. V. Petrov, I. Furó, Journal of Colloid and Interface Science 2007, 305, 280

Kinetic study of rehydration of C-S-H dehydrated by means of water mobility and change in the microporos

THIAGO RICARDO SANTOS NOBRE¹, Monique Palavro Lunardi², Agide Gimenez Marassi³,
Tito José Bonagamba⁴, Antonio Carlos Vieira Coelho², Sérgio Cirelli Angulo²

¹Universidade de São Paulo (*Escola Politécnica*) , ²Universidade de São Paulo, ³Universidade de São Paulo (*Instituto de Física de São Carlos*) , ⁴Universidade de São Paulo (*São Carlos Institute of Physics*)

e-mail: thiago.nobre@lme.pcc.usp.br

Hydrated cement compounds can be recycled through thermal treatment. There are important gaps in the understanding of the dehydration and rehydration behavior of hydrated Portland cement, which can be addressed by studying the fundamental behavior of the constituent cement phases. Since calcium silicate hydrates (C-S-H) are the phases present in the largest volume (~50–60% of the hydrated products), studying this phase is crucial to understanding and predicting the behavior of recycled cements. The aim of this study was to verify whether it is possible to dehydrate and rehydrate synthetic calcium silicate hydrates (pure phases, obtained by mechanochemical synthesis with Ca/Si molar ratios 0.83, investigating whether the structures of these C-S-H phases remain stable throughout dehydration-rehydration cycle (dehydration at 400 °C for 2 h and rehydration in ultrapure water). The results obtained by the different experimental techniques used (XRD, ATR FT-IR, thermogravimetry) showed that it is possible to dehydrate and rehydrate C-S-H phases produced. Kinetic studies showed that the rehydration phenomenon takes place through direct reformation of the dehydrated C-S-H structure itself, and FT-IR tests evidenced that when rehydrated the C-S-H layers expand as water is imbibed. ¹H-NMR shows an instantaneous redistribution of water from coarser pores back into the finer C-S-H spaces to equilibrate internal surface energy gradients because the water controls multiple chemical and mechanical properties of C-S-H.

Acknowledgements

This study was supported by FAPESP (process 2026/15606-1) and CAPES (finance code 001).

References

BALDUSCO, R., NOBRE, T.R.S., ANGULO, S.C., QUARCIONI, V.A., CINCOTTO, M.A. Dehydration and Rehydration of Blast Furnace Slag Cement. *J. Mater. Civ. Eng.* 31, 04019132, 2019. DOI: [https://doi.org/10.1061/\(ASCE\)MT.1943-5533.0002725](https://doi.org/10.1061/(ASCE)MT.1943-5533.0002725)

MCDONALD, P.J., KORB, J.-P., MITCHELL, J., MONTEILHET, L. Surface relaxation and chemical exchange in hydrating cement pastes: A two-dimensional NMR relaxation study.

Phys. Rev. E 72, 011409, 2005. DOI: <https://doi.org/10.1103/PhysRevE.72.011409>

POP, A.; BADEA, C.; ARDELEAN, I. The Effects of Different Superplasticizers and Water-to-Cement Ratios on the Hydration of Gray Cement Using T2-NMR. Appl Magn Reson 44, 1223-1234, 2013. DOI: <https://doi.org/10.1007/s00723-013-0475-5>

Magnetic Resonance Pore Imaging using Simple Echo Pulse Sequences

Humna Asad¹, Petrik Galvosas¹, Philipp Matern², Daniel Holand³, Tristan A. Kuder⁴

¹Victoria University of Wellington (*School of Chemical and Physical Sciences*) , ²Heidelberg University, ³University of Canterbury (*Chemical and Process Engineering*) , ⁴DKFZ Name: German Cancer Research Center

e-mail: humna.asad@vuw.ac.nz

Pulsed Gradient Spin Echo methods, as introduced first by Stejskal and Tanner [1], have constantly evolved over time, becoming more versatile and sophisticated. Examples include structural investigations in porous materials, soft matter research, and biomedical applications. More recently, Diffusive Pore Imaging [2], also known as Magnetic Resonance Pore Imaging (MRPI) [3], uses extended gradients to accumulate the phase of the NMR signal as an average over a long diffusion path, thus tracing out pore structures. Achieving the long-time limit for these extended gradients is crucial; otherwise artefacts such as blurring may occur.

Practical implementations of MRPI are challenging because the magnetisation needs to be maintained in the transverse plane for extended periods of time. This is particularly relevant for samples that induce internal gradients due to their heterogeneous internal pore structure. This has previously been mitigated using MRPI pulse sequences similar to CPMG. While this preserves magnetisation, it also introduces complex coherence pathways and requires frequent and rapid gradient switching. Other approaches have used conventional spin-echo sequences, owing to favourable sample structure and alignment in the B₀ magnetic field.

Here, we report the use of conventional spin-echo sequences applied to diffusion in glass capillaries with diameters of 20 μm . Even at echo times on the order of seconds, we observed decent signal-to-noise ratios. Depending on the specific properties of the sample being examined, this experimental simplification could expand the applicability of sequences that rely on long diffusion times to media containing closed pores.

Acknowledgements

This work was supported by a Ministry of Business, Innovation and Employment, New Zealand Endeavour Programme Grant [UOCX1903].

References

Stejskal, E. O. and Tanner, J. E., J. Chem. Phys. 42, 288 (1965).

Laun, F. B. et al., Phys. Rev. Lett. 107, 048102 (2011).

Hertel, S. A. et al., Phys. Rev. E 92, 012808 (2015).

Monitoring Water Populations During White Cement Hydration Using NMR Relaxometry and Dipolar NMR

Bruno Trebbi¹, Luis Augusto Pereira¹, Gustavo Henrique Freitas de Souza², Agide Gimenez Marassi³, PEDRO CESAR RODRIGUES ALVES ABRÃO^{1,4}, Vanderley M. John⁵, Eduardo Ribeiro de Azevedo³, Tito José Bonagamba^{6,2}

¹Universidade de São Paulo (IFSC) , ²Instituto de Física de São Carlos - USP, ³Universidade de São Paulo (Instituto de Física de São Carlos) , ⁴Escola Politécnica de Universidade de São Paulo, ⁵Universidade de São Paulo (CICS) , ⁶Universidade de São Paulo (São Carlos Institute of Physics)

e-mail: brunotrebbi@usp.br

Water in cementitious materials plays a fundamental role in the hydration process, the evolution of the microstructure, and the resulting mechanical and transport properties. In particular, water associated with the so-called gel pores, consisting of nanometer-sized spaces between calcium silicate hydrate (C-S-H) nanoparticles, as well as water confined within the interlayer spaces of C-S-H, is severely confined and exhibits molecular dynamics that differ markedly from those of bulk water [1].

Nuclear Magnetic Resonance (NMR) relaxometry is widely employed to investigate the different water populations present in cementitious materials [1,2]. However, the severe restriction of molecular motion experienced by highly confined water makes dipolar NMR techniques particularly well suited to probing these populations. In this context, the present work is motivated by the possibility of combining conventional relaxometry with dipolar NMR methods [3] to simultaneously monitor water populations spanning a broad range of molecular mobilities and degrees of confinement during cement hydration. The experiments are performed on white cement, which serves as a model system because of its low concentration of paramagnetic impurities.

Direct excitation and Magic Sandwich Echo (MSE) experiments [3] are employed to identify and quantify ¹H populations associated with strongly confined, low-mobility water species. In parallel, conventional T₁ and T₂ relaxometry is used to monitor the evolution of the more mobile water populations [1,2]. The combination of these complementary approaches enables the simultaneous monitoring of structural water, interlayer water, gel water, and bulk (capillary) water throughout cement hydration, allowing the identification of distinct hydration stages, including the initial and final setting times, as well as the onset of the hardening process.

Acknowledgements

ERdA, BT, and RHSG acknowledge financial support from the Brazilian funding agencies CAPES, Brazil (grant no. [88887.839183/2023-00](#)) and CNPq, Brazil (grant nos. [308760/2022-0](#) and [130118/2023-0](#))

References

] A. Valori, P. J. McDonald e K. L. Scrivener. "The Morphology of C-S-H: Lessons from ^1H Nuclear Magnetic Resonance Relaxometry". *Cement and Concrete Research* 49 (2013), pp. 65-81.

P. J. McDonald et al. " ^1H NMR Relaxation Analysis of Cement-Based Materials: The Spin-Lock $T_{1\rho}$ Experiment and the Partitioning of Water in C-S-H Inter-Layer Spaces". *Cement and Concrete Research* 201 (2026), p. 108125

Fechete, R.; Demco, D. E.; Blümich, B. Chain Orientation and Slow Dynamics in Elastomers by Mixed Magic-Hahn Echo Decays. *J. Chem. Phys.* 2003, 118(5), 2411-2418.

NMR and High-Resolution imaging on the MOGNO Beamline for dynamic system analysis on Porous Media

Maria de Fatima Costa Santos¹, Everton Lucas-Oliveira², Antonio Barbosa de Lima Neto³,
Giancarlo Tosin⁴, João Silva⁴, Edson Vidoto^{1,5}, Nathaly Lopes Archilha³, Tito José
Bonagamba^{6,1}

¹São Carlos Institute of Physics - University of São Paulo, ²Brazilian Center for Research in Energy and Materials (*Brazilian Synchrotron Light Laboratory (LNLS)*), ³Brazilian Center for Research in Energy and Materials, ⁴FIT Instrument, ⁵Universidade de São Paulo, ⁶Universidade de São Paulo (*São Carlos Institute of Physics*)

e-mail: maria.ssantos@lnls.br

Time-Domain Nuclear Magnetic Resonance (TD-NMR) stands out for being a non-invasive technique, that allows the measurement of information regarding the molecular dynamics of fluids. In porous media, this technique enables the study of morphological and physicochemical properties of materials, and it is widely applied across scientific and industrial sectors, with current emphasis on CO₂ geological storage [1]. MOGNO is a micro and nano X-ray imaging beamline dedicated to time-resolved experiments (4D tomography) through in-situ experiments, where a material can be observed under specific conditions [2]. Integrating TD-NMR and X-ray imaging is a perfect combination for studies of porous media, mainly under dynamic conditions [3]. It is in this context that the LEAR group at the University of São Paulo, in partnership with the Brazilian Center for Research in Energy and Materials (CNPEM), is developing an TD-NMR system to be installed at MOGNO for simultaneous acquisitions of high-resolution images and NMR data. Data from both techniques will be crucial for understanding the material's evolution and will also complement computational data processing models. Areas involving processes like saturation, imbibition, and flow, including CO₂ capture and storage, soil, cement, and aquifers, can be explored. In addition to areas involving chemical reactions such as porous media acidification. This work will present some aspects of the project that are under development and previously obtained results that will be explored in the future with the combination of both techniques.

Acknowledgements

The authors would like to thank the financial and institutional support provided by CNPEM, USP, CNPq, FAPESP, CAPES, and Petrobras.

References

Song, Y.-Q. (2013). Magnetic Resonance of Porous Media (MRPM): A perspective. *Journal of Magnetic Resonance*, 229, 12-24. <https://doi.org/10.1016/j.jmr.2012.11.010>

Archilha, N. L., Costa, G. R., Ferreira, G. R. B., Moreno, G. B. Z. L., Rocha, A. S., Meyer, B. C., Pinto, A. C., Miqueles, E. X. S., Cardoso, M. B., & Westfahl Jr, H. (2022). MOGNO, the nano and microtomography beamline at Sirius, the Brazilian synchrotron light source.

Journal of Physics: Conference Series, 2380(1), 012123.
<https://doi.org/10.1088/1742-6596/2380/1/012123>

Lucas-Oliveira, E., Araujo-Ferreira, A. G., Trevizan, W. A., Fortulan, C. A., & Bonagamba, T. J. (2018). Computational approach to integrate 3D X-ray microtomography and NMR data. *Journal of Magnetic Resonance*, 292, 16-24. <https://doi.org/10.1016/j.jmr.2018.05.001>

Open-Access Web Application for Inverse Laplace Transform Processing of Time Domain NMR Signals

Tiago Bueno de Moraes¹, Gustavo Voltani Von Atzingen², Marcelo Camponez do Brasil Cardinali²

¹Universidade de São Paulo (*Biosystem Engineering / ESALQ*) , ²Instituto Federal de Educação, Ciência e Tecnologia de São Paulo

e-mail: tiago.moraes@usp.br

Recent advances in compact and low-field time-domain nuclear magnetic resonance (TD-NMR) instruments have considerably expanded their application in food, agricultural, environmental, and materials research. In parallel, the Inverse Laplace Transform (ILT) has become one of the main approaches for extracting relaxation time distributions from TD-NMR signals, providing valuable information about molecular mobility and material structure. However, ILT analysis is still commonly limited to proprietary software or requires specialized knowledge in numerical methods, restricting its widespread adoption by non-specialist users. In this work, we present NMR-ILT, an open-access Web platform for performing ILT analysis of TD-NMR relaxation data through an intuitive and user-friendly interface. The implemented algorithm is based on non-negative least squares (NNLS) combined with Tikhonov regularization and singular value decomposition (SVD), providing robust inversion of ill-posed problems. The platform supports the most widely used TD-NMR pulse sequences, including Carr-Purcell-Meiboom-Gill (CPMG), Inversion Recovery (IR), and Saturation Recovery (SR), and is compatible with data acquired from instruments manufactured by different vendors. The performance of the WebApp was evaluated using simulated datasets and representative experimental signals from food and agricultural materials. The obtained relaxation time distributions showed excellent agreement with those generated by established ILT software while providing a freely accessible, browser-based environment that requires no software installation. By making advanced TD-NMR signal processing openly available, the proposed platform has the potential to facilitate research, teaching, and the dissemination of relaxometry methods across a broad scientific community.

Acknowledgements

This research was funded by Fundação de Amparo à Pesquisa do Estado de São Paulo (FAPESP) grant number 2025/09284-9 and Conselho Nacional de Desenvolvimento Científico e Tecnológico (CNPq) grants 306611/2022-8 and 302714/2026-0.

References

Fordham, E., Venkataramanan, L., Mitchell, J., and Valori, A.: What are, and what are not, Inverse Laplace Transforms, *The Open-Access Journal for the Basic Principles of Diffusion Theory, Experiment and Application*, 29, 1-8, 2017

Istratov, A. A. and Vyvenko, O. F.: Exponential analysis in physical phenomena, *Review of*

Scientific Instruments, 70, 1233-1257, 1999. <https://doi.org/10.1063/1.1149581>

Moraes, T.B.; et al.; An open-access WebApp for inverse Laplace transform analysis of time-domain nuclear magnetic resonance signals. *Magnetic Resonance*, v. 7, p. 39-51, 2026. <https://doi.org/10.5194/mr-7-39-2026>

Quantifying Inter-pore Exchange in Complex Porous Media: A T_2 -Filtered NMR Study from Reservoir Rocks to Bioactive Glasses

Nataly Melo Campos¹, Everton Lucas-Oliveira², Henrik Bradtmüller¹, Tito José Bonagamba¹

¹Universidade de São Paulo (*São Carlos Institute of Physics*) , ²Brazilian Center for Research in Energy and Materials (*Brazilian Synchrotron Light Laboratory (LNLS)*)

e-mail: natalymelo@usp.br

Multi-compartment systems are ubiquitous in natural and engineered porous materials, where fluids or ions are distributed among environments with distinct physical, chemical, and geometrical properties. In complex media, ranging from sedimentary rocks with liquid inclusions (e.g., carbonate reservoirs) to mesoporous bioactive glasses, this heterogeneity gives rise to multiple compartments and fluid-surface interactions, which are reflected in broad Nuclear Magnetic Resonance (NMR) relaxation time distributions. However NMR relaxometry does not, by itself, reveal whether these compartments are dynamically connected. In this work, the T_2 -filtered T_2 - T_2 relaxation exchange method (T_2F - T_2 - T_2RE) [1,2] is employed to investigate and quantify the migration dynamics (exchange) of fluid molecules between distinct T_2 environments. This protocol uses a fixed transverse relaxation filter to suppress fast-relaxing components, allowing for a time-efficient tracking of how magnetization is recovered through exchange as a function of storage time. The results demonstrate that T_2F - T_2 - T_2RE is able to identify and quantify the exchange rates among pore families, providing a low-field NMR protocol for testing the connectivity of the pore network. In sedimentary rocks, the extracted exchange rates were correlated with macroscopic transport properties, specifically permeability, proving the method's predictive potential. This approach shows significant potential for the characterization of mesoporous bioactive glasses, [3] where understanding the exchange between intra-particle mesopores and the surrounding medium is key to optimizing ion release and drug delivery kinetics. This work highlights the technique's versatility across physics, geosciences, and the frontiers of materials science.

Acknowledgements

This study was financed by the Fundação de Amparo à Pesquisa do Estado de São Paulo-Brasil (FAPESP)- Grant 2026/04225-7 and 2023/18439-0.

References

- [1] D'EURYDICE, M. N. et al. T_2 -filtered T_2 - T_2 exchange NMR. *The Journal of Chemical Physics*, v. 144, n. 20, p. 204201, 05 2016. ISSN 0021-9606. Available at: <https://doi.org/10.1063/1.4951712>.
- [2] LEE, J. H. et al. Two-dimensional inverse laplace transform NMR: altered relaxation times allow detection of exchange correlation. *Journal of the American Chemical Society*, v.

115, n. 17, p. 7761-7764, 1993.

[3] P.N. Gunawidjaja, A.Y.H. Lo, I. Izquierdo-Barba, A. García, D. Arcos, B. Stevansson, J. Grins, M. Vallet-Regí, M. Edén, Biomimetic Apatite Mineralization Mechanisms of Mesoporous Bioactive Glasses as Probed by Multinuclear ^{31}P , ^{29}Si , ^{23}Na and ^{13}C SolidState NMR, J. Phys. Chem. C 114(45) (2010) 19345-19356.

Study of Local Environments in Crystalline and Glassy Framework Materials by Solid-State NMR

Renato Pereira Murback Filho¹, Flaviana Campos Pamplona Ribeiro², Ricardo José da Silva Afonso², Marcos de Oliveira Junior³

¹Instituto de Física de São Carlos - USP (IFSC), ²Instituto de Física de São Carlos - USP,

³Instituto de Física de São Carlos - USP (*Departamento de Física e Ciências Interdisciplinares*)

e-mail: renato.pe.murback@usp.br

High-resolution magic-angle spinning (MAS) NMR has become a key technique for investigating porous framework materials, providing atomic-scale information on local structure that complements diffraction by remaining sensitive to short-range order even in highly disordered systems [1]. This capability is particularly important for metal-organic frameworks (MOFs), where amorphization and compositional modifications often preserve local chemical connectivity while disrupting long-range crystallinity.

This contribution presents recent advances in the application of multinuclear MAS NMR to elucidate local structure in crystalline and glassy MOFs. By combining information from spin-1/2 and quadrupolar nuclei, solid-state NMR probes metal coordination, linker environments, chemical connectivity, and structural disorder. In mixed-linker cadmium imidazolate frameworks, ¹H, ¹³C, ¹⁵N, and ¹¹³Cd NMR demonstrate that vitrification preserves the primary Cd-N coordination network despite the development of local geometric disorder. Complementary ¹¹³Cd{¹H} REDOR and variable-temperature NMR experiments further distinguish distortions in coordination geometry from changes in chemical connectivity and reveal dynamic processes across the glass transition.

The versatility of this approach is further demonstrated in mixed-metal Zn/Ga ZIF materials. Multinuclear MAS NMR reveals the coexistence of two structural domains after vitrification: a Zn-rich glassy phase and residual Ga-rich crystalline environments. These results show that the local structure and phase evolution can be controlled through metal composition, providing a chemical route to MOF glass-ceramics.

Together, these examples highlight the unique capability of high-resolution MAS NMR to characterize local structure, structural heterogeneity, and glass formation in porous framework materials, providing insights that are inaccessible by diffraction alone.

Acknowledgements

This study was financed, in part, by the São Paulo Research Foundation (FAPESP), Brasil. Process Number 2026/11291-6, 2022/02974-1 and by the National Council for Scientific and Technological Development (CNPq), Grant No. 312802/2023-4.

References

(1)Serra, A. R. B.; Casagrande, T. R.; de Lima, J. F.; de Oliveira, M. F.; Júnior, S. A.; de

Oliveira Junior, M.; Serra, O. A. Synthesis and Structural Characterization of an Amorphous and Photoluminescent Mixed Eu/Zr Coordination Compound, a Potential Marker for Gunshot Residues. *Sci* 2022, 4 (4), 43.

Understanding the role of cellulose ether in water retention and hydration process of cementitious tile adhesive using NMR analysis

Luis Augusto Pereira¹, Agide Gimenez Marassi², Gustavo Mattos Fortes³, Caroline Cassia Alves³, Caio Cesar Dente Exposito³, Aparecido Donizeti Fernandes de Amorim⁴, Tito José Bonagamba⁵

¹Universidade de São Paulo (IFSC), ²Universidade de São Paulo (Instituto de Física de São Carlos), ³Saint-Gobain, ⁴Universidade de São Paulo, ⁵Universidade de São Paulo (São Carlos Institute of Physics)

e-mail: lap_scp@usp.br

Cement-based materials, including Cementitious Tile Adhesive (CTA), are widely utilized for their exceptional binding properties. While the fundamental mechanisms governing their performance are not yet fully understood, workability is known to be primarily controlled by two competing processes: hydration and water evaporation. [1] Studies have demonstrated that cellulose ethers can modulate these processes by reducing evaporation rates and modifying hydration kinetics. [2,3]

This study evaluates the effects of different cellulose ethers and chemical accelerators on two industrial-grade CTA formulations (AC-I and AC-III, respectively, according to ABNT NBR 14081), provided by Saint-Gobain Research Brazil. In the first group (AC-I), hydroxypropyl methylcellulose (HPMC) and hydroxyethyl methylcellulose (HEMC) were tested at concentrations of 0.1, 0.2, and 0.7 wt%. In the second group (AC-III), two types of accelerators were assessed. Water dynamics in the hydration process were monitored using low-field NMR relaxometry (T2 measurements) and one-dimensional MRI (1D MRI).

For AC-I, 1D MRI revealed that increasing cellulose ether creates a drying layer, which is suggested to form an evaporation-reducing barrier. ¹H relaxation measurements showed no significant difference between 0.1% and 0.2% concentrations, indicating that evaporation effects in the experimental setup were insufficient to differentiate cellulose retention at low concentrations, although the samples with 0.7% concentration showed a strong chemical reaction retardation and water retention.

In the case of AC-III, ¹H 1D-MRI revealed a pronounced difference in the effect of the accelerator during the initial hours of sample curing, enabling the observation of a faster hydration kinetics. ¹H relaxation measurements also showed great potential to differentiate the chemical additive effects in hydration kinetics.

References

Taylor, Harry FW. Cement chemistry. Vol. 2. London: Thomas Telford, 1997.

Faiyas, A. P. A., Erich, S. J. F., Huinink, H. P., Adan, O. C. G., & Nijland, T. G. (2016). Effect

of MHEC on evaporation and hydration characteristics of glue mortar. *Cement and Concrete Research*, 83, 97-103.

Faiyas, A. P. A., Erich, S. J. F., Huinink, H. P., & Adan, O. C. G. (2019). Understanding the water absorption from MHEC modified glue mortar into porous tile: Influence of pre-drying. *Construction and Building Materials*, 217, 363-371.

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

03

Human Health, Environmental Science, Food, and Biomaterials

POSTER PRESENTATIONS

**RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026**

Solid-state NMR study of species confined into the nanopores of porous carbon materials

Paulo Cesar de Mello Correa¹, Daniel Fernandes Cipriano¹, Miguel Ângelo Schettino Jr.¹, Jair C. C. Freitas¹

¹Universidade Federal do Espírito Santo (*Department of Physics*)

e-mail: paulo.correa@edu.ufes.br

Porous carbons are widely employed in a broad range of applications, including pollutant removal from aqueous and gaseous media, energy storage devices, heterogeneous catalysis, and CO₂ capture by physical adsorption. Solid-state nuclear magnetic resonance (NMR) spectroscopy is a promising technique for studying molecules and ions confined within the porous network of carbon materials. The main phenomenon observed in the NMR spectrum of a porous material impregnated with a solution is the nucleus-independent chemical shift (NICS). The magnitude of the NICS measured in an NMR spectrum can provide structural information about the porous material under investigation, such as pore size, specific surface area (SSA) and pore volume, among others [1,2]. However, the observation of NICS in an NMR spectrum and its interpretation may be affected by different structural and chemical factors specific to each material studied. Activated carbons (ACs) are porous carbon materials with high SSA and that can be obtained from the pyrolysis and activation of a wide variety of precursors [3]. In this work, ACs produced from the babassu coconut endocarp were impregnated with distilled water and aqueous solutions of NaF, NaBF₄, and LiCl for solid-state NMR experiments with magic angle spinning (MAS). The objective was to record ¹H, ⁷Li and ¹⁹F NMR spectra and assess the NICS magnitude for the different probe nuclei confined within the porous network. This work seeks to obtain relevant information for understanding the chemical and dynamic aspects of confined species in porous media. The results show that ions of different types exhibit distinct accessibility to the AC porous network, mostly depending on the porosity of the carbon matrix and the ion sizes. In contrast, water molecules readily penetrate the pores of all studied ACs, giving rise to NICS values primarily affected by the pore sizes.

Acknowledgements

This work was supported by CAPES (Finance Code 001), FAPES (grants 892/2023 and 348/2026) and CNPq (grant 310528/2022-4).

References

- 1) Xing Y.-Z. et al. Probing carbon micropore size distribution by nucleus independent chemical shift. *Carbon*, Elsevier, v. 77, p. 1132-1139, 2014. <https://doi.org/10.1016/j.carbon.2014.06.031>
- 2) Cervini L. et al. Factors affecting the nucleus-independent chemical shift in NMR studies of microporous carbon electrode materials. *Energy Storage Materials*, 21, 335, 2019. <https://doi.org/10.1016/j.ensm.2019.05.010>

3) Brito, G. M. et al. One-step methodology for preparing physically activated biocarbons from agricultural biomass waste. J. Environ. Chem. Eng. 7, 103113, 2019. <https://doi.org/10.1016/j.jece.2019.103113>

Study on Human Bone Samples Using Acoustography

Frederico Possato Tagliaferro¹, João Henrique Uliana¹, Reinaldo Cesar², Antônio Adilton Oliveira Carneiro¹

¹Universidade de São Paulo, ²Universidade Estadual de Campinas

e-mail: frederico.possato@usp.br

The development of non-destructive methods for bone characterization has become increasingly important for the diagnosis and monitoring of skeletal diseases. Acoustography, based on the detection of vibroacoustic signals generated by ultrasound radiation, has emerged as a promising technique for assessing the mechanical properties of biological tissues. This study aimed to evaluate the feasibility of Pulse Emission Acoustography (APE) for the characterization of human trabecular bone samples and to investigate its correlation with structural parameters previously obtained by micro-computed tomography (micro-CT). Human trabecular bone specimens previously classified as control, osteopenic, and osteoporotic were analyzed using a dedicated acoustography system. A focused 3-MHz confocal ultrasound transducer generated acoustic radiation force, while the resulting vibroacoustic response was detected using a broadband hydrophone. The specimens were scanned using a high-precision three-dimensional positioning system, and the acquired signals were processed to generate acoustographic images. Signal-to-noise ratio (SNR) measurements were obtained from selected regions of interest and compared with previously measured Bone Quality Index (BQI) and structural parameters. Acoustographic imaging successfully differentiated bone specimens presenting distinct structural characteristics. Samples with higher trabecular degradation exhibited lower vibroacoustic signal intensity, indicating reduced mechanical response to the applied radiation force. Quantitative analysis demonstrated a correlation between the acoustographic signal and bone quality parameters obtained by micro-CT. The results indicate that vibroacoustic signal intensity reflects changes in bone microarchitecture and mechanical properties, supporting the potential application of acoustography as a complementary tool for bone quality assessment and osteoporosis research.

Acknowledgements

Fapesp (2018/16939-8; 2023/09165-4)

References

Fatemi M. and Greenleaf J. F. "Ultrasound stimulated vibro-acoustic spectroscopy", Science, vol. 280, p. 82-85, April 1998.

ULIANA, JOÃO H. ; BRAZ, GUILHERME A. ; OLIVEIRA, ÉVERTON L. ; ARAÚJO-FERREIRA, ARTHUR G. ; MORAIS, MATEUS M. ; TREVIZAN, WILLIAN A. ; FORTULAN, CARLOS A. ; BONAGAMBA, TITO J. ; PAVAN, THEO Z. ; CARNEIRO, ANTONIO A. O. . Investigation of rock porosity using vibroacoustography. Journal of the Brazilian Society of Mechanical Sciences and Engineering, v. 46, p. 1, 2024.

14. BRAZ, GUILHERME ; AGNOLLITTO, PAULO M. ; Pavan, T Z ; BARBOSA, M. N. ; CARNEIRO, AAO ; CARNEIRO, A. A. O. . Tissue Characterization by Low-Frequency Acoustic Waves Generated by a Single High-Frequency Focused Ultrasound Beam. ULTRASOUND IN MEDICINE AND BIOLOGY, v. 47, p. 334-344, 2021

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

04

Natural and Artificial Porous Media & Cultural Heritage

POSTER PRESENTATIONS

**RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26-30, 2026**

Darcian and non-Darcian gas permeametry as a transport-based probe of carbonation in cement-based porous media

Murilo Daniel de Mello Innocentini¹

¹Universidade de Ribeirão Preto (*Chemical Engineering*)

e-mail: minnocentini@unaerp.br

Carbonation reshapes the pore network of cement-based materials: CaCO₃ precipitation fills capillary pores, while decalcification of C-S-H and shrinkage may open new pathways. Since these opposite effects may compensate in total porosity, techniques sensitive to pore connectivity and to the effective flow path are required. This contribution presents permeametry as a transport-based complement to NMR studies of carbonated porous media. Fluid flow is described by the Forchheimer equation, $\Delta P/L = (\mu/k_1)v_s + (\rho/k_2)v_s^2$, whose coefficients k_1 (Darcian, m²) and k_2 (non-Darcian, m) are intrinsic to the porous structure and independent of the permeating fluid. Three experimental configurations are discussed: steady-state air and water permeametry, hot-gas permeametry, and pressure- or vacuum-decay, the latter allowing non-destructive testing of large or finished components in about 50 s per point. Results are presented for Class G well-cement formulations before and after accelerated carbonation, and for corrugated fiber-cement sheets exposed to atmospheric CO₂ and liquid water, with k_1 values spanning 10⁻¹⁹ to 10⁻¹⁵ m². Data are interpreted through the permeability map (k_2 versus k_1 , built from more than 1000 literature values covering 10⁻²¹ to 10⁻⁵ m²), which locates carbonated cementitious materials among rocks, concretes and ceramic membranes, and reveals deviations from the general k_2 - k_1 trend associated with changes in tortuosity and pore-throat constriction rather than in total pore volume. Spatially resolved pressure-decay mapping further shows that carbonation and water ingress are strongly heterogeneous within a single component. Combining permeametry with NMR relaxometry and diffusometry offers a route to separate the connected, flow-carrying fraction of the pore network from the total pore volume, linking carbonation-induced microstructural changes to the transport properties that govern CO₂ and water ingress, service life and well integrity in CO₂ storage.

References

Innocentini MDM, Araújo Neto O, Crespi MR (2022) Rapid non-destructive evaluation of the air and water permeability of commercial corrugated fibercement roofing sheets. *Construction and Building Materials* 322:126457. <https://doi.org/10.1016/j.conbuildmat.2022.126457>

Fabrication of Artificial Carbonate Porous Media: A Comparison between Powder Compaction and Additive Manufacturing

Mateus Mota Morais¹, Tito José Bonagamba², Paolo Colombo³, Carlos Alberto Fortulan¹

¹Universidade de São Paulo (*São Carlos School of Engineering*) , ²Universidade de São Paulo (*São Carlos Institute of Physics*) , ³Università degli Studi di Padova

e-mail: mateus.morais@usp.br

Petroleum engineering utilizes natural rock samples (core plugs) to calibrate characterization tools, such as Nuclear Magnetic Resonance (NMR), and to validate numerical models. However, natural carbonate core plugs are extremely heterogeneous, expensive, and often subject to legal restrictions on their use. There is a significant gap in the production of artificial porous media composed solely of calcium carbonate, as most current replicas rely on polymeric binders or cements that alter the wettability and chemical reactivity of the matrix. This study presents two strategies to obtain pure calcite artificial porous media. The first strategy is isostatic powder compaction using pore-forming agents. This method produces samples with high relative density (up to 93%) and high mechanical strength (up to 110 MPa in compression), which is comparable to natural rocks and sufficient for petrophysical tests under high pressures. Its main disadvantage is geometric limitation to simpler shapes and low permeability (0.05-0.06 mD) due to small, poorly connected pore throats. The second strategy is additive manufacturing (vat-photopolymerization) of calcite with pore formers. The advantage lies in its exceptional geometric freedom, allowing the creation of macroscopic channels and complex structures with fully connected porosity and permeability (30-50 mD). However, the method yields significantly lower mechanical strength and imposes wall-thickness limitations due to the manufacturing process involved. Both methods provide controlled, reproducible porous media for advanced NMR studies. The presentation will compare the two methods, identify which applications are better suited to each, and outline the challenges and opportunities for improvement.

Acknowledgements

This study was financed, in part, by the São Paulo Research Foundation (FAPESP), Brasil. Grants 2020/16012-1 and 2021/12556-0

References

Morais MM. Fabrication of sintered calcium carbonate parts with multiscale porosity: producing artificial rocks for petrophysical studies and other applications. 2024. Thesis (Doctor in Science) - Department of Industrial Engineering, University of Padova / São Carlos School of Engineering, University of São Paulo, São Carlos, 2024.

Morais MM, et al. Fabrication and petrophysical characterization of artificial carbonate

rocks with multiscale porosity sintered in a CO₂ atmosphere. *Geoenergy Science and Engineering*. 2023;229:212096. <https://doi.org/10.1016/j.geoen.2023.212096> .

Factors Influencing Pore Structure Changes in Purple-clay (Zisha) Ceramics: A Comparative Study Using ^1H NMR Relaxometry and Mercury Intrusion Porosimetry

Guojun Xu¹, Yuting Liu¹, Guantao Huang², Wanru Shu³, Leonardo Conti⁴, Feng Yuan²,
Leonardo Brizi⁵

¹Università di Bologna (DIFA), ²Jingdezhen Ceramic University (School of Archaeology and Cultural Heritage), ³Università di Bologna (SCORE), ⁴Università di Bologna (Department Of Physics And Astronomy), ⁵Università di Bologna (Physics and Astronomy)

e-mail: guojun.xu2@unibo.it

Single-sided nuclear magnetic resonance (NMR) offers a non-destructive approach for characterizing the pore size distribution in porous ceramic materials¹. In this study, we applied single-sided NMR to investigate the pore structure of Purple-clay (Zisha), a mineral-based ceramic clay traditionally used for the production of teapots and provide relatively sweeter tea soup². This special effect is thought to be possibly related to the pore structure inside Purple-clay³, but so far it has not been fully investigated. We studied Huanglongshan-Dicaoqing Purple-clay from Dingshu Town, Jiangsu Province, and compared it with a commonly used soil-based clay from Meishan Town, Zhejiang Province. We also evaluated the influence of traditional clay preparation versus modern machinery-based preparation.

The pore size distribution was investigated using 1D and 2D NMR time-domain measurements performed with a MOUSE PM10 device (Magritek, New Zealand; $B_0 = 0.327$ T). Complementary mercury intrusion porosimetry measurements were performed using ThermoQuest instruments from the PASCAL 140 and 240 series to support the interpretation of the porous structure derived from NMR. The results show that Purple-clay materials have a higher percentage of pores in the 20–150 nm range compared to normal soil-based clay, providing quantitative evidence of their different porous architecture. Traditional clay preparation further increased the proportion of larger pores and produced a continuous pore size distribution. These results demonstrate that single-sided NMR can serve as an effective quantitative tool for evaluating the porous structures of Purple-clay and for distinguishing the material's provenance and preparation method.

References

Terenzi C, Casieri C, De Luca F. Two-dimensional nuclear magnetic resonance correlation maps as a signature of firing in iron-rich ceramics made from carbonatic raw clays. *APPLIED CLAY SCIENCE*. 2011;53(3):517-24.

Liao Z, Chen Y, Tzen J, Kuo P, Lee M, Mai F, et al. Effect of teapot materials on the chemical composition of oolong tea infusions. *JOURNAL OF THE SCIENCE OF FOOD AND AGRICULTURE*. 2018;98(2):751-7.

Yang C, Kong J, Yang J, Chu C, Wang X, Li Y. The study of crystal-phase composition and pore structure for Dicaoqing-Zisha compared with porcelain and pottery. CERAMICS INTERNATIONAL. 2021;47(8):10650-7.

Oleogel assembly and application: from a porous-media characterization to a biofertilizer technology

Isadora Fenerich Almeida¹, Yuri Fahl Santos¹, Daiane Bortolote Ferreira², Luisa Souza Almeida¹, Rodrigo Henrique dos Santos Garcia³, Cristiane Sanchez Farinas², Luiz Alberto Colnago⁴

¹Universidade de São Paulo (IQSC), ²Embrapa, ³Universidade de São Paulo (IFSC),
⁴Embrapa (instrumentation)

e-mail: isadorafenerich@usp.br

An oleogel is, by definition, a 3D structure created by incorporating a structuring agent, known as a gelator, which forms self-assembled structures via physical bonds, encapsulating a hydrophobic liquid. This enables the formation of a porous media containing micelle-like structures in its makeup, physically enclosing the oil within the structure. Time Domain Nuclear Magnetic Resonance is a versatile technique for material characterization, providing insights on its properties and structure. Although sequences of transversal relaxation measurements, such as CPMG, are commonly employed for this purpose in oleogel samples, longitudinal relaxation and Magic Sandwich Echo (MSE) techniques remains unexplored. These are valuable methods due to their ability to qualitatively and quantitatively access interactions, viscosity, and material structure. The present study enabled an oleogel structure and explored such sequences to characterize it. In addition, it tests an application of the final material as a biofertilizer for a bacterial biopesticide.

Using Ethylcellulose as structuring agent, it was possible to obtain a physical entanglement with the Soybean oil (SO) through hydrogen bonds. This enabled the organization of a gel-like porous material. It was observed a relationship between concentration increase and a progressive self-organized structure, with more brittle forms at even higher concentrations. The T1 and T2 sequences revealed a limitation in molecular mobility as the concentration increased, leading to the development of micelle-like structures. Conversely, the MSE successfully quantified the Rigid fraction (R_{if}) and detected an excess in the R_f, implying the immobilization of the SO. Meanwhile, when evaluating the feasibility of such material as an encapsulating agent for controlled release of *Bacillus thuringiensis* as biopesticide, it was possible to demonstrate its ability to extend cellular viability during both storage and field-application conditions.

Acknowledgements

This study was financed, in part, Conselho Nacional de Desenvolvimento Científico e Tecnológico - CNPq, project number #381526/2026-7, #404690/2023-8, #306611/2022-8, São Paulo Research Foundation (FAPESP), project number #2024/03278-4, #2025/00509-8, #2025/27385-7 and Fundação de Apoio à Pesquisa e ao Desenvolvimento (FAPED).

References

A.J. Gravelle, M. Davidovich-Pinhas, A.K. Zetzel, S. Barbut, A.G. Marangoni, Influence of

solvent quality on the mechanical strength of ethylcellulose oleogels, *Carbohydrate Polymers*, Volume 135, 2016, Pages 169-179, ISSN 0144-8617, <https://doi.org/10.1016/j.carbpol.2015.08.050>.

Cucinelli Neto RP, da Rocha Rodrigues EJ, Bruno Tavares MI. Proton NMR relaxometry as probe of gelatinization, plasticization and montmorillonite-loading effects on starch-based materials. *Carbohydr Polym*. 2018 Feb 15;182:123-131. doi: 10.1016/j.carbpol.2017.11.021. Epub 2017 Nov 6. PMID: 29279106.

Shanshan Li, Łukasz Łopusiewicz, Danila Merino, Mahmood Alizadeh Sani, Pratap Kalita, Swarup Roy, Tao Yang, Tao Fei, Wanli Zhang, High-performance ethyl cellulose composite films: Innovations in functional enhancement for sustainable food packaging, *Carbohydrate Polymers*, Volume 368, Part 2, 2025, 124154, ISSN 0144-8617, <https://doi.org/10.1016/j.carbpol.2025.124154>.

Two-Photon Confocal Microscopy for Simultaneous Three-Dimensional Characterization of Pore Architecture and the Spatial Distribution of Aromatic Molecules in Sedimentary Porous Rocks

Kevyn Reis de Souza¹, Agide Gimenez Marassi¹, Tito José Bonagamba², Francisco Eduardo Gontijo Guimarães³

¹Universidade de São Paulo (*Instituto de Física de São Carlos*) , ²Universidade de São Paulo (*São Carlos Institute of Physics*) , ³Universidade de São Paulo (*São Carlos Institute of Physics*)

e-mail: kevin.reis@usp.br

Understanding the spatial distribution and organization of aromatic organic matter within sedimentary reservoir rocks is essential for investigating fluid transport, wettability, and hydrocarbon recovery. Conventional techniques such as X-ray microtomography, electron microscopy, and nuclear magnetic resonance provide valuable structural information but offer limited insight into the molecular organization of aromatic compounds confined within pore networks. Here, we introduce two-photon confocal microscopy^{1,2} as a multimodal optical approach for the three-dimensional characterization of Berea sandstone and Bedford and Indiana limestone samples containing naturally occurring aromatic molecules such as asphaltenes. Near-infrared femtosecond excitation at 800 nm selectively excites aromatic chromophores through nonlinear absorption, generating fluorescence in the visible range while minimizing light scattering and enabling optical sectioning up to ~50 µm below the rock surface. Simultaneous hyperspectral imaging and fluorescence lifetime imaging microscopy (FLIM) provide an emission spectrum and fluorescence decay for every image pixel, allowing the spatial mapping of aromatic species with submicrometric resolution. Beyond molecular detection, spectral shifts, emission broadening, and fluorescence lifetime variations reveal differences in molecular organization and photophysical connectivity associated with local aromatic concentration and intermolecular interactions. In parallel, second harmonic generation (SHG) imaging identifies crystalline mineral phases within the pore walls, enabling the simultaneous visualization of the organic and inorganic fractions. The combination of hyperspectral imaging, FLIM, SHG, and three-dimensional optical sectioning establishes a unique multimodal platform for investigating pore architecture, mineral interfaces, and the supramolecular organization of aromatic compounds¹.

Acknowledgements

The authors acknowledge the support provided by: INCT FAPESP-CNPq, - grant numbers: 2025/26804-6, 408468/2024-6; FAPESP (Sao Paulo Research Foundation)—grant numbers: 2013/07276-1(CEPOF—CEPID Program), 2009/54035-4 (EMU multiuser facilities). This work was supported by the USP-COFECUB program, which funded collaborative exchanges between Brazilian and French laboratories. M.L.F.V. acknowledges financial support.

References

1. Maria L. F. Vicente, Jeanne Blanchet, Mariana M. Veras, Dominique Jamet, Jean-Louis

Jamet, Stéphane Mounier, Houssam Hajjoul, and Francisco E. G. Guimarães, Label-Free Two-Photon Spectral Microscopy to Track Black Carbon Fate in Live Copepod. *Environmental Science & Technology* 2026 60 (22), 16135-16145 DOI: 10.1021/acs.est.5c18449;

2. Bové, H. et al. Biocompatible Label-Free Detection of Carbon Black Particles by Femtosecond Pulsed Laser Microscopy. *Nano Lett* 16, 3173-3178 (2016).

Water Absorption and Dynamics in 11th Century Wall Paintings: Assessing Surface Treatments via NMR Profiling

Leonardo Conti¹, Carlo Golini¹, Guojun Xu¹, Sylvie Cheney², Leonardo Brizi¹

¹Università di Bologna (*Department of Physics and Astronomy "Augusto Righi"*) , ²Autonomous Region of Valle d'Aosta (*Department of Cultural Heritages and Activities*)

e-mail: leonardo.conti8@unibo.it

In-situ NMR depth profiling for cultural heritage purposes is an expanding field¹ due to its advantages over most other techniques which are limited to surface analysis. Specifically, when investigating the water absorption properties of surfaces, NMR can directly characterize both water content and its kinetics^{2,3} using portable and low-cost equipment.

This study investigated 11th century wall paintings in the Collegiate Church of St. Pietro and Orso in Aosta via single-sided NMR depth profiling, using an NMR-MOUSE PM10 ($B_0 = 0.327$ T) mounted on a micrometric precision lift. This work aimed to evaluate and compare the removal of hydrophobic coatings using methyl ethyl ketone (MEK) applied via two innovative electrospun tissues. Eight measurement spots were selected to account for potential variations in the cleaning process caused by pigment composition and uneven coating distribution.

Before and after treatment, each spot was profiled three times using CPMG sequences after moistening with a spray dispenser. The first profile, acquired immediately after spraying, was used to set the depth range for the subsequent profiles, which were acquired after 20 and 40 minutes. Noise profiles were collected to filter the signal, along with a weighted moving average between subsequent profile points. The analysis focused on the cumulative profiles and their slopes, which respectively represent the total water content and its spatial distribution.

Both cleaning methods were confirmed to remove the hydrophobic coating, given that faster water transport was observed. The analysis also showed one carrier tissue predominantly increasing the total volume of water penetrating the wall surface, whereas the other promoted a more homogeneous spatial distribution. These results confirm single-sided NMR as a powerful tool to investigate the structure of porous media of interest to cultural heritage whose standardization would lead to procedures accessible to non-NMR experts.

References

Rehorn, C., & Blümich, B. (2018). Cultural heritage studies with mobile NMR. *Angewandte Chemie International Edition*, 57(25), 7304-7312.

Golini, C., Yang, Q., Waldecker, M., Lenz, R., Brizi, L., Haber-Pohlmeier, S., ... & Heimerl, F. (2026). Investigation of the late-Roman burial chamber at Reichertsberg in Trier by NMR

depth profiling. Solid state nuclear magnetic resonance, 102074.

Di Tullio, V., Sciutto, G., Proietti, N., Prati, S., Mazzeo, R., Colombo, C., ... & Capitani, D. (2018). ^1H NMR depth profiles combined with portable and micro-analytical techniques for evaluating cleaning methods and identifying original, non-original, and degraded materials of a 16th century Italian wall painting. *Microchemical Journal*, 141, 40-50.

Water dynamics and structural evolution in silicate-based porous media: from solutions to colloidal gels probed by dynamic NMR relaxometry

Sidi-Boulenouar¹, Benjamin Maillet², Arnaud Poulesquen³

¹Gustave Eiffel University (*Laboratoire Navier*) , ²Laboratoire Navier (*Université Gustave Eiffel*) , ³CEA

e-mail: rahima.sidi-boulenouar@univ-eiffel.fr

Understanding water dynamics in porous media, from reactive solutions to consolidated gels, is essential for predicting transport, aging, and stability in natural and engineered materials. However, capturing these processes under non-equilibrium conditions across relevant time and length scales remains challenging.

In this work, we develop and apply a dynamic low-field NMR relaxometry framework to investigate water dynamics and structural evolution in silicate-based systems, spanning from alkaline solutions to deformable colloidal gels.

We first investigate aqueous alkali silicate solutions to quantify changes in water mobility and interfacial interactions as a function of hydroxide concentration and alkali nature. Transverse relaxation measurements show that NMR relaxometry provides a sensitive probe of solution speciation and early-stage mesoscale organization, even prior to gel formation.

We then extend this approach to drying colloidal and aluminosilicate gels, where water transport is coupled to deformation, gradient formation, and network reconfiguration. By tracking transverse relaxation times (T_2) as a function of saturation, and combining bulk measurements with one-dimensional spatial water profiles, we identify power-law relationships linking relaxation efficiency and desaturation. These relationships reveal distinct drying regimes and enable discrimination between homogeneous and instability-driven drying.

A minimal numerical framework is introduced to separate the contributions of gradient development, macroscopic contraction, and particle network reconfiguration. Overall, this work establishes NMR relaxometry as a unified, non-destructive tool to probe water dynamics in evolving porous media.

References

Poulesquen, A., Rodrigues, D. G., Sidi-Boulenouar, R., Maillet, B., Goze-bac, C., & Petit, D. (2026). Comprehensive Structural and Dynamical Study of Alkali Silicate Solutions: Influence of Hydroxide Concentration and Alkali Nature. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 139622.

Maillet, B.; Sidi-Boulenouar, R.; Coussot, P. Dynamic NMR Relaxometry as a Simple Tool for

Measuring Liquid Transfers and Characterizing Surface and Structure Evolution in Porous Media. *Langmuir* 2022, 38 (49), 15009-15025. <https://doi.org/10.1021/acs.langmuir.2c01918>.

Sidi-Boulenouar, R. et al. submitted — Dynamic NMR Relaxometry Highlights Drying-Induced Heterogeneity and Structural Reconfiguration in Colloidal Gels, *Langmuir*, 2026.

Magnetic Resonance in Porous Media 2026



Grouperment
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

05

Mobile NMR

POSTER PRESENTATION



RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026

Designing and Shimming Halbach Array Magnets: A Historical Perspective with Modern Implications

Andrew McDowell¹, Robert Lown¹

¹NuevoMR, LLC

e-mail: mcdowell@nuevomr.com

Most magnetic resonance practitioners developing or using array (or ring) magnets refer to them as “Halbachs” and almost always reference Klaus Halbach’s 1980 paper. However, evidence suggests that modern workers rely heavily on magnetic field simulation software and are largely unaware of most of the theoretical results in the paper. This may be due to the terse presentation of the unfamiliar complex-valued techniques used by Halbach.

Even more under-utilized is the work of Bob Gluckstern from the mid-1980s. He developed methods for calculating and mitigating the effects of finite length in these magnets. Unfortunately, his results are publicly available only in abbreviated and cryptic form in a patent. The details of Gluckstern’s work are known only to those who worked directly with him.

The early work of Halbach and Gluckstern was done mostly with pencil and paper. It is rich with insights that may be obscured by computer simulations and calculations. We continue to use the techniques to design and build magnets, and it strikes us that familiarity with these 40-year-old results would be beneficial to modern magnet designers, especially those seeking higher homogeneity.

To that end, we present the nearly lost theory in some detail. We work a number of practical examples and discuss implications for magnet design projects. We hope that even those who are not currently designing magnets will recognize the importance and value of acknowledging the giants of our field.

References

A.F. McDowell and R.R. Lown, "Designing and shimming Halbach Array magnets", JMR Open, submitted.

Revisiting Shim-a-Ring Magnets for Improved B Homogeneity

Shin Utsuzawa¹

¹Schlumberger

e-mail: sutsuzawa@slb.com

Halbach magnet assemblies are widely used in NMR to generate strong static magnetic fields with good field homogeneity within the sample region while minimizing external stray fields [1]. In practice, these assemblies are realized using multiple discrete magnet segments with prescribed orientations [2], leading to significant fabrication complexity, sensitivity to tolerances, and bulky structures.

The “shim-a-ring” magnet [3] provides a simpler alternative based on a single diametrically magnetized ring and a concentric ferromagnetic shim. The induced magnetization of the shim follows the spatial field distribution of the ring, resulting in an effective continuous angular variation analogous to an ideal Halbach configuration. This architecture supports straightforward, self-aligned assembly without the need for precision placement of multiple magnets. Despite these advantages, the shim-a-ring approach is constrained by limited degrees of freedom for shaping the magnetic field, which can restrict achievable field homogeneity compared to discretized assemblies.

In this study, we extend the shim-a-ring concept by introducing refined configuration strategies that improve control of the magnetic field distribution while preserving simplicity and compactness. Representative analyses demonstrate that enhanced ring-based designs can achieve improved field homogeneity without the complexity of multi-element magnet assemblies, supporting the development of practical permanent magnet solutions for compact NMR systems.

References

- E. Danieli, et al., Journal of Magnetic Resonance, 198: 80-87 (2009).
- P. Blümler and H. Soltner, Applied Magnetic Resonance, 54: 1701-1739 (2023).
- P. Nath, et al., Applied Physics Letters, 102: 202409 (2013).

TD-NMR in Semicrystalline Polymers: Morphology and Dynamics

Valeriia Baranauskaite^{1,2}, Mariia Ivanova¹, Erkki Lähderanta³, Leonid Grunin¹

¹Resonance Systems, ²Lappeenranta-Lahti University of Technology (*Department of Physics*) ,
³Lappeenranta-Lahti University of Technology

e-mail: v.baranauskaite@resonance-systems.de

Time-Domain NMR (TD-NMR) is particularly well suited for probing phase composition, molecular mobility, and nanoscale morphology in semicrystalline solids due to the dominance of the dipole-dipole interactions. TD-NMR is especially valuable for investigation of structurally complex systems, composed of phases with distinct molecular mobility. In this work, commodity polymers (polyethylene and polypropylene) with various crystallinities are investigated using several TD-NMR experiments over a wide range of temperatures. The analysis of the FID and related sequences based on the second-moment approximation allowed identification of thermal regions with uniform relaxation behavior. The temperature dependence of the spin-lattice relaxation revealed characteristic extrema associated with different motional regimes, from localized side-group reorientations to cooperative segmental chain dynamics. Additionally, the double-quantum and multiple-quantum NMR experiments were used to gain information about the structural heterogeneity obtained from distributions of residual dipolar couplings, which reflect local motional restrictions of crystalline and amorphous phases.

Finally, the nanoscale morphology was characterized by spin diffusion experiments, which probe magnetization transfer between domains of different mobility. Using data from DQ experiments, we demonstrated the possibility to estimate domain sizes while avoiding spectral deconvolution.

Overall, the utilization and analysis of variety of available TD-NMR techniques provide a unified, model-free framework for describing crystallinity, molecular mobility, and phase morphology in semicrystalline polymers. TD-NMR thus delivers comprehensive structural and dynamic information across multiple time and length scales in complex polymer systems.

Acknowledgements

Funded by the European Union

Horizon Europe (HORIZON)
Marie Skłodowska-Curie Actions
Doctoral Networks (MSCA-DN)
HORIZON-MSCA-DN-2021
Grant Agreement: 101072758

References

- L. Grunin, M. Ivanova, V. Schiraya and T. Grunina, *Appl. Magn. Reson.*, 2023, 54, 929–955.
- K. Saalwächter, *Modern Magnetic Resonance*, Springer Int. Publ., 2018, 755–781.
- V. M. Litvinov, O. Persyn, V. Miri and J. M. Lefebvre, *Macromolecules*, 2010, 43, 7668–7679.

Magnetic Resonance in Porous Media 2026



Groupement
AMPERE

17th International Bologna Conference on
Magnetic Resonance in Porous Media

SECTION

06

Advances in Mathematics, Engineering, AI, and Quantum Computing

POSTER PRESENTATIONS

RIBEIRÃO PRETO & CAMPINAS, BRAZIL
OCTOBER 26–30, 2026

Acoustic Techniques for Porosity Analysis in Petroleum Reservoir Sandstones

João Henrique Uliana¹, Guilherme A. Braz¹, Mateus Mota Moraes², Everton Lucas-Oliveira³, Arthur Gustavo de Araujo Ferreira⁴, Willian Andrighetto Trevizan⁵, Carlos Alberto Fortulan², Theo Z. Pavan⁶, Tito José Bonagamba⁴, Antônio Adilton Oliveira Carneiro⁶

¹Fundação Instituto Polo Avançado da Saúde de Ribeirão Preto (*Supera Centro de Tecnologia*) , ²São Carlos School of Engineering - University of São Paulo (*Mechanical Engineering*) , ³Brazilian Center for Research in Energy and Materials (*Brazilian Synchrotron Light Laboratory (LNLS)*) , ⁴São Carlos Institute of Physics - University of São Paulo, ⁵Petroleo Brasileiro SA (*Cenpes*) , ⁶Universidade de São Paulo

e-mail: joaohenriqueuliana@yahoo.com.br

The characterization of oil reservoir rocks is critical for the petroleum industry, as porosity, permeability, and mineral composition directly determine fluid storage and flow. Conventional methods like scanning electron microscopy, X-ray diffraction, X-ray microtomography, and nuclear magnetic resonance are accurate but costly, slow, and complex. To address this, the research investigated photoacoustic microscopy (PAM) and vibroacoustography (VA) for sandstone rocks. PAM uses pulsed laser absorption to generate acoustic waves encoding optical and mechanical properties. Using a 532 nm laser, PAM images of 11 sandstones were acquired, with porosity from 18.8 to 32.8% and pore radii from 6 to 60 μm . Signal intensity was compared with photographs to identify mineral regions. Brighter PAM regions corresponded to higher absorption, and k-means clustering achieved Lin's concordance of 0.972. Frequency analysis showed mean frequency correlated with pore radius (Spearman -0.81, R^2 0.80), while porosity correlation was weaker (-0.41, R^2 0.26), indicating pore dimensions dominate acoustic response. VA is based on nonlinear interaction of two confocal ultrasound beams at different frequencies, generating lowfrequency signals sensitive to stiffness and porosity. Experiments on alumina ceramics (5-30% porosity) showed linear VA amplitude increase in the 82-85 kHz band. For sandstones, VA followed this trend, except Berea and Boise due to mineralogical differences, revealing sensitivity to heterogeneity. VA images also showed hot spots in porous samples, suggesting mechanical variations. Both techniques are non-contact, lowcost, and operate in reflection mode, suitable for field use. However, reservoir heterogeneities over centimeters to meters scales mean small plugs may not represent bulk formations without upscaling. The findings demonstrate that PAM and VA are promising complementary tools for porosity estimation and morphological analysis of reservoir rocks.

Acknowledgements

This study was financed, in part, by Petrobras, Brazil (Process No. 2020/00010-0), and by the São Paulo Research Foundation (FAPESP, process No. 2018/16939-8)

References

Lucas-Oliveira E, Araujo-Ferreira AG, Trevizan WA, dos Santos BC, Bonagamba TJ (2020) Sandstone surface relaxivity determined by NMR T2 distribution and digital rock simulation for permeability evaluation. J Petrol Sci Eng 193:107400. <https://doi.org/10.1016/j.petrol.2020.107400>

Uliana, J. H., Trevizan, W. A., Carneiro, A. A. O., Oliveira, E. L., Pavan, T. Z., Ferreira, A. A., & Bonagamba, T. J. (2026). Photoacoustic microscopy of sandstone reservoirs rocks. 10.1109/IUS51837.2023.10308378

Uliana, J. H., Braz, G. A., Oliveira, E. L., Araújo-Ferreira, A. G., Morais, M. M., Trevizan, W. A., Fortulan, C. A., Bonagamba, T. J., Pavan, T. Z., & Carneiro, A. A. O. (2024). Investigation of rock porosity using vibroacoustography. Journal of the Brazilian Society of Mechanical Sciences and Engineering, *46*(585), 1-11. <https://doi.org/10.1007/s40430-024-05141-0>

An NMR Platform for Quantum Computing

Ygor de Castro Lourenço¹, Gabriel Henrique Maranzatto², Arthur Gustavo de Araujo Ferreira³, Alexandre Ferreira Ramos⁴, Edson Vidoto¹, Aparecido Donizeti Fernandes de Amorim¹, Tito José Bonagamba¹

¹São Carlos Institute of Physics - University of São Paulo, ²Institute of Geosciences and Exact Sciences, São Paulo State University, ³National Service for Industrial Training - São Paulo, ⁴School of Arts, Sciences, and Humanities, University of São Paulo

e-mail: ygorcl@usp.br

NMR remains one of the most versatile techniques for demonstrations of quantum computing. In this work, we present Ugly-Cat, an experimental-computational platform utilizing the quadrupolar coupling of ^{23}Na nuclei in a liquid crystal sample placed in a 9.4T magnet. (1,2) The four energy levels of this quadrupolar nucleus directly form a 2-qubit Hilbert space, without requiring multiple coupled spins. Starting from thermal equilibrium, the computational basis states are prepared using strongly modulated rf pulses (3). These pulses are numerically optimized by varying the amplitude and phase while incorporating the quadrupolar Hamiltonian into the optimization to achieve high-fidelity state preparation. Similarly, the components of the universal set of quantum gates, such as Hadamard gates, are prepared using the same rf pulse optimization approach to generate, for example, the entangled states required for the implementation of basic quantum algorithms. The platform also simulates the time evolution of the quantum system, enabling prediction of the quantum states produced by any pulse sequence. These states can be experimentally reconstructed using quantum state tomography (2), which yields the full density matrix and allows the fidelity of the implemented quantum operations to be quantified. The entire pipeline is integrated into a graphical user interface (GUI) where users can draw arbitrary 2-qubit circuits. The system automatically compiles these circuits into rf pulse sequences, executes them on the spectrometer, and displays the experimentally reconstructed state alongside the simulated prediction, making the platform highly accessible to non-NMR experts. The same architecture is being extended to a 3-qubit system using ^{133}Cs nuclei in a liquid crystal sample. As a next step, we aim to advance quantum computing methods for signal processing, targeting future applications in porous media using in-house NMR systems or higher-qubit commercial quantum processors.

Acknowledgements

The authors gratefully acknowledge the support provided by USP, FAPESP, CNPq, CAPES.

References

Oliveira, I.S.; Sarthour, R.S.; Bonagamba, T.J.; Azevedo, E.R.; Freitas, J.C.C. NMR Quantum Information Processing. Amsterdam: Elsevier, 2007.

Araújo-Ferreira, A.G.; Brasil, C.A.; Soares-Pinto, D.O.; Azevedo, E.R.; Bonagamba, T.J.;

Teles, J. Quantum state tomography and quantum logical operations in a three qubits NMR quadrupolar system. *International Journal of Quantum Information*, v. 10, n. 2, p. 1250016, 2012.

Fortunato, E.M. Design of strongly modulating pulses to implement precise effective Hamiltonians for quantum information processing. *Journal of Chemical Physics*, v. 116, n. 17, p. 7599-7606, 2002.

Deep Learning Analysis of T1-Weighted MRI for Characterizing Vertebral Fragility

Juliana Giurlani¹, Marcello Henrique Nogueira-Barbosa¹

¹Universidade de São Paulo (CCIFM - COORDENADORIA DE CIÊNCIA DA IMAGEM E FÍSICA MÉDICA)

e-mail: becjuliana@gmail.com

Introduction: Bone strength transcends mineral density, depending on trabecular microarchitecture and marrow adipose tissue. While DXA is the standard for osteoporosis diagnosis, its 2D projection often misclassifies fracture risks. MRI offers a non-invasive 3D evaluation of the bone's porous media. We investigate the computational analysis of T1-weighted lumbar spine MRI using Convolutional Neural Networks (CNNs) to identify bone fragility.

Methods: A dataset of 1,773 vertebral body images was extracted from T1-weighted MRIs of 59 females. Patients were stratified by DXA and fracture history: Normal, Osteopenia (with/without fracture), and Osteoporosis (with/without fracture). After applying Contrast Limited Adaptive Histogram Equalization (CLAHE), we evaluated CNN architectures (ResNet50, MobileNetV2, VGG16). VGG16 with partial fine-tuning was selected to extract high-frequency spatial patterns representing trabecular disorganization and fat infiltration.

Results: VGG16 demonstrated superior performance in capturing the textural signature of the porous tissue. In binary classification, it distinguished normal bone integrity from osteoporotic fragility with an AUC of 1.00. Crucially, it revealed a phenotypic convergence: images of osteopenic patients with fragility fractures shared the exact visual and textural patterns of severe osteoporosis. PCA of the latent space confirmed this, polarizing samples into distinct extremes (Integrity vs. Fragility Signatures).

Conclusion: CNN-based MRI texture analysis captures the structural quality of the porous trabecular network, prioritizing biological risk over pure densitometry. VGG16 applied to routine T1-weighted MRIs acts as a sensitive complementary biomarker, offering a pathway for automated opportunistic screening of vertebral fragility.

References

Li, W., Wang, W., Zhang, M., Chen, Q., & Li, S. (2024). Associations of marrow fat fraction with MR imaging based trabecular bone microarchitecture in first-time diagnosed type 1 diabetes mellitus. *Frontiers in Endocrinology*, 15. <https://doi.org/10.3389/fendo.2024.1287591> Cited by: 4

Soldati, E., Rossi, F., Vicente, J., et al. (2021). Survey of MRI Usefulness for the Clinical Assessment of Bone Microstructure. *International Journal of Molecular Sciences*, 22, 2509. <https://doi.org/10.3390/ijms22052509> Cited by: 33

Yeh, L.-R., Zhang, Y., Chen, J.-H., et al. (2022). A deep learning-based method for the diagnosis of vertebral fractures on spine MRI: retrospective training and validation of ResNet. *European Spine Journal*, 31, 2022-2030. <https://doi.org/10.1007/s00586-022-07121-1> Cited by: 69

Ugly Cat, a computational system for Quantum Information processing based on NMR

Alexandre Ferreira Ramos¹, Jaime Cavalcanti Guedes¹, Ygor de Castro Lourenço², Radija Ingrid Silva¹, Lucas Carvalho Simionato³, Vinicius Oliveira da Silva¹, Suzylaine da Silva Lima¹, Carlos Augusto Roque³, Arthur Gustavo de Araujo Ferreira³, Tito José Bonagamba²

¹School of Arts, Sciences, and Humanities, University of São Paulo, ²São Carlos Institute of Physics - University of São Paulo, ³National Service for Industrial Training - São Paulo

e-mail: alex.amos@usp.br

A modular computational platform, denoted Ugly Cat, for operating the NMR-based Quantum Information processing machine developed by LEAR [1], is presented. The integrative core of Ugly Cat platform orchestrates the dynamics of the modules required for operating the Quantum Computer, for producing radiofrequency (rf) pulses necessary for the creation of quantum states, and for feeding the visual interface. A module based on Krotov algorithm for quantum control produces rf pulses of specific intensity, duration, and phase to generate initial states or logic gates in the Quantum Computer.

The Hamiltonian used to define the control consists on coupling the nuclear spin with the external fields through: (i) the Zeeman interaction (dominant term); (ii) the quadrupolar interaction (time-independent perturbation); (iii) the radio-frequency pulses (time-dependent perturbation). The propagator is used to compute spin system time evolution under the aforementioned interactions.

A module for translating rf pulses into commands for an NMR console was developed. A module for visual interface (based on Quirk package [2]) enables drag-and-drop design of quantum circuits along with their respective simulation and experimental evaluation in a NMR-based Quantum Computer.

A module translating the output of the NMR machine into visualizable quantum states was produced.

The modular structure of our platform allows it to be adapted for operation with any NMR spectrometer console, as well as other classes of Quantum Computers, including those based on Nuclear Quadrupolar Resonance (NQR) [3].

As the next step, our research groups will advance quantum computing protocols to improve signal processing, utilizing the two- and three-qubit NMR/NQR systems we have developed.

Acknowledgements

The authors gratefully acknowledge the support provided by USP, FAPESP, CNPq, CAPES.

References

[1] <https://ifsc-lear.weebly.com/>

- [2] M. Haghparast, R. Heikkinen, S. Ovaskainen, J. Fuchs, J.P.P. Jokinen and T. Mikkonen, Quirk-E quantum circuit simulator: Integrated tool for quantum algorithm development, *SoftwareX*, 32, 102383 (2025)
- [3] J. Teles, C. Rivera-Ascona, R.S. Polli, R. Oliveira-Silva, E.L.G. Vidoto, J.P. Andreeta and T.J. Bonagamba, Experimental implementation of quantum information processing by Zeeman-perturbed nuclear quadrupole resonance. *Quantum Inf Process* 14, 1889–1906 (2015).

Author Index

17th International Bologna Conference on Magnetic Resonance in Porous Media

AUTHORS A-Z

247 AUTHORS / 389 AUTHOR CREDITS

A

Abrão, Pedro Cesar Rodrigues Alves	59, 96, 116
Acosta, Rodolfo	19, 37, 68
Afonso, Ricardo José da Silva	124
Afrough, Armin	42
Alfonso, JORGE LUIZ Gonzalez	90
Alfonzo, José Alejandro Moreno	94
Almeida, Isadora Fenerich	139
Almeida, Luisa Souza	139
Altenhof, Adam	24
Alves, Caroline Cassia	126
Amorim, Aparecido Donizeti Fernandes de	34, 126, 155
Ananiadou, Antonela	103
Anedda, Roberto	110
Angulo, Sérgio Cirelli	113
Anoardo, Esteban	26
Araujo, Wagner W. R.	13
Archilha, Nathaly Lopes	10, 89, 118
Arif, Muhammad Zulqarnain	101
Arns, Christoph	3, 5
Artaxo, Paulo	39
Asad, Humna	30, 115
Atzingen, Gustavo Voltani Von	120
Augustine, Matthew P	33
Aum, Lorena Cardoso Batista	8
Aum, Pedro Tupã Pandava	8
Azeredo, Rodrigo Bagueira de V. de	94
Azevedo, Eduardo Ribeiro de	23, 62, 99, 104, 107, 116
Azevedo, Mariana Teixeira de	4

B

Balcom, Bruce	24, 48, 106
Baranauskaite, Valeriia	150
Barbieri, Fiamma	68
Baroncha, Georgiy	14, 112
Baruffaldi, Fabio	46
Basser, Peter	27
Bermudez, Silvia Lorena Bejarano	91, 92
Berni, Matteo	46
Bertizzolo, Emanuel Gpmes	72
Bez, Luiz Fernando	7, 15, 88
Bluemich, Bernhard	67
Bonagamba, Tito José	8, 21, 34, 59, 76, 86, 89, 109, 113, 116, 118, 122, 126, 135, 141, 153, 155, 159
Bondarenko, Niktia	24
Bortolotti, Villiam	51, 110
Bradt Müller, Henrik	122
Braz, Guilherme A.	153
Brizi, Leonardo	11, 44, 46, 51, 73, 109, 110, 137, 143

C

Cai, Teddy	27
Campos, Nataly Melo	122
Cardarelli, Paolo	46
Cardinali, Marcelo Camponez do Brasil	120
Carneiro, Antônio Adilton Oliveira	131, 153
Carozzi, Alessandro	44
Carvalho, Marcio	81
Castello, Daniel	15
Cavallo, Carola	46

Author Index

17th International Bologna Conference on Magnetic Resonance in Porous Media

AUTHORS A-Z

247 AUTHORS / 389 AUTHOR CREDITS

Cavallo, Maddalena	44
Cesar, Reinaldo	131
Chapiro, Grigori	80
Chávez, Sinai Morales	76, 77, 86
Cheney, Sylvie	143
Chiarini, Alessandro	44
Cid, Mariana Paula	37
Cipriano, Daniel Fernandes	129
Clasen, Christian	103
Coelho, Antonio Carlos Vieira	113
Colnago, Luiz Alberto	99, 139
Colombo, Paolo	135
Comín, Romina	37
Constante, Luis	76, 77
Constante, Luis G.	86
Conti, Leonardo	46, 109, 137, 143
Correa, Paulo Cesar de Mello	129
Costa, Anderson Augusto da Silva	91, 92
Cousot	25
Coutinho, Bernardo	34
Coutinho, Henrique Yan de Seta	88
Cruz, Alessandro dos Santos Evangelista da	4, 90
Cunha, Alessander Marciano da	7, 88

D

Damholt, Zacharias Brimnes Visby	42
Derakhshandeh, Hamed	70
Domené, Esteban A.	19
Dorst, Diane Damaris	99

E

El Bakkali, Imane	32
-------------------	----

Estrada, Flavia Regina	53
Exposito, Caio Cesar Dente	126

F

Fantoni, Simone	46
Farinas, Cristiane Sanchez	139
Fernández, Pablo Andrés	37
Ferrari, Lucia	51, 110
Ferreira, Amanda Iglessias	53
Ferreira, Arthur Gustavo de Araujo	21, 34, 59, 89, 153, 155, 159
Ferreira, Daiane Bortolote	139
Fleury, Marc	17
Foerster, Bernd Uwe	8
Fognani, Roberta	46
Fortes, Gustavo Mattos	126
Fortulan, Carlos Alberto	135, 153
Freitas, Jair C. C.	129
Fridjonsson, Einar	58, 72

G

Galvosas, Petrik	30, 115
Garcia, Rodrigo Henrique dos Santos	99, 104, 107, 139
Gervais, Christel	32
Giurlani, Juliana	157
Golini, Carlo	143
Goncalves, Danielle Santos	53
Greenbaum, Steven	101
Grunin, Leonid	150
Guedes, Jaime Cavalcanti	159
Guimarães, Francisco Eduardo Gontijo	141
Gurgel, Leandro Vinícius Alves	99

Author Index

17th International Bologna Conference on Magnetic Resonance in Porous Media

AUTHORS A-Z

247 AUTHORS / 389 AUTHOR CREDITS

H

Holand, Daniel	30, 115
Huang, Guantao	137
Huster, Daniel	49

I

Imel, Adam	101
Innocentini, Murilo Daniel de Mello	134
Ivanova, Mariia	150

J

Jiang, Minchuan	12
John, Vanderley M.	59, 60, 96, 116

K

Kirch, Alessandro	13
Kong, Xiang-Zhao	24
Kozlovskaya, Elena	70
Kuder, Tristan A.	115

L

Lafon, Olivier	32
Lähderanta, Erkki	150
Landi, Germana	110
Laurencin, Danielle	32
Le, Tien Dung	12
Leiderman, Ricardo	7, 15, 88, 94
Li, Rupeng	3
Lima, Feliipe Carvalho Pombo	88
Lima, Suzylaine da Silva	159
Lima Neto, Antonio Barbosa de	118
Linck, Yamila Garro	19, 68

Liu, Yuting	137
Lopes, Pedro Cortez Fetter	7
Lourenço, Ygor de Castro	155, 159
Lown, Robert	148
Lucas, Cláudio Regis dos Santos	8
Lucas-Oliveira, Everton	21, 34, 89, 118, 122, 153
Lunardi, Monique Palavro	96, 113

M

Maillet	25
Maillet, Benjamin	145
Mamani, Vladivostok F. S.	13
Maranzatto, Gabriel Henrique	155
Marassi, Agide Gimenez	21, 34, 109, 113, 116, 126, 141
Martin-Neto, Ladislau	64
Marull, Patricio Díaz	68
Masiero, Diana M.	19
Matern, Philipp	115
Maurício, Júnior Cintra	53
Mavridis, Aristarchos	18, 103
McDowell, Andrew	66, 148
Métro, Thomas-Xavier	32
Miranda, Caetano Rodrigues	13
Monti, Gustavo A.	19, 68
Moraes, Tiago Bueno de	120
Morais, Mateus Mota	135, 153
Morin, Devin	24
Moyne, Christian	12
Murad, Marcio	12
Murback Filho, Renato Pereira	104, 124
Muzzi, Andreas	88

Author Index

17th International Bologna Conference on Magnetic Resonance in Porous Media

AUTHORS A-Z

247 AUTHORS / 389 AUTHOR CREDITS

N

Nadol, Athulya	32
Nagmutdinova, Anastasiia	51, 110
Nascimento, Moacyr	4, 78, 90
Nascimento Neto, Moacyr do	34
Niasse, Yaye	32
Nobre, Thiago Ricardo Santos	113
Nogueira-Barbosa, Marcello Henrique	157
Novotnt, Etelvino Henrique	62

O

Oliveira, Emanuele Amorim	107
Oliveira, Ivan S.	4, 84, 90
Oliveira Junior, Marcos de	104, 124
Olivera, María Eugenia	68

P

Paiva, Fernando Fernandes	8
Pajander, Jari Pekka	42
Papoti, Daniel	109
Paranhos, Caio M.	99
Pavan, Theo Z.	153
Pel, Leo	55
Pereira, André Maués Brabo	7, 15, 88, 94
Pereira, Luis Augusto	116, 126
Pérez, Anilet Cabrer	96
Pires, Adolfo Puime	76, 77, 86
Poulesquen, Arnaud	145
Pourpoint, Frederique	32

R

Rahause, Crina	14, 112
Ramos, Alexandre Ferreira	155, 159
Ribeiro, Flaviana Campos Pamplona	124
Riley, Isabella Maria	18
Rocha, Arthur Costa Poyares	15, 88
Rodella, Cristiane Barbieri	53
Roque, Carlos Augusto	159

S

Saar, Martin	24
Sakellariou, Dimitrios	18, 36, 103
Santos, Maria de Fatima Costa	118
Santos, Yuri Fahl	139
Sarthour, Roberto	4
Schettino Jr., Miguel Ângelo	129
Sebastião, Pedro José	101
Sequeiros, Gerónimo	19
Shikhov, Igor	3, 5
Shu, Wanru	137
Sidi-Boulenouar	25, 145
Silva, Antonio José Roque da	40
Silva, João	118
Silva, Radija Ingrid	159
Silva, Rodrigo de Oliveira	18, 103
Silva, Vinicius Oliveira da	159
Simionato, Lucas Carvalho	159
Skibsted, Jørgen	57
Smeulders, David	55
Song, Yi-Qiao	43, 54
Souza, Alexandre Martins	4

Author Index

17th International Bologna Conference on Magnetic Resonance in Porous Media

AUTHORS A-Z

247 AUTHORS / 389 AUTHOR CREDITS

Souza, Andre Alves de	15, 91, 92, 94
Souza, Giselle de Araujo Lima e	101
Souza, Gustavo Henrique Freitas de	116
Souza, Kevyn Reis de	141
Souza Filho, Manoel Vicente de	94
Stael, Giovanni Chaves	91, 92, 94
Steiner, Mathias B	83
Stemmelen, Didier.	12
Surmas, Rodrigo	89

T

Tagliaferro, Frederico Possato	131
Telkki, Ville-Veikko	70
Testa, Claudia	44, 46, 51
Tolentino, Helio Cesar Nogueira	2
Torrez, Alvaro	13
Tosin, Giancarlo	118
Trebbi, Bruno	99, 104, 107, 116
Trevizan, Willian Andrighetto	21, 34, 41, 89, 153

U

Uehara, Márcio Kenji	109
Uliana, João Henrique	131, 153
Utsuzawa, Shin	149

V

Valiullin, Rustem	14, 112
Velasco, Manuel Isaac	19, 37
Vidoto, Edson	21, 34, 109, 118, 155
Viera, Martin Alberto Diaz	76, 77, 86
Volkringer, Christophe	32
Vosegaard, Thomas	42

W

Williamson, Nathan	27
--------------------	----

X

Xu, Guojun	137, 143
------------	----------

Y

Yan, Peiyuan	106
Yuan, Feng	137

Z

Zama, Fabiana	110
Zawodzinski, Thomas	101
Zhang, Yingli	29
Zhivonitko, Vladimir V.	70